

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **Loxeal 56-03**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

1.3. Details of the supplier of the safety data sheet

Name **LOXEAL S.R.L.**
Full address **Via Marconato 2**
District and Country **20811 Cesano Maderno (MB) Italia**
Tel. **+390362529301**
Fax **+390362524225**
e-mail address of the competent person responsible for the Safety Data Sheet **info@loxeal.com**

1.4. Emergency telephone number

For urgent inquiries refer to
BELGIUM: 070 245 245
MALTA: Ministry for Health - 2122 4071
IRELAND: 01 809 2566 (24/7) or 01 809 2166 (7 days/week, 8am-10pm)

CHEMTREC UK: +(44)-870-8200418
CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Warning**

SECTION 2. Hazards identification ... / >>

Hazard statements:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.

Precautionary statements:

P280	Wear protective gloves / protective clothing / eye protection / face protection.
P302+P352	In case of contact with the skin: wash abundantly with soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains:

CUMYL HYDROPEROXIDE
2-HYDROXYETHYL METHACRYLATE
TETRADECYL METHACRYLATE
dodecyl methacrylate

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
dodecyl methacrylate		
INDEX 607-247-00-9	$10 \leq x < 30$	STOT SE 3 H335
EC 205-570-6		STOT SE 3 H335: $\geq 10\%$
CAS 142-90-5		
REACH Reg. 01-2119489778-11-XXXX		
2-HYDROXYETHYL METHACRYLATE		
INDEX 5	$5 \leq x < 10$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317
EC 212-782-2		
CAS 868-77-9		
REACH Reg. 01-2119490169-29-XXXX		
TETRADECYL METHACRYLATE		
INDEX 1	$1 \leq x < 5$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335
EC 219-835-9		
CAS 2549-53-3		
REACH Reg. 01-2119489775-17-XXXX		
CUMYL HYDROPEROXIDE		
INDEX 617-002-00-8	$1 \leq x < 2,5$	Org. Perox E H242, Acute Tox. 3 H331, Acute Tox. 4 H302, Acute Tox. 4 H312, STOT RE 2 H373, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Chronic 2 H411
EC 201-254-7		Skin Corr. 1B H314: $\geq 10\%$, Skin Irrit. 2 H315: $\geq 3\%$, Eye Dam. 1 H318: $\geq 3\%$, Eye Irrit. 2 H319: $\geq 1\%$, STOT SE 3 H335: $\geq 1\%$
CAS 80-15-9		LD50 Oral: 382 mg/kg, LD50 Dermal: 1400 mg/kg, STA Inhalation mists/powders: 0,501 mg/l
REACH Reg. 01-2119475796-19-XXXX		
ETHANEDIOL		
INDEX 603-027-00-1	$1 \leq x < 5$	Acute Tox. 4 H302, STOT RE 2 H373
EC 203-473-3		STA Oral: 500 mg/kg
CAS 107-21-1		
REACH Reg. 01-2119456816-28-XXXX		

SECTION 3. Composition/information on ingredients ... / >>**CUMENE**INDEX 601-024-00-X $0 \leq x < 0,1$ **Flam. Liq. 3 H226, Carc. 1B H350, Asp. Tox. 1 H304, STOT SE 3 H335,
Aquatic Chronic 2 H411**

EC 202-704-5

CAS 98-82-8

REACH Reg. 01-2119473983-24-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

CUMYL HYDROPEROXIDE

Specific Conc. Limits H335: C<10%

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash.

Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor: symptomatic treatment.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO₂), and nitric oxides (NO_x).**5.3. Advice for firefighters**

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

SECTION 6. Accidental release measures ... / >>

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nariadení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendletele a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvis higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai" patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
NOR	Norge	Forskrift om ending i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og

SECTION 8. Exposure controls/personal protection ... / >>

NLD	Nederland	grenseverdie), 21. august 2018 nr. 1255 Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénym a mutagénym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

ETHANEDIOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	52	20	104	40	SKIN
TLV	CZE	50	19,4	100	38,8	SKIN
AGW	DEU	26	10	52	20	SKIN
MAK	DEU	26	10	52	20	SKIN
TLV	DNK	26	10			SKIN E
VLA	ESP	52	20	104	40	SKIN
TLV	EST	52	20	104	40	SKIN
VLEP	FRA	52	20	104	40	SKIN
HTP	FIN	50	20	100	40	SKIN
TLV	GRC	125	50	125	50	
AK	HUN	52		104		SKIN
GVI/KGVI	HRV	52	20	104	40	SKIN
VLEP	ITA	52	20	104	40	SKIN
RD	LTU	25	10	50	20	SKIN
RV	LVA	52	20	104	40	SKIN
TLV	NOR	52	20			SKIN
TGG	NLD	52		104		SKIN damp
VLE	PRT	52	20	104	40	SKIN
NDS/NDSch	POL	15		50		SKIN
TLV	ROU	52	20	104	40	SKIN
NGV/KGV	SWE	25	10	104	40	SKIN
NPEL	SVK	52	20	104	40	SKIN
MV	SVN	52	20	104	40	SKIN
ESD	TUR	52	20	104	40	SKIN
WEL	GBR	52	20	104	40	SKIN
OEL	EU	52	20	104	40	SKIN
TLV-ACGIH			25		50	
TLV-ACGIH				10		INHAL

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			7 mg/m3				35 mg/m3	
Skin				53 mg/kg bw/d			106	106 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

2-HYDROXYETHYL METHACRYLATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	NOR	11	2	11	2		

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,482	mg/l
Normal value in marine water	0,0482	mg/l
Normal value for fresh water sediment	3,79	mg/kg
Normal value for marine water sediment	3,79	mg/kg
Normal value for fresh water, intermittent release	1	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,476	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0.83 mg/kg/d				0.83 mg/kg/d
Inhalation				2.9 mg/m3				4.9 mg/m3
Skin				0.83 mg/kg/d				1.3 mg/kg/d

dodecyl methacrylate

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Skin				25 mg/kg bw/d				41.66 mg/kg bw/d

CUMYL HYDROPEROXIDE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0031	mg/l
Normal value in marine water	0,00031	mg/l
Normal value for fresh water sediment	0,023	mg/kg
Normal value for marine water sediment	0,0023	mg/kg
Normal value for water, intermittent release	0,031	mg/l
Normal value of STP microorganisms	0,35	mg/l
Normal value for the terrestrial compartment	0,0029	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								6 mg/m3

SECTION 8. Exposure controls/personal protection ... / >>

CUMENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	100	20	250	50	SKIN
TLV	CZE	100	20	250	50	SKIN
AGW	DEU	50	10	200	40	SKIN
TLV	DNK	100	20			SKIN E
VLA	ESP	50	10	250	50	SKIN
TLV	EST	100	20	250	50	SKIN
VLEP	FRA	100	20	250	50	SKIN
HTP	FIN	50	10	250	50	SKIN
TLV	GRC	245	50	370	75	
AK	HUN	50		250		SKIN
GVI/KGVI	HRV	50	10	250	50	SKIN
VLEP	ITA	100	20	250	50	SKIN
RD	LTU	50	10	170	35	SKIN
RV	LVA	100	20	250	50	SKIN
TLV	NOR	100	20	250	50	SKIN
TGG	NLD	100		250		SKIN
VLE	PRT	50	10	250	50	INHAL
VLE	PRT	50	10	250	50	SKIN
NDS/NDSch	POL	50		250		SKIN
TLV	ROU	50	10	250	50	SKIN
NGV/KGV	SWE	50	10	250	50	SKIN
NPEL	SVK	50	10	250	50	SKIN
MV	SVN	100	20	250	50	SKIN
ESD	TUR	100	20	250	50	SKIN
WEL	GBR	125	25	250	50	SKIN
OEL	EU	50	10	250	50	SKIN
TLV-ACGIH			5			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,035	mg/l
Normal value in marine water	0,004	mg/l
Normal value for fresh water sediment	3,22	mg/kg/d
Normal value for marine water sediment	0,322	mg/kg/d
Normal value of STP microorganisms	200	mg/l
Normal value for the terrestrial compartment	0,624	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				5				
				mg/kg bw/d				
Inhalation				16,6			250	100
				mg/m3			mg/m3	mg/m3
Skin				1,2				15,4
				mg/kg bw/d				mg/kg bw/d

TETRADECYL METHACRYLATE

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Skin				25				41.66
				mg/kg bw/d				mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

SECTION 8. Exposure controls/personal protection ... / >>

When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).
Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

None required, unless indicated otherwise in the chemical risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	blue	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 100 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-soluble (in water)
Kinematic viscosity	not available	
Dynamic viscosity	≈20000 mPa s Thixo	Temperature: 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,1	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

ETHANEDIOL

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable if stored in original containers at temperatures lower than the self accelerated decomposition temperature (SADT).

SECTION 10. Stability and reactivity ... / >>

10.3. Possibility of hazardous reactions

ETHANEDIOL

Risk of explosion on contact with: perchloric acid. May react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition. Avoid transferring into containers that may have been contaminated with other substances. Avoid storing close to inflammable or combustible products.

ETHANEDIOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the formation of explosive peroxides or other potentially hazardous substances.

ETHANEDIOL

May develop: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, carbon monoxide, hydrogen.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

ETHANEDIOL

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ETHANEDIOL

Ingestion initially stimulates the central nervous system; later replaced by a phase of depression. There may be kidney damage, with anuria and uremia. Over-exposure symptoms are: vomiting, drowsiness, difficulty in breathing, convulsions. The lethal dose for humans is approx. 1.4 ml/kg.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

ETHANEDIOL

LD50 (Dermal):	9530 mg/kg Rabbit
LD50 (Oral):	> 2000 mg/kg Rat
STA (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

2-HYDROXYETHYL METHACRYLATE

LD50 (Dermal):	> 5000 mg/kg
LD50 (Oral):	> 5000 mg/kg

dodecyl methacrylate

LD50 (Dermal):	> 3000 mg/kg
LD50 (Oral):	> 5000 mg/kg

SECTION 11. Toxicological information ... / >>**CUMYL HYDROPEROXIDE**

LD50 (Dermal):	1400 mg/kg
LD50 (Oral):	382 mg/kg
LC50 (Inhalation mists/powders):	1,37 mg/l/4h
STA (Inhalation mists/powders):	0,501 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

CUMENE

LD50 (Dermal):	> 3160 mg/kg Rabbit
LD50 (Oral):	1400 mg/kg Rat
LC50 (Inhalation vapours):	> 17,6 mg/l/6h Rat

TETRADECYL METHACRYLATE

LD50 (Oral):	> 17500 mg/kg
--------------	---------------

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

ETHANEDIOL

Available studies have shown no carcinogenic potential. In a carcinogenicity study lasting two years, carried out by the US National Toxicology Program (NTP), in which ethylene glycol was administered in the feed, "no evidence of carcinogenic activity" in male and female B6C3F1 mice was observed (NTP, 1993).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information**12.1. Toxicity**

SECTION 12. Ecological information ... / >>

2-HYDROXYETHYL METHACRYLATE	
LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	380 mg/l/48h
EC50 - for Algae / Aquatic Plants	836 mg/l/72h
dodecyl methacrylate	
LC50 - for Fish	> 10000 mg/l/96h
CUMYL HYDROPEROXIDE	
LC50 - for Fish	3,9 mg/l/96h
EC50 - for Crustacea	18,84 mg/l/48h
EC50 - for Algae / Aquatic Plants	3,1 mg/l/72h
Chronic NOEC for Crustacea	9,15 mg/l
Chronic NOEC for Algae / Aquatic Plants	1 mg/l
TETRADECYL METHACRYLATE	
LC50 - for Fish	> 10000 mg/l/96h

12.2. Persistence and degradability

ETHANEDIOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
2-HYDROXYETHYL METHACRYLATE	
Rapidly degradable	
CUMYL HYDROPEROXIDE	
NOT rapidly degradable	
CUMENE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

ETHANEDIOL	
Partition coefficient: n-octanol/water	-1,36
CUMENE	
Partition coefficient: n-octanol/water	3,55
BCF	94,69

12.4. Mobility in soil

CUMENE	
Partition coefficient: soil/water	2,946

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 15. Regulatory information ... / >>

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Org. Perox E	Organic peroxide, type E
Carc. 1B	Carcinogenicity, category 1B
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H350	May cause cancer.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods

SECTION 16. Other information ... / >>

- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

SECTION 16. Other information ... / >>

Changes to previous review:
The following sections were modified:
02 / 03 / 08 / 15 / 16.