



# GRSE18S-N1142


GR18

PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



Ordering information

| Type          | part no. |
|---------------|----------|
| GRSE18S-N1142 | 1069630  |

Other models and accessories → [www.sick.com/GR18](http://www.sick.com/GR18)

Detailed technical data

Features

|                                 |                                                                                              |
|---------------------------------|----------------------------------------------------------------------------------------------|
| Functional principle            | Through-beam photoelectric sensor                                                            |
| Dimensions (W x H x D)          | 18 mm x 18 mm x 38.1 mm                                                                      |
| Housing design (light emission) | Cylindrical                                                                                  |
| Thread diameter (housing)       | M18 x 1                                                                                      |
| Optical axis                    | Axial                                                                                        |
| Sensing range max.              | 0 m ... 15 m                                                                                 |
| Sensing range                   | 0 m ... 10 m                                                                                 |
| Type of light                   | Visible red light                                                                            |
| Light source                    | PinPoint LED <sup>1)</sup>                                                                   |
| Light spot size (distance)      | Ø 250 mm (10 m)                                                                              |
| Wave length                     | 650 nm                                                                                       |
| Adjustment                      | Potentiometer, 270°<br>Potentiometer                                                         |
| Display                         |                                                                                              |
| LED green                       | Operating indicator<br>Static on: power on                                                   |
| LED yellow                      | Status of received light beam<br>Static on: object not present<br>Static off: object present |

<sup>1)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

## Mechanics/electronics

|                                             |                                                       |
|---------------------------------------------|-------------------------------------------------------|
| <b>Supply voltage <math>U_B</math></b>      | 10 V DC ... 30 V DC <sup>1)</sup>                     |
| <b>Ripple</b>                               | < 5 V <sub>pp</sub> <sup>2)</sup>                     |
| <b>Current consumption</b>                  | 30 mA                                                 |
| <b>Switching output</b>                     | NPN                                                   |
| <b>Output function</b>                      | Complementary                                         |
| <b>Switching mode</b>                       | Light/dark switching                                  |
| <b>Output current <math>I_{max}</math></b>  | ≤ 100 mA <sup>3)</sup>                                |
| <b>Response time</b>                        | < 500 μs <sup>4)</sup>                                |
| <b>Switching frequency</b>                  | 1,000 Hz <sup>5)</sup>                                |
| <b>Connection type</b>                      | Cable, 4-wire, 2 m <sup>6)</sup>                      |
| <b>Cable material</b>                       | Plastic, PVC                                          |
| <b>Circuit protection</b>                   | A <sup>7)</sup><br>B <sup>8)</sup><br>D <sup>9)</sup> |
| <b>Protection class</b>                     | III                                                   |
| <b>Housing material</b>                     | Metal, Nickel-plated brass and ABS                    |
| <b>Optics material</b>                      | Plastic, PMMA                                         |
| <b>Enclosure rating</b>                     | IP67                                                  |
| <b>Items supplied</b>                       | Fastening nuts (4 x)                                  |
| <b>Electromagnetic compatibility (EMC)</b>  | EN 60947-5-2                                          |
| <b>Test input</b>                           | Sender OFF at "Test" 0 V                              |
| <b>Ambient operating temperature</b>        | -25 °C ... +55 °C <sup>10)</sup>                      |
| <b>Ambient temperature, storage</b>         | -40 °C ... +70 °C                                     |
| <b>UL File No.</b>                          | NRKH.E348498 & NRKH7.E348498                          |
| <b>Part number of individual components</b> | 2075623 GRS18S-D1341 2075661 GRE18S-N1132             |

<sup>1)</sup> Limit values. Operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed  $U_V$  tolerances.

<sup>3)</sup> At  $U_V > 24$  V or ambient temperature > 49 °C,  $I_A$  max. = 50 mA.

<sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

<sup>6)</sup> Do not bend below 0 °C.

<sup>7)</sup> A =  $V_S$  connections reverse-polarity protected.

<sup>8)</sup> B = inputs and output reverse-polarity protected.

<sup>9)</sup> D = outputs overcurrent and short-circuit protected.

<sup>10)</sup> At  $U_V \leq 24$  V and  $I_A < 50$  mA.

## Certificates

|                                           |   |
|-------------------------------------------|---|
| <b>EU declaration of conformity</b>       | ✓ |
| <b>UK declaration of conformity</b>       | ✓ |
| <b>ACMA declaration of conformity</b>     | ✓ |
| <b>Moroccan declaration of conformity</b> | ✓ |
| <b>China RoHS</b>                         | ✓ |
| <b>ECOLAB certificate</b>                 | ✓ |

|                                                   |   |
|---------------------------------------------------|---|
| cULus certificate                                 | ✓ |
| Photobiological safety (DIN EN 62471) certificate | ✓ |


Classifications

|                |          |
|----------------|----------|
| ECLASS 5.0     | 27270901 |
| ECLASS 5.1.4   | 27270901 |
| ECLASS 6.0     | 27270901 |
| ECLASS 6.2     | 27270901 |
| ECLASS 7.0     | 27270901 |
| ECLASS 8.0     | 27270901 |
| ECLASS 8.1     | 27270901 |
| ECLASS 9.0     | 27270901 |
| ECLASS 10.0    | 27270901 |
| ECLASS 11.0    | 27270901 |
| ECLASS 12.0    | 27270901 |
| ETIM 5.0       | EC002716 |
| ETIM 6.0       | EC002716 |
| ETIM 7.0       | EC002716 |
| ETIM 8.0       | EC002716 |
| UNSPSC 16.0901 | 39121528 |


Adjustments GRL18(S), GRSE18(S), Sensitivity setting: Potentiometer, 270 °




Connection diagram Cd-088



Characteristic curve GRSE18S



Light spot size GRSE18, red light




Sensing range diagram GRSE18S



Response range GRSE18S



Dimensional drawing GR18S, metal, cable, straight, adjustable



Dimensions in mm (inch)  
① Connection cable 2 m

- ② Threaded mounting hole M18 x 1
- ③ LED indicator yellow
- ④ LED indicator green
- ⑤ sensitivity control: potentiometer 270°
- ⑥ Fastening nuts (2x); width across 24, metal

## Recommended accessories

Other models and accessories → [www.sick.com/GR18](http://www.sick.com/GR18)

|                                                                                   | Brief description                                                                                                                                                                                                                                                                                         | Type       | part no. |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------|
| Mounting systems                                                                  |                                                                                                                                                                                                                                                                                                           |            |          |
|  | <ul style="list-style-type: none"> <li><b>Description:</b> Mounting bracket for M18 sensors</li> <li><b>Material:</b> Steel</li> <li><b>Details:</b> Steel, zinc coated</li> <li><b>Items supplied:</b> Without mounting hardware</li> <li><b>Suitable for:</b> GR18, V180-2, V18, W15, Z1, Z2</li> </ul> | BEF-WN-M18 | 5308446  |
| connectors and cables                                                             |                                                                                                                                                                                                                                                                                                           |            |          |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Male connector, M12, 4-pin, straight, A-coded</li> <li><b>Description:</b> Unshielded</li> <li><b>Connection systems:</b> Screw-type terminals</li> <li><b>Permitted cross-section:</b> ≤ 0.75 mm²</li> </ul>                       | STE-1204-G | 6009932  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)