

# IRL-P211E41

ZoneControl

**PHOTOELECTRIC SENSORS** 





## Ordering information

Туре	part no.
IRL-P211E41	1063185

Other models and accessories → www.sick.com/ZoneControl

Illustration may differ



#### Detailed technical data

#### Features

Functional principle	Photoelectric retro-reflective sensor
Actuator	Pneumatic, valve on board
Max. number of sensors	Approx. 30 <sup>1)</sup> Approx. 50 <sup>2)</sup>
Logical principle of operation	Single accumulation
Type of Release	Single release, block (slug) release
Dimensions (W x H x D)	50 mm x 147.4 mm x 48.9 mm
Sensing range max.	250 mm 1,500 mm
Sensing range	250 mm 1,500 mm <sup>3)</sup>
Focus	7°
Type of light	Visible red light
Light source	LED <sup>4)</sup>
Light spot size (distance)	Ø 20 mm (500 mm)
Angle of dispersion	7°
Adjustment	Potentiometer, 9 turns
Special applications	ZoneControl

 $<sup>^{1)}\,\</sup>mbox{When powerd from the end of the IR daisy chain.}$ 

 $<sup>^{\</sup>rm 2)}$  When powerd from center of the IR daisy chain.

<sup>3)</sup> On reflective tape REF-7610-K.

 $<sup>^{4)}</sup>$  Average service life: 100,000 h at TU = +25 °C.

#### Mechanics/electronics

Supply voltage U <sub>B</sub>	19.2 V DC 27.6 V DC $^{1)}$
Ripple	< 5 V <sub>pp</sub> <sup>2)</sup>
Current consumption	20 mA <sup>3)</sup>
Switching output	PNP
Signal voltage PNP HIGH/LOW	Approx. V <sub>S</sub> – 0.5 V / 0 V
Output current I <sub>max.</sub>	≤ 100 mA
Response time	2 ms
Switching frequency	250 Hz
Connection type	Male connector M12, 4-pin
Connection type for daisy chain	Cable with female connector, M12, 4-pin 1.2 m
Circuit protection	A <sup>4)</sup> C <sup>5)</sup> D <sup>6)</sup>
Protection class	III
Weight	175 g
Housing material	Plastic, ABS
Enclosure rating	IP65
Shock and vibration resistance	According to IEC 68
Ambient operating temperature	-10 °C +55 °C
Ambient temperature, storage	-40 °C +75 °C
UL File No.	NRKH.E189383 & NRKH7.E189383
Medium for valves	Compressed air or neutral gases filtered, non-lubricated or lubricated
Design solenoid valve	3/2-way valve
Mode of operation solenoid valve	Air to Brake (NO)
Connection type solenoid valve	Compressed air 2 x 8 mm diameter, output line 4 mm diameter
Coil ratings	24 V DC 1 W
Air flow rate	Approx. 20 NI/min
Ventilation capacity	Approx. 130 NI/min
Operating pressure range	2 bar 8 bar

<sup>1)</sup> Limit values.

#### Safety-related parameters

MTTF <sub>D</sub>	1,374 years
DC <sub>avg</sub>	0 %
B <sub>10D</sub>	20,000,000 Switching cycles <sup>1)</sup>

<sup>1)</sup> Only for devices containing electro-mechanical components. In this case, the MTTF<sub>D</sub> value of the entire device must be calculated from the given B<sub>10D</sub> value, the number of switching cycles and the given MTTF<sub>D</sub> value.

 $<sup>^{2)}\,\</sup>mbox{May}$  not fall below or exceed  $\mbox{U}_{\mbox{\sc V}}$  tolerances.

 $<sup>^{</sup>m 3)}$  Without load and valve deenergized.

 $<sup>^{5)}</sup>$  C = interference suppression.

<sup>6)</sup> D = outputs overcurrent and short-circuit protected.

#### Pneumatic

Coil ratings	24 V DC 1 W
Medium for valves	Compressed air or neutral gases filtered, non-lubricated or lubricated
Design solenoid valve	3/2-way valve
Connection type solenoid valve	Compressed air 2 x 8 mm diameter, output line 4 mm diameter
Air flow rate	Approx. 20 NI/min
Ventilation capacity	Approx. 130 NI/min
Operating pressure range	2 bar 8 bar


#### Certificates

EU declaration of conformity	✓
China RoHS	✓


#### Classifications

ECLASS 5.0	27270902
ECLASS 5.1.4	27270902
ECLASS 6.0	27270902
ECLASS 6.2	27270902
ECLASS 7.0	27270902
ECLASS 8.0	27270902
ECLASS 8.1	27270902
ECLASS 9.0	27270902
ECLASS 10.0	27270902
ECLASS 11.0	27270902
ECLASS 12.0	27270902
ETIM 5.0	EC002717
ETIM 6.0	EC002717
ETIM 7.0	EC002717
ETIM 8.0	EC002717
UNSPSC 16.0901	39121528


## Connection diagram Cd-264



#### Light spot size



#### Dimensional drawing IR, valve metric/imperial



Dimensions in mm (inch)

- Potentiometer
- ② LED
- 3 fixing hole

#### PHOTOELECTRIC SENSORS

- 4 Center of optical axis, sender
- ⑤ Center of optical axis, receiver
- 6 male connector M12, 4-pin
- To series connection, cable with female connector

#### Recommended accessories

Other models and accessories → www.sick.com/ZoneControl

	Brief description	Туре	part no.
reflectors and optics			
	<ul> <li>Description: Self-adhesive, not suitable for photoelectric retro-reflective sensors with polarisation filter, customizable size by roll</li> <li>Dimensions: 30 mm 220 mm</li> <li>Ambient operating temperature: -25 °C +65 °C</li> </ul>	REF-7610-K	4018617
Mounting syst	ems		
	<ul> <li>Description: Mounting bracket</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Mounting hardware included</li> </ul>	BEF-WN-RT/IRT	2074621
0 0	<ul> <li>Description: Mounting bracket</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Mounting hardware included</li> <li>Usable for: WTR/WLR, IRT</li> </ul>	BEF-WK-WTR	2051786
	<ul> <li>Description: Plate N11N for universal clamp bracket</li> <li>Material: Stainless steel</li> <li>Details: Stainless steel 1.4571 (sheet), Stainless steel 1.4408 (clamp)</li> <li>Items supplied: Universal clamp (5322627), mounting hardware</li> <li>Usable for: DeltaPac, Glare, WTD20E</li> </ul>	BEF-KHS-N11N	2071081
connectors an	nd cables		
	<ul> <li>Connection type head A: Female connector, M12, 4-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Sensor/actuator cable</li> <li>Cable: 5 m, 4-wire, PVC</li> <li>Description: Sensor/actuator cable, unshielded</li> <li>Application: Zones with chemicals, Uncontaminated zones</li> </ul>	YF2A14-050VB3XLEAX	2096235
1	<ul> <li>Connection type head A: Male connector, M12, 4-pin, straight, A-coded</li> <li>Description: Unshielded</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm²</li> </ul>	STE-1204-G	6009932
	<ul> <li>Connection type head A: Female connector, M12, 4-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Sensor/actuator cable</li> <li>Cable: 5 m, 4-wire, PUR, halogen-free</li> <li>Description: Sensor/actuator cable, unshielded</li> <li>Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li> </ul>	YF2A14-050UB3XLEAX	2095608

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

