

KUP-0610-J

Shaft couplings

SHAFT ADAPTATION





Ordering information

Туре	part no.
KUP-0610-J	2127056

Other models and accessories → www.sick.com/Shaft_couplings

Detailed technical data

Features

Product segment	Shaft adaptation
Product	Shaft couplings
Description	Claw coupling, shaft diameter 6 mm / 10 mm, damping element 80 shore blue, maximum shaft offset: radial \pm 0.22 mm, axial \pm 1 mm angular \pm 1.3°, max. speed 19,000 rpm, angle of twist max. 10°, –30 °C to +80 °C, max. torque 800 Ncm, tightening torque of screws: ISO 4029 150 Ncm, material: aluminum flange, damping element: polyurethane


Classifications

ECLASS 5.0 23031090 ECLASS 5.1.4 23031090	
FCI ASS 5.1.4 23031090	
20001000	
ECLASS 6.0 23031090	
ECLASS 6.2 23031090	
ECLASS 7.0 23031090	
ECLASS 8.0 23031090	
ECLASS 8.1 23031090	
ECLASS 9.0 23031090	
ECLASS 10.0 23031090	
ECLASS 11.0 23031090	
UNSPSC 16.0901 31163014	

Certificates

China-RoHS	✓

Dimensional drawing



Dimensions in mm (inch)

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

