

# BTF13-J1QM3064

HighLine

**WIRE DRAW ENCODERS** 





### Ordering information

Туре	part no.
BTF13-J1QM3064	1127316

Included in delivery: MRA-F130-130D1 (1), AHM36A-S3JC014X12 (1), BEF-FA-020-050WDE (1)

Other models and accessories → www.sick.com/HighLine



#### Detailed technical data

#### Safety-related parameters

MTTF <sub>D</sub> (mean time to dangerous failure)	270 years (EN ISO 13849-1) <sup>1)</sup>
--	--

<sup>1)</sup> This product is a standard product and does not constitute a safety component as defined in the Machinery Directive. Calculation based on nominal load of components, average ambient temperature 40 °C, frequency of use 8760 h/a. All electronic failures are considered hazardous. For more information, see document no. 8015532.

#### Performance

Measurement range	0 m 30 m
Encoder	Absolute encoders
Resolution (wire draw + encoder)	0.02 mm <sup>1) 2)</sup>
Repeatability	≤ 2 mm <sup>3)</sup>
Linearity	≤ ± 2 mm <sup>3)</sup>
Hysteresis	≤ 5 mm <sup>3)</sup>

 $<sup>^{1)}</sup>$  The values shown have been rounded.

#### Interfaces

Communication interface	SAE J1939
Programmable/configurable	✓

#### **Electronics**

Connection type	Male connector, M12, 5-pin, universal
Supply voltage	10 V 30 V
Power consumption	≤ 1.5 W (without load)

<sup>&</sup>lt;sup>2)</sup> Example calculation based on the BTF08 with PROFINET: 200 mm (wire draw length per revolution - see Mechanical data): 262,144 (number of steps per revolution) = 0.001 mm (resolution of wire draw + encoder combination).

<sup>3)</sup> Value applies to wire draw mechanism.

#### Mechanics

Weight	6.32 kg
Measuring wire material	Highly flexible stranded steel 1,4401 stainless steel V4A
Measuring wire diameter	0.81 mm
Weight (measuring wire)	2.6 g/m
Housing material, wire draw mechanism	Aluminum (anodised), plastic
Spring return force	10 N 20 N <sup>1)</sup>
Length of wire pulled out per revolution	332.4 mm
Life of wire draw mechanism	Typ. 1,000,000 cycles <sup>2) 3)</sup>
Actual wire draw length	30.2 m
Wire acceleration	15 m/s <sup>2</sup>
Operating speed	6 m/s
Mounted encoder	AHM36 SAE J1939, AHM36A-S3JC014x12, 1120251
Mounted mechanic	MRA-F130-130D1, 6028629

 $<sup>^{1)}</sup>$  These values were measred at an ambient temperature of 25  $\,^{\circ}$  C. There may be variations at other temperatures.

#### Ambient data

EMC	According to EN 61000-6-2 and EN 61000-6-3
Enclosure rating	IP64, mounted mechanic IP66, Encoder (IEC 60529) IP67, Encoder (IEC 60529)
Operating temperature range	-30 °C +70 °C

#### Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓

#### Classifications

ECLASS 5.0	27270590
ECLASS 5.1.4	27270590
ECLASS 6.0	27270590
ECLASS 6.2	27270590
ECLASS 7.0	27270590
ECLASS 8.0	27270590
ECLASS 8.1	27270590
ECLASS 9.0	27270590
ECLASS 10.0	27270613
ECLASS 11.0	27270503
ECLASS 12.0	27270503

 $<sup>^{2)}</sup>$  Average values, which depend on the application.


<sup>3)</sup> The service life depends on the type of load. This is influenced by environmental conditions, the installation location, the measuring range in use, the traversing speed, and acceleration.


## BTF13-J1QM3064 | HighLine

WIRE DRAW ENCODERS

ETIM 5.0	EC001486
ETIM 6.0	EC001486
ETIM 7.0	EC001486
ETIM 8.0	EC001486
UNSPSC 16.0901	41112113


## Dimensional drawing





Dimensions in mm (inch)

### Anschlussbelegung



PIN	Signal	Wire colors (cable connection)	Function
1	CAN Shield	White	Shielding
2	VDC	Red	Supply voltageEn- coder10 V DC 30 V DC
3	GND/CAN GND	Blue	O V (GND)
4	CAN high	Black	CAN signal
5	CAN low	Pink	CAN signal
Housing	-	-	Shielding

#### Recommended accessories

Other models and accessories → www.sick.com/HighLine

	Brief description	Туре	part no.	
Mounting systems				
0	Description: Joint ball for later insertion in wire end ring with 20 mm diameter. The use of this joint ball enables movement in multiple levels of freedom.	Joint protection for wire rope BTF/PRF/MRA	5318683	
	Description: Compressed air attachment for MRA-F080 and MRA-F130 HighLine wire draw mechanism	MRA-F-P	6073769	
	Description: Flange adapter for HighLine wire draw mechanisms, adaption of face mount flange with centering hub 20 mm to 50 mm servo flange     Material: Aluminum     Details: Aluminum     Items supplied: Including 3 countersunk screws M3 x 10	BEF-FA-020-050WDE	2073776	
	Description: Additional brush attachment for wire draw mechanism MRA-F130 (5 m, 10 m, 20 m and 30 m from HighLine series)	MRA-F130-B	6038562	
	Description: Wire draw deflection pulley for wire draw mechanism MRA-F130 (5m, 10m, 20m and 30m from HighLine series)	MRA-F130-R	6028631	
programming devices				
A D . SX	Product segment: Programming devices Product family: PGT-12 Pro  Description: Hand-held programming device for the programmable SICK AHS/AHM36 CANopen encoders, TMS/TMM61 CANopen inclination sensors, TMS/TMM88 CANopen, TMS/TMM88 Analog, and wire draw encoders with AHS/AHM36 CANopen. Compact dimensions, low weight, and intuitive operation.  Items supplied: 1 x PGT-12-Pro standalone programming tool, 4 x 1.5 V (AA) alkaline mignon batteries	PGT-12-Pro	1076313	

	Brief description	Туре	part no.
connectors a	nd cables		
///	<ul> <li>Connection type head A: Flying leads</li> <li>Connection type head B: Flying leads</li> <li>Signal type: CANopen, DeviceNet™</li> <li>Items supplied: By the meter</li> <li>Cable: 4-wire, twisted pair</li> <li>Description: CANopen, shielded, DeviceNet™</li> <li>Note: Wire shield Al-Pt film, overall shield C-screen tin-plated</li> </ul>	LTG-2804-MW	6028328
Co	<ul> <li>Connection type head A: Female connector, M12, 5-pin, straight, A-coded</li> <li>Signal type: CANopen, DeviceNet™</li> <li>Description: CANopen, shieldedDeviceNet™</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm²</li> </ul>	DOS-1205-GA	6027534
Co	<ul> <li>Connection type head A: Male connector, M12, 5-pin, straight, A-coded</li> <li>Signal type: CANopen, DeviceNet™</li> <li>Description: CANopen, shieldedDeviceNet™</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm²</li> </ul>	STE-1205-GA	6027533
	<ul> <li>Connection type head A: Male connector, M12, 5-pin, straight</li> <li>Signal type: CANopen</li> <li>Description: CANopen, unshielded</li> </ul>	CAN male connector	6021167
5	<ul> <li>Connection type head A: Female connector, M12, 5-pin, A-coded</li> <li>Connection type head B: Female connector, M12, 5-pin, A-coded</li> <li>Connection type head C: Male connector, M12, 5-pin, A-coded</li> <li>Description: Unshielded</li> </ul>	DSC-1205T000025KMC	6030664
66	<ul> <li>Connection type head A: Female connector, M12, 5-pin, straight, A-coded</li> <li>Connection type head B: Male connector, M12, 5-pin, straight, A-coded</li> <li>Signal type: Fieldbus, CANopen, DeviceNet™</li> <li>Cable: 2 m, 4-wire, PUR, halogen-free</li> <li>Description: Fieldbus, shielded, CANopen, DeviceNet™</li> <li>Application: Drag chain operation, Zones with oils and lubricants</li> </ul>	YF2A15-020C1B- M2A15	2106279
No.	<ul> <li>Connection type head A: Female connector, M12, 5-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Fieldbus, CANopen, DeviceNet™</li> <li>Cable: 2 m, 4-wire, PUR, halogen-free</li> <li>Description: Fieldbus, shielded, CANopen, DeviceNet™</li> <li>Application: Drag chain operation, Zones with oils and lubricants</li> </ul>	YF2A15-020C1BXLEAX	2106283
4.4	<ul> <li>Connection type head A: Female connector, M12, 5-pin, straight, A-coded</li> <li>Connection type head B: Male connector, M12, 5-pin, straight, A-coded</li> <li>Signal type: Fieldbus, CANopen, DeviceNet™</li> <li>Cable: 5 m, 4-wire, PUR, halogen-free</li> <li>Description: Fieldbus, shielded, CANopen, DeviceNet™</li> <li>Application: Drag chain operation, Zones with oils and lubricants</li> </ul>	YF2A15-050C1B- M2A15	2106281
No.	<ul> <li>Connection type head A: Female connector, M12, 5-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Fieldbus, CANopen, DeviceNet™</li> <li>Cable: 5 m, 4-wire, PUR, halogen-free</li> <li>Description: Fieldbus, shielded, CANopen, DeviceNet™</li> <li>Application: Drag chain operation, Zones with oils and lubricants</li> </ul>	YF2A15-050C1BXLEAX	2106284
66	<ul> <li>Connection type head A: Female connector, M12, 5-pin, straight, A-coded</li> <li>Connection type head B: Male connector, M12, 5-pin, straight, A-coded</li> <li>Signal type: Fieldbus, CANopen, DeviceNet™</li> <li>Cable: 10 m, 4-wire, PUR, halogen-free</li> <li>Description: Fieldbus, shielded, CANopen, DeviceNet™</li> <li>Application: Drag chain operation, Zones with oils and lubricants</li> </ul>	YF2A15-100C1B- M2A15	2106282
No.	<ul> <li>Connection type head A: Female connector, M12, 5-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Fieldbus, CANopen, DeviceNet™</li> <li>Cable: 10 m, 4-wire, PUR, halogen-free</li> <li>Description: Fieldbus, shielded, CANopen, DeviceNet™</li> <li>Application: Drag chain operation, Zones with oils and lubricants</li> </ul>	YF2A15-100C1BXLEAX	2106286
1.18	<ul> <li>Connection type head A: Female connector, M12, 5-pin, A-coded</li> <li>Connection type head B: Female connector, M12, 5-pin, A-coded</li> <li>Connection type head C: Male connector, M12, 5-pin, A-coded</li> <li>Cable: 0.5 m, TPU</li> </ul>	Y-CAN cable	6083185

# BTF13-J1QM3064 | HighLine WIRE DRAW ENCODERS

	Brief description	Туре	part no.		
	Description: Shielded				
Wire draw mechanism					
	<ul> <li>Product segment: Wire draw mechanism</li> <li>Product family: Wire draw mechanism for wire draw encoders</li> <li>Description: HighLine wire draw mechanism for servo flange with 6 mm shaft, measuring range 0 m 30 m</li> <li>Items supplied: Without encoder</li> </ul>	MRA-F130-130D1	6028629		

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

