

# DSL-1104-T0M3

Y- and T-splitters

**CONNECTORS AND CABLES** 





#### Ordering information

Туре	part no.
DSL-1104-T0M3	6011683

Other models and accessories → www.sick.com/Y-\_and\_T-splitters



#### Detailed technical data

#### Technical specifications

Connection type head A Connection type head B Female connector, M12, 4-pin, A-coded Connection type head C Male connector, M12, 4-pin, A-coded Connecting cable O.3 m, PUR, halogen-free Cable material PUR, halogen-free TPU Connector material head A TPU Connector material head C TPU Housing color Locking nut material Zinc die-cast, nickel-plated Shielding, head  Male connector, M12, 4-pin, A-coded Male connector, M12, 4-pin,
Connection type head C  Connecting cable  Cable material  Housing material  Connector material head A  Connector material head C  Housing color  Corange  Locking nut material  Male connector, M12, 4-pin, A-coded  O.3 m, PUR, halogen-free  PUR, halogen-free  TPU  TPU  TPU  Connector material head C  TPU  Corange  Zinc die-cast, nickel-plated
Connecting cable Cable material PUR, halogen-free Housing material TPU Connector material head A TPU Connector material head C Housing color Locking nut material  Connector material  Connector material  Corange  Corange
Cable material PUR, halogen-free  Housing material TPU  Connector material head A TPU  Connector material head C TPU  Housing color Orange  Locking nut material Zinc die-cast, nickel-plated
Housing material  Connector material head A  TPU  Connector material head C  TPU  Housing color  Locking nut material  Zinc die-cast, nickel-plated
Connector material head A  TPU  Connector material head C  Housing color  Locking nut material  TPU  Orange  Zinc die-cast, nickel-plated
Connector material head C TPU  Housing color Orange  Locking nut material Zinc die-cast, nickel-plated
Housing color Cocking nut material  Zinc die-cast, nickel-plated
Locking nut material  Zinc die-cast, nickel-plated
Shielding head
Silicitudes of Silicitudes
Shielding Unshielded
Reference voltage ≤ 60 V DC, ≤ 300 V DC
Rated impulse voltage 2 kV
Current loading 4 A
Note Signal interrogation and logic interrupt
Enclosure rating IP67
Operating temperature
Head -25 °C +80 °C

#### Certificates


EU declaration of conformity	✓
UK declaration of conformity	✓
China-RoHS	✓

#### Classifications

ECLASS 5.0	27279201
ECLASS 5.1.4	27279201
ECLASS 6.0	27279201
ECLASS 6.2	27279201
ECLASS 7.0	27279201


ECLASS 8.0	27279201
ECLASS 8.1	27279201
ECLASS 9.0	27440108
ECLASS 10.0	27440108
ECLASS 11.0	27440108
ECLASS 12.0	27440108
ETIM 5.0	EC002585
ETIM 6.0	EC002585
ETIM 7.0	EC002585
ETIM 8.0	EC002585
UNSPSC 16.0901	31163032

## Dimensional drawing



Dimensions in mm (inch)

## Connection diagram



## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

