



LMS511-10100 PRO

LMS5xx

2D LIDAR SENSORS





Ordering information

Туре	part no.
LMS511-10100 PRO	1046135

Other models and accessories → www.sick.com/LMS5xx



Detailed technical data

Features

Application		Outdoor, Indoor
Variant		PRO
Resolution power		Standard Resolution
Light source		Infrared (905 nm, ± 10 nm)
Laser class		1 (EN/IEC 60825-1:2014, EN 60825-1:2014+A11:2021)
Aperture angle		
, , , , , , , , , , , , , , , , , , ,	Horizontal	190°
Scanning frequency		25 Hz 35 Hz 50 Hz 75 Hz 100 Hz
Angular resolution		
	Horizontal	0.042°, interlaced
		0.083°, interlaced
		0.1667°
		0.25°
		0.333°
		0.5°
		0.667°
		1°
Scan field flatness		Scan field flatness combined: \pm 0.72° Typical conical error: 1 sigma value - 0.11° \pm 0.1° Typical tilt: 1 sigma value + 0.15° \pm 0.08°
Heating		Self-heating with additional integrated heating
Working range		0.2 m 80 m
Scanning range		

At 10% remission factor	40 m
Measurement accuracy	± 24 mm
Spot size	Divergence: 11.9 mrad At the viewing window: 13.5 mm In 26 m: 322 nm In 40 m: 489 mm
Amount of evaluated echoes	5

Mechanics/electronics

Connection type	4 x M12 round connector
Supply voltage	24 V DC, ± 20 %
Power consumption	22 W, + 55 W heating (typical)
Housing material	AlSi12
Housing color	Gray (RAL 7032)
Window material	Polycarbonate, scratch-resistant coating
Enclosure rating	IP65 (EN 60529, Section 14.2.7) IP67 (EN 60529, Section 14.2.7)
Protection class	III (IEC 61140:2016-11)
Weight	3.7 kg
Dimensions (L x W x H)	160 mm x 155 mm x 185 mm
MTBF	> 100 years

Safety-related parameters

MTTF _D	> 100 years
-------------------	-------------

Performance

Response time	≥ 10 ms
Detectable object shape	Almost any
Systematic error	± 25 mm (1 m 10 m) ± 35 mm (10 m 20 m) ± 50 mm (20 m 30 m) ¹⁾
Statistical error	6 mm (1 m 10 m) 8 mm (10 m 20 m) 14 mm (20 m 30 m) ¹⁾
Integrated application	Field evaluation Output of measurement data
Number of field sets	10 fields
Simultaneous evaluation cases	10
Filter	Echo filter Fog filter Particle filter Average filter Glare filter

 $^{^{1)}\ \}mbox{Typical value;}$ actual value depends on environmental conditions.

Interfaces

Ether	net	✓, TCP/IP, UDP/IP
	Function	Host and AUX, NTP
	Data transmission rate	10/100 MBit/s

Serial	✓ , RS-232, RS-422
Function	Host and AUX
Data transmission rate	9.6 kBaud 500 kBaud
CAN	✓
Function	Extension of outputs
Data transmission rate	20 kBit/s, 500 kBit/s, 1 MBit/s, Synchronization
USB	✓
Remark	Mini-USB
Function	Service interface
Digital inputs/outputs	
Inputs	4 (Digital, encoder (HTL), synchronization)
Outputs	6 (digital)
Optical indicators	5 LEDs (Additional 7-segment display)

Ambient data

Object remission	2 % > 1,000 % (reflectors)
Electromagnetic compatibility (EMC)	
Emitted radiation	Industrial environment (IEC 61000-6-3:2020 / EN IEC 61000-6-3:2007+A1:2011)
Electromagnetic immunity	Industrial environment (IEC 61000-6-2:2016 / EN IEC 61000-6-2:2019)
Vibration resistance	
Sine test	10 Hz 150 Hz, Amplitude 0.35 mm to 5 g, 20 cycles $^{1)}$
Shock resistance	15 g, 11 ms, 6 single shocks/axis ²⁾ 10 g, 16 ms, 1,000 continuous shocks/axis ²⁾
Impact resistance	IK05, IK06, IK07 (DIN EN 50102:09-1997)
Ambient operating temperature	-30 °C +50 °C
Storage temperature	-40 °C +70 °C
Ambient light immunity	70,000 lx

 $^{^{1)}}$ IEC 60068-2-6:2007-12.

General notes

Note on use	The sensor does not constitute a safety component as defined by relevant legislation on ma-
	chine safety.

Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
China RoHS	✓
KC Mark certificate	✓
cTUVus certificate	✓
Information according to Art. 3 of Data Act (Regulation EU 2023/2854)	✓

Classifications


ECLASS 5.0	27270990

²⁾ IEC 60068-2-27:2008-02.

ECLASS 5.1.4	27270990
ECLASS 6.0	27270913
ECLASS 6.2	27270913
ECLASS 7.0	27270913
ECLASS 8.0	27270913
ECLASS 8.1	27270913
ECLASS 9.0	27270913
ECLASS 10.0	27270913
ECLASS 11.0	27270913
ECLASS 12.0	27270913
ETIM 5.0	EC002550
ETIM 6.0	EC002550
ETIM 7.0	EC002550
ETIM 8.0	EC002550
UNSPSC 16.0901	41111615


Working range diagram






Scanning range max. 80 m (262.47 ft)


Scanning range for objects up to 10 % remission 40 m (131.23 ft)




- 1) threaded holes M8x9 2) Mounting screws
- 3 Mounting kit 1




- ① threaded holes M8x9
- ② Fixing screw
- 3 Mounting kit 2
- 4 Mounting kit 1




- ① threaded holes M8x9
- ② Mounting screws
- 3 Mounting kit 3
- 4 Mounting kit 2
- ⑤ Mounting kit 1




- ① Post bracket
- ② Mounting bracket 2059271







- ① Weather hood
- ② LMS5xx
- 3 Mounting kit 14 Mounting kit 2



- ① Mounting bracket 2059271
- ② Mounting bracket 2018303



Assembly note




Connection type Ethernet



M12 female connector, 4-pin, D-coded

- ① TX+
- ② RX+
- ③ TX-
- 4 RX-


PIN assignment Data



M12, 12-pin male connector, A-coded

- \bigcirc V_S OUT
- ② RD-/RxD
- ③ OUT1
- 4 GND RS/CAN
- ⑤ OUT2
- ® Reserved
- ⑦ TD-/TxD
- ® Reserved
- 9 RD+
- 10 TD+
- ① CAN LOW
- 2 CAN HIGH


PIN assignment POWER connection



male connector M12, 5-pin, A-coded

- ① V_s ② V_s heat. ③ GND
- ④ Reserved
- ⑤ GND heat.

PIN assignment I/O



M12, 12-pin female connector, A-coded (I/O)

- $\textcircled{1} \ V_S \ OUT$
- ② GND IN1/2
- $3 ln_1$
- ④ GND IN3/4/IN Sync
- ⑤ In₂
- ⑥ In3
- ⑦ GND Out 3 ... 6
- ® IN4/IN Sync
- 9 OUT3
- @ OUT4
- ① OUT5
- @ OUT6/OUT Sync

Recommended accessories

Other models and accessories → www.sick.com/LMS5xx

	Brief description	Туре	part no.
connectors and cables			
	Connection type head A: Female connector, M12, 5-pin, straight, A-coded Connection type head B: Flying leads Signal type: Power Cable: 5 m, 4-wire, PUR, halogen-free Description: Power, shielded Connection systems: Flying leads	YF2A64-050XXXXLEAX	6036159
66	 Connection type head A: Male connector, M12, 4-pin, straight, D-coded Connection type head B: Male connector, RJ45, 4-pin, straight Signal type: Ethernet, PROFINET Cable: 5 m, 4-wire, PUR, halogen-free Description: Ethernet, shielded, PROFINET Application: Drag chain operation, Zones with oils and lubricants 	YM2D24-050P- N1MRJA4	2106184
	 Connection type head A: Male connector, M12, 12-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 5 m, 12-wire, PUR, halogen-free Description: Sensor/actuator cable, shielded Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation 	YM2A2B-050UD3XLEAX	2131093
No.	 Connection type head A: Female connector, M12, 12-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 5 m, 12-wire, PUR, halogen-free Description: Sensor/actuator cable, shielded Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation 	YF2A2B-050UD3XLEAX	2131096
Mounting systems			
	 Description: Mounting bracket for direct mounting, from the rear, on wall or machine, not adjustable Material: Aluminum Details: Aluminum Packing unit: 1 piece 	Mounting kit 1	2015623
	 Description: Mounting bracket for rear mounting on wall or machine, adjustable longitudinal and lateral axes, only in conjunction with mounting kit 1 (2015623) Material: Aluminum Details: Aluminum Packing unit: 1 piece 	Mounting kit 2	2015624

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

