

# M40Z-025002BU0

M4000 Standard A/P

**SAFETY MULTIBEAM SENSORS** 





#### Ordering information

Туре	part no.
M40Z-025002BU0	1200340

Other models and accessories → www.sick.com/M4000\_Standard\_A\_P

Illustration may differ



#### Detailed technical data

#### **Features**

Specialty	Actuator Sensor Interface replaces the system connection
Functional principle	Active/passive
System part	Active unit
Type of diversion	Fibre-optic deflection
Scanning range	0.5 m 4.5 m
Number of beams	2
Beam separation	500 mm
Response time	10 ms

#### Safety-related parameters

Туре	Type 4 (IEC 61496-1)
Safety integrity level	SIL 3 (IEC 61508)
Category	Category 4 (EN ISO 13849)
Performance level	PL e (EN ISO 13849)
$\mbox{PFH}_{\mbox{\scriptsize D}}$ (mean probability of a dangerous failure per hour)	6.6 x 10 <sup>-9</sup> (EN ISO 13849)
T <sub>M</sub> (mission time)	20 years (EN ISO 13849)

#### **Functions**

	Functions	Delivery status
Beam coding	✓	Uncoded

#### Interfaces

Actuator Sensor Interface	✓
System connection	Male connector M12, 4-pin
Configuration method	Configuration buttons

Display elements	LEDs
	7-segment display

#### **Electronics**

Protection class	III (IEC 61140)
Supply voltage $V_S$	(26 V DC 31.6 V DC) <sup>1)</sup>
Power consumption	≤ 0.2 A

<sup>1)</sup> The external voltage supply must be capable of buffering brief mains voltage failures of 20 ms as specified in EN 60204-1. Suitable power supplies are available as accessories from SICK.

#### Mechanics

Dimensions	See dimensional drawing
Housing cross-section	52 mm x 55.5 mm
Material	
Housing	Aluminum alloy ALMGSI 0.5, powder coated
Front screen	Polycarbonate, scratch-resistant coating

#### Ambient data

Enclosure rating	IP65 (EN 60529)
Ambient operating temperature	-30 °C +55 °C
Storage temperature	-30 °C +70 °C
Air humidity	15 % 95 %, Non-condensing
Vibration resistance	5 g, 10 Hz 55 Hz (EN 60068-2-6)
Shock resistance	10 g, 16 ms (EN 60068-2-27)

#### Other information

Wave length	850 nm
-------------	--------

#### Certificates

EU declaration of conformity	<b>√</b>
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
ULus approval	✓
cUL approval	✓
EC-Type-Examination approval	✓
Information according to Art. 3 of Data Act (Regulation EU 2023/2854)	✓


#### Classifications

ECLASS 5.0	27272703
ECLASS 5.1.4	27272703
ECLASS 6.0	27272703
ECLASS 6.2	27272703
ECLASS 7.0	27272703
ECLASS 8.0	27272703

# M40Z-025002BU0 | M4000 Standard A/P SAFETY MULTIBEAM SENSORS

ECLASS 8.1	27272703
ECLASS 9.0	27272703
ECLASS 10.0	27272703
ECLASS 11.0	27272703
ECLASS 12.0	27272703
ETIM 5.0	EC001832
ETIM 6.0	EC001832
ETIM 7.0	EC001832
ETIM 8.0	EC001832
UNSPSC 16.0901	46171620

#### Dimensional drawing Active unit



## Dimensions in mm (inch)

Sender/receiver in one housing

		L1	L2
2	500	643	672
4	300	1,043	1,072

#### Recommended accessories

Other models and accessories → www.sick.com/M4000\_Standard\_A\_P

	Brief description	Туре	part no.		
Mounting systems					
6	<ul> <li>Description: Mounting kit 12, rotatable, swivel mount</li> <li>Packing unit: 4 pieces</li> <li>Suitable for: All protective field heights</li> </ul>	BEF-2SMGEAKU4	2030510		
	<ul> <li>Description: Mounting kit 1, mounting bracket, rigid, L-shaped, including fixing screws and washers</li> <li>Packing unit: 4 pieces</li> <li>Suitable for: All protective field heights</li> </ul>	BEF-3WNGBAST4	7021352		
	<ul> <li>Description: Mounting kit 6, side bracket, rotatable</li> <li>Material: Zinc diecast</li> <li>Details: Zinc diecast</li> <li>Packing unit: 4 pieces</li> <li>Suitable for: All protective field heights</li> </ul>	BEF-1SHABAZN4	2019506		
Commissioning aids and test equipment					
	<ul> <li>Product: Alignment aids</li> <li>Dimensions (W x H x L): 19 mm</li> <li>67.3 mm</li> <li>66.9 mm</li> <li>Description: Laser alignment aid for various sensors, laser class 2 (IEC 60825). Do not look into the beam!</li> </ul>	AR60	1015741		
	Product: Alignment aids     Description: Adapter AR60 for M4000 and M4000 Curtain	AR60 adapter, M4000	4040006		

### SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

