

GRTE18-N1112V

GR18

PHOTOELECTRIC SENSORS





Ordering information

Туре	part no.
GRTE18-N1112V	1085864

Other models and accessories → www.sick.com/GR18

Illustration may differ



Detailed technical data

Features

Functional principle	Photoelectric proximity sensor
Functional principle detail	Energetic
Dimensions (W x H x D)	18 mm x 18 mm x 73.5 mm
Housing design (light emission)	Cylindrical
Housing length	73.5 mm
Thread length	49.3 mm
Thread diameter (housing)	M18 x 1
Optical axis	Axial
Sensing range max.	3 mm 115 mm ¹⁾
Sensing range	5 mm 100 mm ¹⁾
Type of light	Visible red light
Light source	PinPoint LED ²⁾
Light spot size (distance)	Ø 8 mm (100 mm)
Wave length	650 nm
Adjustment	Potentiometer, 270°
Display	
LED green	Operating indicator Static on: power on
LED yellov	V Status of received light beam Static on: object present Static off: object not present

 $^{^{1)}}$ Object with 90% remission (based on standard white, DIN 5033).

²⁾ Average service life: 100,000 h at T_U = +25 °C.

Special applications

Hygienic and washdown zones

Mechanics/electronics

Supply voltage U _B	10 V DC 30 V DC ¹⁾
Ripple	< 5 V _{pp} ²⁾
Current consumption	30 mA
Switching output	NPN
Output function	Complementary
Switching mode	Light/dark switching ³⁾
Signal voltage NPN HIGH/LOW	Approx. $V_S / \leq 3 V$
Output current I _{max.}	\leq 100 mA $^{4)}$
Response time	< 1,000 µs ⁵⁾
Switching frequency	500 Hz ⁶⁾
Connection type	Cable, 4-wire, 2 m ⁷⁾
Cable material	Plastic, PVC
Conductor cross section	0.14 mm ²
Cable diameter	Ø 4.8 mm
Circuit protection	A ⁸⁾ B ⁹⁾ D ¹⁰⁾
Protection class	III
Weight	175 g
Housing material	Metal, Stainless steel V4A (1.4404, 316L)
Optics material	Plastic, PMMA
Tightening torque, max.	90 Nm
Enclosure rating	IP67 IP68 ¹¹⁾ IP69K ¹²⁾
Items supplied	Fastening nuts (2 x)
Electromagnetic compatibility (EMC)	EN 60947-5-2

 $^{^{1)}}$ Limit values. Operated in short-circuit protected network: max. 8 A.

 $^{^{1)}}$ Object with 90% remission (based on standard white, DIN 5033).

 $^{^{2)}}$ Average service life: 100,000 h at $\rm T_U$ = +25 °C.

 $^{^{2)}\,\}mbox{May}$ not fall below or exceed $\mbox{U}_{\mbox{\scriptsize V}}$ tolerances.

 $^{^{3)}}$ Q = light switching; \bar{Q} = dark switching.

 $^{^{4)}}$ At Uv > 24 V or ambient temperature > 49 °C, IA max. = 50 mA.

⁵⁾ Signal transit time with resistive load.

⁶⁾ With light/dark ratio 1:1.

⁷⁾ Do not bend below 0 °C.

 $^{^{8)}}$ A = V_S connections reverse-polarity protected.

 $^{^{9)}}$ B = inputs and output reverse-polarity protected.

B = inputs and output reverse-polarity protected.
 D = outputs overcurrent and short-circuit protected.

 $^{^{11)}}$ According to EN 60529 (10 m water depth / 24 h).

 $^{^{12)}}$ According to ISO 20653:2013-03.

 $^{^{13)}}$ At U_{V} <=24V and I_A<50mA.

Ambient operating temperature	-25 °C +55 °C ¹³⁾
Ambient temperature, storage	-30 °C +75 °C
UL File No.	E348498

 $^{^{1)}}$ Limit values. Operated in short-circuit protected network: max. 8 A.

Certificates

EU declaration of conformity	✓
UK declaration of conformity	√
ACMA declaration of conformity	√
Moroccan declaration of conformity	√
China RoHS	√
ECOLAB certificate	√
cULus certificate	√
Photobiological safety (DIN EN 62471) certificate	✓

Classifications

ECLASS 5.0	27270903
ECLASS 5.1.4	27270903
ECLASS 6.0	27270903
ECLASS 6.2	27270903
ECLASS 7.0	27270903
ECLASS 8.0	27270903
ECLASS 8.1	27270903
ECLASS 9.0	27270903
ECLASS 10.0	27270904
ECLASS 11.0	27270904
ECLASS 12.0	27270903
ETIM 5.0	EC001821
ETIM 6.0	EC001821
ETIM 7.0	EC002719
ETIM 8.0	EC002719
UNSPSC 16.0901	39121528

 $^{^{2)}\,\}mathrm{May}$ not fall below or exceed U_V tolerances.

 $^{^{3)}}$ Q = light switching; \bar{Q} = dark switching.

 $^{^{4)}}$ At Uv > 24 V or ambient temperature > 49 °C, IA max. = 50 mA.

 $^{^{5)}\,\}mathrm{Signal}$ transit time with resistive load.

⁶⁾ With light/dark ratio 1:1.

 $^{^{7)}}$ Do not bend below 0 $^{\circ}\text{C}.$

 $^{^{8)}}$ A = V $_{S}$ connections reverse-polarity protected.

 $^{^{9)}}$ B = inputs and output reverse-polarity protected.

 $^{^{10)}}$ D = outputs overcurrent and short-circuit protected.


 $^{^{11)}}$ According to EN 60529 (10 m water depth / 24 h).

 $^{^{12)}\}operatorname{According}$ to ISO 20653:2013-03.

 $^{^{13)}}$ At U $_{\mbox{\scriptsize V}}$ <=24V and I $_{\mbox{\scriptsize A}}\!<\!50\mbox{\scriptsize mA}.$

Adjustments GRTB18(S) Inox, GRTE18(S) Inox, Sensing range setting: Potentiometer, 270°






Connection diagram Cd-094

Characteristic curve GRTE18S, 100 mm


Operating reserve



- ① Sensing range on black, 6% remission factor
- ② sensing range to gray, 20% remission factor

3 Sensing range on white, 90% remission factor


Light spot size GRTE18S, 100 mm



dimensions in mm (inch)

Sensing range

Sensing range diagram GRTE18S, 100 mm




Distance in min (inc

Sensing range max.


- ① Sensing range on black, 6% remission factor
- 2) sensing range to gray, 20% remission factor
- 3 Sensing range on white, 90% remission factor

Response range GRTE18S, 100 mm





Dimensional drawing GR18 Inox, cable, straight



Dimensions in mm (inch)

- ① Connection
- ② Threaded mounting hole M18 x 1
- 3 fastening nuts (2 x); width across 24, stainless steel
- 4 Potentiometer, 270°
- ⑤ LED indicator (4 x)
- 6 optical axis, receiver
- ⑦ optical axis, sender

Recommended accessories

Other models and accessories → www.sick.com/GR18

	Brief description	Туре	part no.	
Mounting systems				
40	 Description: Mounting bracket for M18 sensors Material: Stainless steel Details: Stainless steel Items supplied: Without mounting hardware 	BEF-WN-M18N	5320947	
connectors and cables				
1	 Connection type head A: Male connector, M12, 4-pin, straight, A-coded Description: Unshielded Connection systems: Screw-type terminals Permitted cross-section: ≤ 0.75 mm² 	STE-1204-G	6009932	

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

