

# LL3-TS05

Fiber-optic cables

**FIBER-OPTIC SENSORS** 



## Ordering information



Туре	part no.
LL3-TS05	5334043

Other models and accessories → www.sick.com/Fiber-optic\_cables

#### Detailed technical data

#### **Features**

Device type	Fiber-optic cables
Functional principle	Through-beam system, consisting of a sender and a receiver
Fiber-optic head design	Flat type, 90° deflection, Array
Application	High flexible (static), Area detection
Special features	Small fiber optic cable cell
Compatible fiber-optic amplifiers	GLL70, WLL80, WLL180, GLL170(T), WLL24 Ex
Sensing range max.	Depending on the fiber optic amplifier used
Minimal object diameter	0.2 mm <sup>1)</sup>
Optical fiber head	
Integrated lens	No
Compatibility tip adapters	No
Optical fiber	
Compatibility with infrared light	No
Optical fiber cable can be shortened	✓
Adapter end sleeves required	No

 $<sup>^{1)}</sup>$  Minimum detectable object was determined at optimum measuring distance and optimum setting.

#### Mechanics

Optical fiber head	
Light emission	Radial
Fiber-optic head array width	4 mm
Optical fiber	
Fiber length	2,000 mm
Bending radius	5 mm
Dynamic flexibility (robotics)	No
Outside diameter, optical fiber cable connection	2.2 mm
Fiber arrangement	Multi-fiber
Core structure	16 x Ø 0,265 mm Multi-fiber
Material	

Optical fiber head	Stainless steel
Sheath	Polyethylen (PE)
Fibers	Polymethylmethacrylat (PMMA)
Weight	31 g

#### Ambient data

Ambient operating temperature	-55 °C +70 °C
-------------------------------	---------------

#### Classifications

ECLASS 5.0	27270905
ECLASS 5.1.4	27270905
ECLASS 6.0	27270905
ECLASS 6.2	27270905
ECLASS 7.0	27270905
ECLASS 8.0	27270905
ECLASS 8.1	27270905
ECLASS 9.0	27270905
ECLASS 10.0	27270905
ECLASS 11.0	27270905
ECLASS 12.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
ETIM 8.0	EC002651
UNSPSC 16.0901	39121528

## Sensing ranges with WLL180T

Operating mode 16 μs	210 mm
Operating mode 70 µs	560 mm
Operating mode 250 µs	1,020 mm
Operating mode 2 ms	1,780 mm
Operating mode 8 ms	2,650 mm
Note	Sensing ranges related to fiber-optic sensors with type of light: visible red light


## Sensing ranges with GLL170


Operating mode 250 µs	86 mm
-----------------------	-------

## Sensing ranges with GLL170T

Operating mode 50 µs	480 mm
Operating mode 250 µs	804 mm

## Dimensional drawing





Dimensions in mm (inch)

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

