



# IM30-15NPS-ZUK

**IM Standard** 

**INDUCTIVE PROXIMITY SENSORS** 





# Ordering information

Туре	part no.
IM30-15NPS-ZUK	1017435

Other models and accessories → www.sick.com/IM\_Standard

Illustration may differ



### Detailed technical data

### **Features**

reatures	
Housing	Metric
Housing	Short-body
Thread size	M30 x 1.5
Diameter	Ø 30 mm
Sensing range S <sub>n</sub>	15 mm
Installation type	Non-flush
Switching frequency	500 Hz
Connection type	Cable, 3-wire, 2 m
Switching output	PNP
Switching output detail	PNP
Output function	NO
Electrical wiring	DC 3-wire
Enclosure rating	IP67 <sup>1)</sup>

<sup>&</sup>lt;sup>1)</sup> According to EN 60529.

### Mechanics/electronics

,	
Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 % <sup>1)</sup>
Voltage drop	$\leq$ 1.5 V $^{2)}$
Time delay before availability	≤ 15 ms
Hysteresis	1 % 10 %
Reproducibility	≤ 3 % <sup>3)</sup> 4)
Temperature drift (of S <sub>r</sub> )	± 10 %

 $<sup>^{1)}</sup>$  Of  $V_S$ .

<sup>2)</sup> At I may

 $<sup>^{\</sup>rm 3)}$  Supply voltage  $U_B$  and constant ambient temperature Ta.

<sup>&</sup>lt;sup>4)</sup> Of Sr.

EMC	According to EN 60947-5-2
Continuous current I <sub>a</sub>	≤ 300 mA
Cable material	PUR/PVC
Conductor size	0.5 mm <sup>2</sup>
Wire-break protection	✓
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	30 g, 11 ms / 10 55 Hz, 1 mm
Ambient operating temperature	-25 °C +70 °C
Housing material	Brass, Nickel-plated brass
Sensing face material	Plastic
Housing length	40 mm
Thread length	25 mm
Tightening torque, max.	50 Nm

 $<sup>^{1)}</sup>$  Of  $V_{S}$ .

### Installation note

Remark	Associated graphic see "Installation"
Α	15 mm
В	45 mm
c	30 mm
D	45 mm
E	18 mm
F	120 mm

### Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓

### Classifications

ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101

<sup>&</sup>lt;sup>2)</sup> At I<sub>a</sub> max.

 $<sup>^{\</sup>rm 3)}$  Supply voltage  $\rm U_B$  and constant ambient temperature Ta.


<sup>&</sup>lt;sup>4)</sup> Of Sr.


# IM30-15NPS-ZUK | IM Standard

INDUCTIVE PROXIMITY SENSORS

ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714
UNSPSC 16.0901	39122230

### Installation note Non-flush installation







# Connection type



### Connection diagram Cd-001



### Dimensional drawing



Dimensions in mm (inch)

- ① Connection
- ② Display LED
- 3 Fastening nuts (2x); width across 36, metal

#### Recommended accessories

Other models and accessories → www.sick.com/IM\_Standard

	Brief description	Туре	part no.
Mounting systems			
0	<ul> <li>Description: Mounting plate for M30 sensors</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Without mounting hardware</li> </ul>	BEF-WG-M30	5321871
40	<ul> <li>Description: Mounting bracket for M30 sensors</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Without mounting hardware</li> </ul>	BEF-WN-M30	5308445
	<ul> <li>Description: Plate N10 for universal clamp bracket, M30</li> <li>Material: Steel, zinc diecast</li> <li>Details: Zinc plated steel (sheet), Zinc die cast (clamping bracket)</li> <li>Items supplied: Universal clamp (5322626), mounting hardware</li> <li>Usable for: M30 round sensors</li> </ul>	BEF-KHS-N10	2062372

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

