

# WL11-2P2432P07

W11-2

**PHOTOELECTRIC SENSORS** 





# Ordering information

Туре	part no.
WL11-2P2432P07	1050674

Included in delivery: P250 (1)

Other models and accessories → www.sick.com/W11-2





### Detailed technical data

#### **Features**

Functional principle	Photoelectric retro-reflective sensor	
Functional principle detail	With minimum distance to reflector (dual lens system)	
Dimensions (W x H x D)	15.6 mm x 48.5 mm x 42 mm	
Housing design (light emission)	Rectangular	
Sensing range max.	0.15 m 10 m <sup>1)</sup>	
Sensing range	0.15 m 8 m <sup>1)</sup>	
Focus	Approx. 2.2°	
Type of light	Visible red light	
Light source	LED <sup>2)</sup>	
Light spot size (distance)	Ø 50 mm (3 m)	
Angle of dispersion	Approx. 2.2°	
Wave length	640 nm	
Adjustment	Single teach-in button	

<sup>1)</sup> Reflector PL80A.

 $<sup>^{2)}</sup>$  Average service life: 100,000 h at TU = +25 °C.

# Mechanics/electronics

Supply voltage U <sub>B</sub>	10 V DC 30 V DC <sup>1)</sup>
Ripple	< 5 V <sub>pp</sub> <sup>2)</sup>
Current consumption	30 mA <sup>3)</sup>
Switching output	PNP
Output function	Complementary
Switching mode	Light/dark switching
Signal voltage PNP HIGH/LOW	Uv - 2.5 V / approx. 0 V
Output current I <sub>max.</sub>	≤ 100 mA
Response time	$\leq$ 2.5 ms $^{4)}$
Switching frequency	200 Hz <sup>5)</sup>
Connection type	Male connector M12, 4-pin
Circuit protection	A <sup>6)</sup> C <sup>7)</sup> D <sup>8)</sup>
Protection class	III
Weight	120 g
Polarisation filter	✓
Special device	✓
Housing material	Plastic, ABS
Optics material	Plastic, PMMA
Enclosure rating	IP66 IP67 IP69K
Items supplied	Reflector P250
Ambient operating temperature	-30 °C +60 °C
Ambient temperature, storage	-40 °C +75 °C
UL File No.	NRKH.E181493 & NRKH7.E181493

 $<sup>^{1)}\,\</sup>mathrm{Limit}$  values when operated in short-circuit protected network: max. 8 A.

# Safety-related parameters

MTTF <sub>D</sub>	1,625 years
<b>DC</b> <sub>avg</sub>	0 %
T <sub>M</sub> (mission time)	20 years

#### Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓

 $<sup>^{2)}\,\</sup>mathrm{May}$  not fall below or exceed  $\mathrm{U}_{\mathrm{V}}$  tolerances.

<sup>3)</sup> Without load.

<sup>&</sup>lt;sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

 $<sup>^{6)}</sup>$  A = V<sub>S</sub> connections reverse-polarity protected.

 $<sup>^{7)}</sup>$  C = interference suppression.

 $<sup>^{\</sup>rm 8)}$  D = outputs overcurrent and short-circuit protected.

# WL11-2P2432P07 | W11-2


# PHOTOELECTRIC SENSORS

ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
ECOLAB certificate	✓
cULus certificate	✓
EAC certificate / DoC	✓
Photobiological safety (DIN EN 62471) certificate	<b>✓</b>

# Classifications

ECLASS 5.0	27270902
ECLASS 5.1.4	27270902
ECLASS 6.0	27270902
ECLASS 6.2	27270902
ECLASS 7.0	27270902
ECLASS 8.0	27270902
ECLASS 8.1	27270902
ECLASS 9.0	27270902
ECLASS 10.0	27270902
ECLASS 11.0	27270902
ECLASS 12.0	27270902
ETIM 5.0	EC002717
ETIM 6.0	EC002717
ETIM 7.0	EC002717
ETIM 8.0	EC002717
UNSPSC 16.0901	39121528


### **Dimensional drawing**



Dimensions in mm (inch)

- ① Optical axis, sender
- 2 Optical axis, receiver
- 3 LED indicator yellow: Status of received light beam
- 4 LED indicator green: Supply voltage active
- ⑤ Mounting hole ø 4.2 mm
- 6 male connector M12, 4-pin

### Adjustments Teach-in



- 2 LED indicator yellow: Status of received light beam
- 3 green LED indicator: power on, teach-in mode I
- 3 blue LED indicator: teach-in mode II
- ® Single teach-in button,
- 6 function 1: teach-in sensitivity on reflector,
- (6) function 2: change operation/teach-in mode


# Connection type



# Connection diagram Cd-083

$$\begin{array}{c|c} & BN & 1 \\ \hline & BN & 2 \\ \hline & BU & 3 \\ \hline & & -(M) \\ \hline & BK & 4 \\ \hline & Q \\ \hline \end{array}$$

### Characteristic curve



- ① Reflector PL80A
- ② Reflector C110A
- 3 Reflector PL50A
- 4 Reflector PL40A
- ⑤ Reflector PL30A
- 6 Reflector PL20A
- 7 Reflective tape Diamond Grade

### Recommended accessories

Other models and accessories → www.sick.com/W11-2

	Brief description	Туре	part no.	
Mounting syst	Mounting systems			
	<ul> <li>Description: Mounting bracket, large</li> <li>Material: Stainless steel</li> <li>Details: Stainless steel</li> <li>Items supplied: Mounting hardware included</li> <li>Suitable for: W11-2, W12-3, W16</li> </ul>	BEF-WG-W12	2013942	
00 A 10	<ul> <li>Description: Universal mounting bracket for reflectors</li> <li>Dimensions (W x H x L): 85 mm x 90 mm x 35 mm</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Suitable for: C110A, P250, PL20, PL30A, PL40A, PL80A</li> </ul>	BEF-WN-REFX	2064574	
6	<ul> <li>Description: Plate N11N for universal clamp bracket</li> <li>Material: Stainless steel</li> <li>Details: Stainless steel 1.4571 (sheet), Stainless steel 1.4408 (clamp)</li> <li>Items supplied: Universal clamp (5322627), mounting hardware</li> <li>Usable for: DeltaPac, Glare, WTD20E</li> </ul>	BEF-KHS-N11N	2071081	
reflectors and	optics			
	<ul> <li>Description: Rectangular, screw connection</li> <li>Dimensions: 40 mm 60 mm</li> <li>Ambient operating temperature: -30 °C +65 °C</li> </ul>	PL4OA	1012720	
connectors ar	nd cables			
0	<ul> <li>Connection type head A: Female connector, M12, 4-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Sensor/actuator cable</li> <li>Cable: 5 m, 4-wire, PVC</li> <li>Description: Sensor/actuator cable, unshielded</li> <li>Application: Zones with chemicals, Uncontaminated zones</li> </ul>	YF2A14-050VB3XLEAX	2096235	
1	<ul> <li>Connection type head A: Male connector, M12, 4-pin, straight, A-coded</li> <li>Description: Unshielded</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm²</li> </ul>	STE-1204-G	6009932	
No.	<ul> <li>Connection type head A: Female connector, M12, 4-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Sensor/actuator cable</li> <li>Cable: 5 m, 4-wire, PUR, halogen-free</li> <li>Description: Sensor/actuator cable, unshielded</li> <li>Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li> </ul>	YF2A14-050UB3XLEAX	2095608	

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

