

GRTB18S-P1201VS23

GR18

PHOTOELECTRIC SENSORS





Ordering information

Туре	part no.
GRTB18S-P1201VS23	1122447

Other models and accessories → www.sick.com/GR18

Illustration may differ



Detailed technical data

Features

Functional principle	Photoelectric proximity sensor	
Functional principle detail	Background suppression	
Dimensions (W x H x D)	18 mm x 18 mm x 55.9 mm	
Housing design (light emission)	Cylindrical	
Housing length	55.9 mm	
Thread length	31.7 mm	
Thread diameter (housing)	M18 x 1	
Optical axis	Axial	
Sensing range max.	3 mm 250 mm ¹⁾	
Sensing range	20 mm 150 mm ¹⁾	
Type of light	Visible red light	
Light source	PinPoint LED ²⁾	
Light spot size (distance)	Ø 7 mm (100 mm)	
Wave length	650 nm	
Adjustment	None	
Display		
LED green	Operating indicator Static on: power on	
LED yellow	Status of received light beam Static on: object present Static off: object not present	

 $^{^{1)}}$ Object with 90% remission (based on standard white, DIN 5033).

 $^{^{2)}}$ Average service life: 100,000 h at TU = +25 °C.

Special applications	Hygienic and washdown zones	
Special features	Sensing range preset to 250 mm based on objects to be sensed with 90 $\%$ reflectivity	

¹⁾ Object with 90% remission (based on standard white, DIN 5033).

Mechanics/electronics

Supply voltage \mathbf{U}_{B}	10 V DC 30 V DC ¹⁾
Ripple	< 5 V _{pp} ²⁾
Current consumption	30 mA
Switching output	PNP
Output function	Complementary
Switching mode	Light/dark switching ³⁾
Signal voltage PNP HIGH/LOW	V _S - (≤ 3 V) / approx. 0 V
Output current I _{max.}	\leq 100 mA $^{4)}$
Response time	< 500 μs ⁵⁾
Switching frequency	1,000 Hz ⁶⁾
Connection type	Cable, 4-wire, 5 m ⁷⁾
Cable material	Plastic, PVC
Conductor cross section	0.14 mm ²
Cable diameter	Ø 4.8 mm
Circuit protection	A ⁸⁾ B ⁹⁾ D ¹⁰⁾
Protection class	III
Weight	100 g
Housing material	Metal, Stainless steel V4A (1.4404, 316L)
Optics material	Plastic, PMMA
Tightening torque, max.	90 Nm
Enclosure rating	IP67 IP68 ¹¹⁾ IP69K ¹²⁾
Items supplied	Fastening nuts (2 x)

 $^{^{1)}}$ Limit values. Operated in short-circuit protected network: max. 8 A.

 $^{^{2)}}$ Average service life: 100,000 h at TU = +25 °C.

 $^{^{2)}\,\}mbox{May}$ not fall below or exceed $\mbox{U}_{\mbox{\sc V}}$ tolerances.

 $^{^{3)}}$ Q = light switching; \bar{Q} = dark switching.

⁴⁾ At Uv > 24 V or ambient temperature > 49 °C, IA max. = 50 mA.

⁵⁾ Signal transit time with resistive load.

⁶⁾ With light/dark ratio 1:1.

⁷⁾ Do not bend below 0 °C.

 $^{^{8)}}$ A = V_S connections reverse-polarity protected.

⁹⁾ B = inputs and output reverse-polarity protected.

 $^{^{10)}}$ D = outputs overcurrent and short-circuit protected.

 $^{^{11)}}$ According to EN 60529 (10 m water depth / 24 h).

¹²⁾ According to ISO 20653:2013-03.

 $^{^{13)}}$ At U_V <=24V and I_A<50mA.

Electromagnetic compatibility (EMC)	EN 60947-5-2
Ambient operating temperature	-25 °C +55 °C ¹³⁾
Ambient temperature, storage	-30 °C +75 °C
UL File No.	NRKH.E348498 & NRKH7.E348498

 $^{^{1)}}$ Limit values. Operated in short-circuit protected network: max. 8 A.

Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
ECOLAB certificate	✓
cULus certificate	✓
Photobiological safety (DIN EN 62471) certificate	✓

Classifications

ECLASS 5.0	27270904
ECLASS 5.1.4	27270904
ECLASS 6.0	27270904
ECLASS 6.2	27270904
ECLASS 7.0	27270904
ECLASS 8.0	27270904
ECLASS 8.1	27270904
ECLASS 9.0	27270904
ECLASS 10.0	27270904
ECLASS 11.0	27270904
ECLASS 12.0	27270903
ETIM 5.0	EC002719
ETIM 6.0	EC002719
ETIM 7.0	EC002719
ETIM 8.0	EC002719
UNSPSC 16.0901	39121528
·	

 $^{^{2)}\,\}mbox{May}$ not fall below or exceed $\mbox{U}_{\mbox{\scriptsize V}}$ tolerances.

 $^{^{3)}}$ Q = light switching; $\boldsymbol{\bar{Q}}$ = dark switching.

 $^{^{4)}}$ At Uv > 24 V or ambient temperature > 49 °C, IA max. = 50 mA.

 $^{^{5)}}$ Signal transit time with resistive load.

⁶⁾ With light/dark ratio 1:1.

 $^{^{7)}}$ Do not bend below 0 °C.

 $^{^{8)}}$ A = V_S connections reverse-polarity protected.

 $^{^{9)}}$ B = inputs and output reverse-polarity protected.

 $^{^{10)}}$ D = outputs overcurrent and short-circuit protected.

 $^{^{11)}}$ According to EN 60529 (10 m water depth / 24 h).

¹²⁾ According to ISO 20653:2013-03.


 $^{^{13)}}$ At $\rm U_{V}$ <=24V and $\rm I_{A}{<}50mA.$


Connection diagram Cd-094



Characteristic curve GRTB18(S) Inox

Minimum distance between set sensing range and background (white, 90%) in % of sensing range







Example: Sensing range on black, 6% x = 100 mm, y = (10% of 100 mm) =10 mm

- ① Sensing range on black, 6 % remission
- 2 Sensing range on gray, 18 % remission
- 3 Sensing range on white, 90 % remission

Light spot size GRTB18(S)




Sensing range diagram



- Sensing range
- Sensing range max.
- ① Sensing range on black, 6% remission factor
- ② Sensing range on gray, 18% remission factor
- 3 Sensing range on white, 90% remission factor

Dimensional drawing GRTB18S Inox, cable, straight



Dimensions in mm (inch)

- ① Connection
- ② Threaded mounting hole M18 x 1
- 3 fastening nuts (2 x); width across 24, stainless steel
- ⑤ LED indicator (4 x)
- 6 optical axis, receiver
- ⑦ optical axis, sender
- Standard direction

Recommended accessories

Other models and accessories → www.sick.com/GR18

	Brief description	Туре	part no.
Mounting systems			
40	 Description: Mounting bracket for M18 sensors Material: Stainless steel Details: Stainless steel Items supplied: Without mounting hardware 	BEF-WN-M18N	5320947
connectors ar	nd cables		
	 Connection type head A: Male connector, M12, 4-pin, straight, A-coded Description: Unshielded Connection systems: Screw-type terminals Permitted cross-section: ≤ 0.75 mm² 	STE-1204-G	6009932

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

