

IM12-04NCP-ZW1

IM Standard

INDUCTIVE PROXIMITY SENSORS





Ordering information

Туре	part no.
IM12-04NCP-ZW1	7902929

Other models and accessories → www.sick.com/IM_Standard

Illustration may differ



Detailed technical data

Features

Housing	Metric
Housing	Standard design
Thread size	M12 x 1
Diameter	Ø 12 mm
Sensing range S _n	4 mm
Safe sensing range S _a	3.24 mm
Installation type	Non-flush
Switching frequency	1,000 Hz
Connection type	Cable, 4-wire, 2 m
Switching output	PNP / NPN
Switching output detail	PNP / NPN
Output function	NC / NO
Output characteristic	Wire configurable
Electrical wiring	DC 4-wire
Enclosure rating	IP67 ¹⁾

¹⁾ According to EN 60529.

Mechanics/electronics

Wednamed, creditation		
Supply voltage	10 V DC 30 V DC	
Ripple	≤ 10 % ¹⁾	
Voltage drop	\leq 1.2 V $^{2)}$	
Time delay before availability	≤ 250 ms	
Hysteresis	2 % 10 %	
Reproducibility	≤ 5 % ³⁾	

 $^{^{1)}}$ Of V_{S} .

²⁾ At L may

 $^{^{\}rm 3)}$ Supply voltage U_B and constant ambient temperature Ta.

⁴⁾ Of Sr.

	4)
Temperature drift (of S _r)	± 10 %
EMC	According to EN 60947-5-2
Continuous current I _a	≤ 100 mA
Cable material	PVC
Conductor size	0.22 mm ²
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	30 g, 11 ms / 10 55 Hz, 1 mm
Ambient operating temperature	-25 °C +70 °C
Housing material	Brass, Nickel-plated brass
Sensing face material	Plastic
Housing length	60 mm
Thread length	45 mm
Tightening torque, max.	≤ 10 Nm

 $^{^{1)}}$ Of V_{S} .

Reduction factors

Note	The values are reference values which may vary
Stainless steel (V2A, 304)	Approx. 0.8
Aluminum (AI)	Approx. 0.45
Copper (Cu)	Approx. 0.4

Installation note

Remark	Associated graphic see "Installation"
A	12 mm
В	24 mm
С	12 mm
D	12 mm
E	6 mm
F	32 mm

Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
Moroccan declaration of conformity	1
China RoHS	✓

Classifications

ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101

²⁾ At I_a max.

 $^{^{\}rm 3)}$ Supply voltage $\rm U_B$ and constant ambient temperature Ta.


⁴⁾ Of Sr


IM12-04NCP-ZW1 | IM Standard

INDUCTIVE PROXIMITY SENSORS

ECLASS 7.0 27270101 ECLASS 8.0 27270101 ECLASS 8.1 27270101 ECLASS 9.0 27270101 ECLASS 9.0 27270101 ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714 ETIM 7.0 EC002714	ECLASS 7.0 27270101 ECLASS 8.0 27270101 ECLASS 8.1 27270101 ECLASS 9.0 27270101 ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714		
ECLASS 8.0 27270101 ECLASS 8.1 27270101 ECLASS 9.0 27270101 ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714	ECLASS 8.0 27270101 ECLASS 8.1 27270101 ECLASS 9.0 27270101 ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714 ETIM 7.0 EC002714 ETIM 8.0 EC002714	ECLASS 6.2	27270101
ECLASS 8.1 27270101 ECLASS 9.0 27270101 ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714	ECLASS 8.1 27270101 ECLASS 9.0 27270101 ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714 ETIM 7.0 EC002714 ETIM 8.0 EC002714	ECLASS 7.0	27270101
ECLASS 9.0 27270101 ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714	ECLASS 9.0 27270101 ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714 ETIM 7.0 EC002714 ETIM 8.0 EC002714	ECLASS 8.0	27270101
ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714	ECLASS 10.0 27270101 ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714 ETIM 7.0 EC002714 ETIM 8.0 EC002714	ECLASS 8.1	27270101
ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714	ECLASS 11.0 27270101 ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714 ETIM 7.0 EC002714 ETIM 8.0 EC002714	ECLASS 9.0	27270101
ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714	ECLASS 12.0 27274001 ETIM 5.0 EC002714 ETIM 6.0 EC002714 ETIM 7.0 EC002714 ETIM 8.0 EC002714	ECLASS 10.0	27270101
ETIM 5.0 EC002714 ETIM 6.0 EC002714	ETIM 5.0 EC002714 ETIM 6.0 EC002714 ETIM 7.0 EC002714 ETIM 8.0 EC002714	ECLASS 11.0	27270101
ETIM 6.0 EC002714	ETIM 6.0 EC002714 ETIM 7.0 EC002714 ETIM 8.0 EC002714	ECLASS 12.0	27274001
	ETIM 7.0 EC002714 ETIM 8.0 EC002714	ETIM 5.0	EC002714
ETIM 7.0 EC002714	ETIM 8.0 EC002714	ETIM 6.0	EC002714
		ETIM 7.0	EC002714
ETIM 8.0 EC002714	UNSPSC 16.0901 39122230	ETIM 8.0	EC002714
UNSPSC 16.0901 39122230		UNSPSC 16.0901	39122230

Installation note Non-flush installation







Connection type




Connection diagram Cd-026





Dimensional drawing IM12, DC, cable, non-flush



Dimensions in mm (inch)

- ① Connection
- ② Display LED
- ③ Fastening nuts (2x); width across 17, metal

Recommended accessories

Other models and accessories → www.sick.com/IM_Standard

	Brief description	Туре	part no.
Mounting syst	ems		
	 Description: Clamping block for round sensors M12, with fixed stop Material: Plastic Details: Plastic (PA12), glass-fiber reinforced Items supplied: Mounting hardware included 	BEF-KHF-M12	2051480
	 Description: Clamping block for round sensors M12, without fixed stop Material: Plastic Details: Plastic (PA12), glass-fiber reinforced Items supplied: Mounting hardware included 	BEF-KH-M12	2051479
	 Description: Mounting plate for M12 sensors Material: Steel Details: Steel, zinc coated Items supplied: Without mounting hardware 	BEF-WG-M12	5321869
40	 Description: Mounting bracket for M12 sensors Material: Steel Details: Steel, zinc coated Items supplied: Without mounting hardware 	BEF-WN-M12	5308447

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

