Data sheet

# GRSE18S-P1336

## GR18

**PHOTOELECTRIC SENSORS**

SICK
Sensor Intelligence.

Illustration may differ

## Ordering information

| Type | part no. |
|---|---|
| GRSE18S-P1336 | 1059545 |

Other models and accessories ➜ www.sick.com/GR18

## Detailed technical data

### Features

| | |
|---|---|
| **Functional principle** | Through-beam photoelectric sensor |
| **Dimensions (W x H x D)** | 18 mm x 18 mm x 38.1 mm |
| **Housing design (light emission)** | Cylindrical |
| **Thread diameter (housing)** | M18 x 1 |
| **Optical axis** | Axial |
| **Sensing range max.** | 0 m ... 15 m |
| **Sensing range** | 0 m ... 10 m |
| **Type of light** | Visible red light |
| **Light source** | PinPoint LED [1] |
| **Light spot size (distance)** | Ø 250 mm (10 m) |
| **Wave length** | 650 nm |
| **Adjustment** | None |
| **Display** | |
| LED green | Operating indicator<br>Static on: power on |
| LED yellow | Status of received light beam<br>Static on: object not present<br>Static off: object present |

[1] Average service life: 100,000 h at $T_U$ = +25 °C.

## Mechanics/electronics

| | |
|---|---|
| **Supply voltage $U_B$** | 10 V DC ... 30 V DC [1] |
| **Ripple** | < 5 $V_{pp}$ [2] |
| **Current consumption** | 30 mA |
| **Switching output** | PNP |
| **Switching mode** | Light switching |
| **Signal voltage PNP HIGH/LOW** | $V_S$ - (≤ 3 V) / approx. 0 V |
| **Output current $I_{max.}$** | ≤ 100 mA [3] |
| **Response time** | < 500 µs [4] |
| **Switching frequency** | 1,000 Hz [5] |
| **Connection type** | Cable, 3-wire, 2 m [6] |
| **Cable material** | Plastic, PVC |
| **Circuit protection** | A [7]<br>B [8]<br>D [9] |
| **Protection class** | III |
| **Housing material** | Plastic, ABS |
| **Optics material** | Plastic, PMMA |
| **Enclosure rating** | IP67 |
| **Items supplied** | Fastening nuts (4 x) |
| **Electromagnetic compatibility (EMC)** | EN 60947-5-2 |
| **Ambient operating temperature** | –25 °C ... +55 °C [10] |
| **Ambient temperature, storage** | –40 °C ... +70 °C |
| **UL File No.** | NRKH.E348498 & NRKH7.E348498 |
| **Part number of individual components** | 2065196 GRS18S-D1336 2065199 GRE18S-P1336 |

[1] Limit values. Operated in short-circuit protected network: max. 8 A.
[2] May not fall below or exceed $U_V$ tolerances.
[3] At Uv > 24 V or ambient temperature > 49 °C, IA max. = 50 mA.
[4] Signal transit time with resistive load.
[5] With light/dark ratio 1:1.
[6] Do not bend below 0 °C.
[7] A = $V_S$ connections reverse-polarity protected.
[8] B = inputs and output reverse-polarity protected.
[9] D = outputs overcurrent and short-circuit protected.
[10] At $U_V$ <=24V and $I_A$<50mA.

## Certificates

| | |
|---|---|
| **EU declaration of conformity** | ✓ |
| **UK declaration of conformity** | ✓ |
| **ACMA declaration of conformity** | ✓ |
| **Moroccan declaration of conformity** | ✓ |
| **China RoHS** | ✓ |
| **ECOLAB certificate** | ✓ |
| **cULus certificate** | ✓ |

| | |
|---|---|
| **Photobiological safety (DIN EN 62471) certificate** | ✓ |

## Classifications

| | |
|---|---|
| **ECLASS 5.0** | 27270901 |
| **ECLASS 5.1.4** | 27270901 |
| **ECLASS 6.0** | 27270901 |
| **ECLASS 6.2** | 27270901 |
| **ECLASS 7.0** | 27270901 |
| **ECLASS 8.0** | 27270901 |
| **ECLASS 8.1** | 27270901 |
| **ECLASS 9.0** | 27270901 |
| **ECLASS 10.0** | 27270901 |
| **ECLASS 11.0** | 27270901 |
| **ECLASS 12.0** | 27270901 |
| **ETIM 5.0** | EC002716 |
| **ETIM 6.0** | EC002716 |
| **ETIM 7.0** | EC002716 |
| **ETIM 8.0** | EC002716 |
| **UNSPSC 16.0901** | 39121528 |

## Connection type



## Connection diagram Cd-049




① sender
② receiver

## Characteristic curve GRSE18S




## Light spot size GRSE18, red light




## Sensing range diagram GRSE18S



## Response range GRSE18S




## Dimensional drawing GR18S, plastic, cable, straight




Dimensions in mm (inch)
① Connection cable 2 m
② Threaded mounting hole M18 x 1
③ LED indicator yellow
④ LED indicator green
⑤ fastening nut; 22 mm hex, plastic
⑥ Mounting ring

## Recommended accessories

Other models and accessories ➜ www.sick.com/GR18

| | Brief description | Type | part no. |
|---|---|---|---|
| Mounting systems | | | |
| | • **Description:** Mounting bracket for M18 sensors<br>• **Material:** Steel<br>• **Details:** Steel, zinc coated<br>• **Items supplied:** Without mounting hardware<br>• **Suitable for:** GR18, V180-2, V18, W15, Z1, Z2 | BEF-WN-M18 | 5308446 |
| connectors and cables | | | |
| | • **Connection type head A:** Male connector, M8, 3-pin, straight, A-coded<br>• **Description:** Unshielded<br>• **Connection systems:** Screw-type terminals<br>• **Permitted cross-section:** 0.14 mm² ... 0.5 mm² | STE-0803-G | 6037322 |

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

# WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com



SICK
Sensor Intelligence.