

FX3-EBX300002

Interface modules

INTEGRATION MODULES AND ADAPTERS





Ordering information

| Туре | part no. |
|---------------|----------|
| FX3-EBX300002 | 2068728 |

Other models and accessories → www.sick.com/Interface_modules



Detailed technical data

Features

| Product segment | Integration modules and adapters |
|-----------------|----------------------------------|
| Product | Interface modules |
| Specialty | Motor feedback splitter box |

Classifications


| ECLASS 5.0 | 27243092 |
|----------------|----------|
| ECLASS 5.1.4 | 27243092 |
| ECLASS 6.0 | 27249204 |
| ECLASS 6.2 | 27249204 |
| ECLASS 7.0 | 27249204 |
| ECLASS 8.0 | 27249204 |
| ECLASS 8.1 | 27249204 |
| ECLASS 9.0 | 27243192 |
| ECLASS 10.0 | 27243192 |
| ECLASS 11.0 | 27243192 |
| ECLASS 12.0 | 27243192 |
| ETIM 5.0 | EC001604 |
| ETIM 6.0 | EC001604 |
| ETIM 7.0 | EC000474 |
| ETIM 8.0 | EC000474 |
| UNSPSC 16.0901 | 32151705 |

Certificates

| EU declaration of conformity | ✓ |
|------------------------------|---|
| UK declaration of conformity | ✓ |


| ACMA declaration of conformity | ✓ |
|--------------------------------|---|
| China-RoHS | ✓ |
| cULus certificate | ✓ |

Dimensional drawing



Dimensions in mm (inch)

PIN assignment




| Spring terminals | PIN | Signal | Description |
|------------------|-----|---------|---|
| C1 | 1 | NC2 | Do not connect. Used to forward a signal. |
| | 2 | NC1 | Do not connect. Used to forward a signal. |
| | 3 | U_out | Encoder voltage supply of the on-board voltage supply of this motor feedback splitter box |

FX3-EBX300002 | Interface modules

INTEGRATION MODULES AND ADAPTERS


| Spring terminals | PIN | Signal | Description |
|------------------|-----|---------|--|
| | 4 | ENCx_OV | GND encoder connection |
| | 5 | ENCx_C- | Encoder, channel C, negative signal |
| | 6 | ENCx_C+ | Encoder, channel C, positive signal |
| | 7 | ENCx_B- | Encoder, channel B, negative signal |
| | 8 | ENCx_B+ | Encoder, channel B, positive signal |
| | 9 | ENCx_A- | Encoder, channel A, negative signal |
| | 10 | ENCx_A+ | Encoder, channel A, positive signal |
| - | - | - | - |
| C1 | 1 | NC | Do not connect. Used |
| | 2 | NC | to forward a signal. |
| | 3 | NC | |
| | 4 | NC | |
| | 5 | NC | |
| | 6 | NC | |
| | 7 | NC | |
| | 8 | NC | |

PIN assignment



| PIN | Signal | Description |
|-----|---------|--|
| 1 | ENC_A+ | Encoder, channel A, positive signal |
| 2 | ENC_B+ | Encoder, channel B, positive signal |
| 3 | ENC_C+ | Encoder, channel C, positive signal |
| 4 | ENC_24V | 24 V voltage supply for encoder/hardware ID connection box |
| 5 | ENC_ID | Encoder splitter box ID |
| 6 | ENC_A- | Encoder, channel A, negative signal |
| 7 | ENC_B- | Encoder, channel B, negative signal |
| 8 | ENC_C- | Encoder, channel C, negative signal |
| 9 | ENC_OV | GND encoder connection |

PIN assignment



| PIN | Signal | Description |
|-----|----------|--|
| 1 | ENC1_A+ | Encoder 1, signal pair A, positive signal |
| 2 | ENC1_A- | Encoder 1, signal pair A, negative signal |
| 3 | ENC1_24V | 24 V voltage supply for encoder 1 |
| 4 | ENC2_A+ | Encoder 2, signal pair A, positive signal |
| 5 | ENC2_A- | Encoder 2, signal pair A, negative signal |
| 6 | ENC1_B+ | Encoder 1, signal pair B, positive signal |
| 7 | ENC1_B- | Encoder 1, signal pair B, negative signal |
| 8 | ENC_OV | 0 V voltage supply for encoder 1 and encoder 2 |
| 9 | ENC2_B+ | Encoder 2, signal pair B, positive signal |
| 10 | ENC2_B- | Encoder 2, signal pair B, negative signal |
| 11 | ENC1_C+ | Encoder 1, signal pair C, positive signal |
| 12 | ENC1_C- | Encoder 1, signal pair C, negative signal |
| 13 | ENC2_24V | 24 V voltage supply for encoder 2 |
| 14 | ENC2_C+ | Encoder 2, signal pair C, positive signal |
| 15 | ENC2_C- | Encoder 2, signal pair C, negative signal |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

