

# IME12-04BPSZW6KS56

**INDUCTIVE PROXIMITY SENSORS** 



## Ordering information

Туре	part no.
IME12-04BPSZW6KS56	1093752

Included in delivery: BEF-MU-M12 (1)

Other models and accessories → www.sick.com/IME

Illustration may differ



## Detailed technical data

#### **Features**

Housing	Metric
Housing	Short-body
Thread size	M12 x 1
Diameter	Ø 12 mm
Sensing range S <sub>n</sub>	4 mm
Safe sensing range S <sub>a</sub>	3.24 mm
Installation type	Flush
Switching frequency	2,000 Hz
Connection type	Cable, 3-wire, 10 m
Switching output	PNP
Switching output detail	PNP
Output function	NO
Electrical wiring	DC 3-wire
Enclosure rating	IP65 <sup>1)</sup>
Special characteristic	Continuous thread with 2 LEDs
Items supplied	Mounting nut, brass, nickel-plated (2x)

<sup>&</sup>lt;sup>1)</sup> According to EN 60529.

## Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 %

<sup>&</sup>lt;sup>1)</sup> At I<sub>a</sub> max.

 $<sup>^{\</sup>rm 2)}$  Supply voltage  $U_{B}$  and constant ambient temperature Ta.

<sup>&</sup>lt;sup>3)</sup> Of Sr.

Voltage drop	$\leq$ 2 V $^{1)}$
Time delay before availability	≤ 100 ms
Hysteresis	5 % 15 %
Reproducibility	≤ 2 % <sup>2)</sup> 3)
Temperature drift (of S <sub>r</sub> )	± 10 %
EMC	According to EN 60947-5-2
Continuous current I <sub>a</sub>	≤ 200 mA
No load current	≤ 10 mA
Cable material	PVC
Conductor size	0.25 mm <sup>2</sup>
Cable diameter	Ø 3.9 mm
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	30 g, 11 ms/10 Hz 55 Hz, 1 mm
Ambient operating temperature	-25 °C +75 °C
Housing material	Brass, nickel-plated
Sensing face material	Plastic, PA 66
Housing length	44 mm
Thread length	41 mm
Tightening torque, max.	≤ 12 Nm
UL File No.	NRKH.E181493

 $<sup>^{1)}</sup>$  At I $_{\rm a}$  max.

## **Reduction factors**

Note	The values are reference values which may vary
St37 steel (Fe)	1
Stainless steel (V2A, 304)	Approx. 0.8
Aluminum (AI)	Approx. 0.45
Copper (Cu)	Approx. 0.4
Brass (Br)	Approx. 0.4

## Installation note

Remark	Associated graphic see "Installation"
В	24 mm
c	12 mm
D	12 mm
F	32 mm

## Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓

<sup>&</sup>lt;sup>2)</sup> Supply voltage U<sub>B</sub> and constant ambient temperature Ta.

<sup>&</sup>lt;sup>3)</sup> Of Sr.

## IME12-04BPSZW6KS56 | IME


## INDUCTIVE PROXIMITY SENSORS


ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
cULus certificate	✓

## Classifications


FOLACC F O	27270404
ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101
ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714
UNSPSC 16.0901	39122230

## Installation note Flush installation






## Connection diagram Cd-001



## Dimensional drawing



Dimensions in mm (inch)

- ① Connection
- ② Fastening nuts (2x); width across 17, metal

## Recommended accessories

Other models and accessories → www.sick.com/IME

	Brief description	Туре	part no.
Mounting systems			
	<ul> <li>Description: Clamping block for round sensors M12, with fixed stop</li> <li>Material: Plastic</li> <li>Details: Plastic (PA12), glass-fiber reinforced</li> <li>Items supplied: Mounting hardware included</li> </ul>	BEF-KHF-M12	2051480
	<ul> <li>Description: Mounting plate for M12 sensors</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Without mounting hardware</li> </ul>	BEF-WG-M12	5321869
40	<ul> <li>Description: Mounting bracket for M12 sensors</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Without mounting hardware</li> </ul>	BEF-WN-M12	5308447
	<ul> <li>Description: Clamping block for round sensors M12, without fixed stop</li> <li>Material: Plastic</li> <li>Details: Plastic (PA12), glass-fiber reinforced</li> <li>Items supplied: Mounting hardware included</li> </ul>	BEF-KH-M12	2051479

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

