

GRTE18S-P2317

GR18

PHOTOELECTRIC SENSORS





Ordering information

| Туре | part no. |
|---------------|----------|
| GRTE18S-P2317 | 1058196 |

Other models and accessories → www.sick.com/GR18

Illustration may differ



Detailed technical data

Features

| Functional principle | Photoelectric proximity sensor |
|---------------------------------|--|
| Functional principle detail | Energetic |
| Dimensions (W x H x D) | 18 mm x 18 mm x 38.1 mm |
| Housing design (light emission) | Cylindrical |
| Thread diameter (housing) | M18 x 1 |
| Optical axis | Axial |
| Sensing range max. | 3 mm 115 mm ¹⁾ |
| Sensing range | 5 mm 100 mm ¹⁾ |
| Type of light | Visible red light |
| Light source | PinPoint LED ²⁾ |
| Light spot size (distance) | Ø 8 mm (100 mm) |
| Wave length | 650 nm |
| Adjustment | Potentiometer, 270° |
| Display | |
| LED gi | een Operating indicator Static on: power on |
| LED ye | Status of received light beam Static on: object present Static off: object not present |

 $^{^{1)}}$ Object with 90% remission (based on standard white, DIN 5033).

²⁾ Average service life: 100,000 h at $T_U = +25$ °C.

Mechanics/electronics

| Supply voltage U _B | 10 V DC 30 V DC ¹⁾ |
|-------------------------------------|---|
| Ripple | < 5 V _{pp} ²⁾ |
| Current consumption | 30 mA |
| Switching output | PNP |
| Switching mode | Light switching |
| Signal voltage PNP HIGH/LOW | V_S - ($\leq 3 V$) / approx. $0 V$ |
| Output current I _{max.} | \leq 100 mA $^{3)}$ |
| Response time | < 1,000 µs ⁴⁾ |
| Switching frequency | 500 Hz ⁵⁾ |
| Connection type | Connector M12, 3-pin |
| Circuit protection | A ⁶⁾ B ⁷⁾ D ⁸⁾ |
| Protection class | III |
| Housing material | Plastic, ABS |
| Optics material | Plastic, PMMA |
| Enclosure rating | IP67 |
| Items supplied | Fastening nuts (2 x) |
| Electromagnetic compatibility (EMC) | EN 60947-5-2 |
| Ambient operating temperature | -25 °C +55 °C ⁹⁾ |
| Ambient temperature, storage | -40 °C +70 °C |
| UL File No. | NRKH.E348498 & NRKH7.E348498 |

 $^{^{1)}}$ Limit values. Operated in short-circuit protected network: max. 8 A.

Safety-related parameters

| MTTF _D | 1,930 years |
|-------------------|-------------|
| DC _{avg} | 0 % |

Certificates

| EU declaration of conformity | ✓ |
|------------------------------------|---|
| UK declaration of conformity | ✓ |
| ACMA declaration of conformity | ✓ |
| Moroccan declaration of conformity | ✓ |
| China RoHS | ✓ |
| ECOLAB certificate | ✓ |

 $^{^{2)}}$ May not fall below or exceed U_{V} tolerances.

 $^{^{3)}}$ At Uv > 24 V or ambient temperature > 49 °C, IA max. = 50 mA.

 $^{^{4)}}$ Signal transit time with resistive load.

⁵⁾ With light/dark ratio 1:1.

 $^{^{6)}}$ A = V_S connections reverse-polarity protected.

 $^{^{7)}}$ B = inputs and output reverse-polarity protected.

 $^{^{8)}}$ D = outputs overcurrent and short-circuit protected.

 $^{^{9)}}$ At $\rm U_{v}$ <=24V and $\rm I_{A}{<}50mA.$

GRTE18S-P2317 | GR18

PHOTOELECTRIC SENSORS

| cULus certificate | ✓ |
|---|---|
| Photobiological safety (DIN EN 62471) certificate | ✓ |

Classifications

| ECLASS 5.0 | 27270903 |
|----------------|----------|
| ECLASS 5.1.4 | 27270903 |
| ECLASS 6.0 | 27270903 |
| ECLASS 6.2 | 27270903 |
| ECLASS 7.0 | 27270903 |
| ECLASS 8.0 | 27270903 |
| ECLASS 8.1 | 27270903 |
| ECLASS 9.0 | 27270903 |
| ECLASS 10.0 | 27270904 |
| ECLASS 11.0 | 27270904 |
| ECLASS 12.0 | 27270903 |
| ETIM 5.0 | EC001821 |
| ETIM 6.0 | EC001821 |
| ETIM 7.0 | EC002719 |
| ETIM 8.0 | EC002719 |
| UNSPSC 16.0901 | 39121528 |

Adjustments GRTB18(S), GRTE18(S), Sensing range setting: Potentiometer, 270°

Sensing range





Connection type




Connection diagram Cd-045



Characteristic curve GRTE18S, 100 mm


Operating reserve



Distance in mm (inch)


- ① Sensing range on black, 6% remission factor
- ② sensing range to gray, 20% remission factor
- 3 Sensing range on white, 90% remission factor

Light spot size GRTE18S, 100 mm



dimensions in mm (inch)

Sensing range diagram GRTE18S, 100 mm




Sensing range

Sensing range max.


- ① Sensing range on black, 6% remission factor
- 2) sensing range to gray, 20% remission factor
- $\ensuremath{\mathfrak{G}}$ Sensing range on white, 90% remission factor

Response range GRTE18S, 100 mm

Parallel operating range y in mm (inch)



Dimensional drawing GR18S, plastic, connector, straight, adjustable



Dimensions in mm (inch)

- ① Connector M12, 3-pin
- ② Threaded mounting hole M18 x 1
- 3 LED indicator yellow
- 4 LED indicator green
- ⑤ sensitivity control: potentiometer 270°
- 6 fastening nut; 22 mm hex, plastic
- ⑦ Mounting ring

Recommended accessories

Other models and accessories → www.sick.com/GR18

| | Brief description | Туре | part no. |
|--------------|--|------------|----------|
| Mounting sys | tems | | |
| 40 | Description: Mounting bracket for M18 sensors Material: Steel Details: Steel, zinc coated Items supplied: Without mounting hardware Suitable for: GR18, V180-2, V18, W15, Z1, Z2 | BEF-WN-M18 | 5308446 |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

