



SIU2-L0011A002

Display modules

INTEGRATION MODULES AND ADAPTERS

SICK
Sensor Intelligence.



Ordering information

Type	part no.
SIU2-L0011A002	2084701

Other models and accessories → www.sick.com/Display_modules



Detailed technical data

Features

Accessory group	Display modules
Description	Operator panel for the Inspector VSP product family, except VSPI-4xxxx. The operator panel supports the display of images and results, switching between recipes, and the management of Inspector configurations. The Inspector Viewer has a 100 Mbit/s Ethernet interface and requires a 24 V DC voltage supply.
Housing material	Aluminum alloy
Enclosure rating	IP65
Ambient operating temperature	0 °C ... +50 °C
Storage temperature	-40 °C ... +75 °C
Dimensions (W x H x L)	19 cm x 14 cm x 6.4 cm
Weight	1.45 kg

Certificates


EU declaration of conformity	✓
China-RoHS	✓

Classifications

ECLASS 5.0	19029001
ECLASS 5.1.4	19029001
ECLASS 6.0	19140390
ECLASS 6.2	19140390
ECLASS 7.0	19140390
ECLASS 8.0	19140390
ECLASS 8.1	19140390
ECLASS 9.0	19140390
ECLASS 10.0	19140390
ECLASS 11.0	19140390
ECLASS 12.0	19140390
ETIM 5.0	EC001428
ETIM 6.0	EC001428
ETIM 7.0	EC001428

ETIM 8.0	EC001428
----------	----------

Dimensional drawing



Dimensions in mm (inch)

Recommended accessories

Other models and accessories → www.sick.com/Display_modules

	Brief description	Type	part no.
connectors and cables			
	• Connection type head A: Female connector, M12, 4-pin, straight, A-coded • Connection type head B: Flying leads • Signal type: Sensor/actuator cable • Cable: 2 m, 4-wire, PUR, halogen-free • Description: Sensor/actuator cable, unshielded • Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-020UB3XLEAX	2095607
	• Connection type head A: Female connector, M12, 4-pin, straight, A-coded • Connection type head B: Flying leads • Signal type: Sensor/actuator cable • Cable: 0.6 m, 4-wire, PUR, halogen-free • Description: Sensor/actuator cable, unshielded • Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-C60UB3XLEAX	2145654
	• Connection type head A: Female connector, M12, 4-pin, straight, A-coded • Connection type head B: Flying leads • Signal type: Sensor/actuator cable • Cable: 1 m, 4-wire, PUR, halogen-free • Description: Sensor/actuator cable, unshielded • Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-010UB3XLEAX	2145655
	• Connection type head A: Female connector, M12, 4-pin, straight, A-coded • Connection type head B: Flying leads • Signal type: Sensor/actuator cable • Cable: 3 m, 4-wire, PUR, halogen-free • Description: Sensor/actuator cable, unshielded • Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation	YF2A14-030UB3XLEAX	2145656

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com