

Base station

Base stations

RECHARGEABLE BATTERIES AND BASE STATIONS





Ordering information

Туре	part no.
Base station	4112984

Other models and accessories → www.sick.com/Base_stations

Detailed technical data

Features

Description	Charging/Communication station for HW1911 / HW1991, Bluetooth class 1, 100 m, host interfaces: RS-232 / USB / KBW (Honeywell CCB22-100BT-03N)
Items supplied	Accessories not included with delivery, please order separately.
Weight	295 g
Enclosure rating	IP51
Dimensions (W x H x L)	245 mm 60 mm 102 mm
Operating voltage	4 V DC 5.5 V DC
Power consumption	Charging (5 V DC), standby 1 A, 120 mA
Ambient operating temperature	-20 °C +50 °C
Storage temperature	-40 °C +70 °C
Housing color	Gray

Classifications

ECLASS 5.0	27050604
ECLASS 5.1.4	27050604
ECLASS 6.0	27050604
ECLASS 6.2	27050604
ECLASS 7.0	27050604
ECLASS 8.0	27050604
ECLASS 8.1	27050604
ECLASS 9.0	27050604
ECLASS 10.0	27050604
ECLASS 11.0	27050604
ECLASS 12.0	27280105
ETIM 5.0	EC000359
ETIM 6.0	EC000359
ETIM 7.0	EC000359
ETIM 8.0	EC000359
UNSPSC 16.0901	26111704

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

