

WLA16P-1I722100ZZZ W16

PHOTOELECTRIC SENSORS





Ordering information

Туре	part no.
WLA16P-1I722100ZZZ	1222787

Other models and accessories → www.sick.com/W16

Illustration may differ



Detailed technical data

Features

Functional principle	Photoelectric retro-reflective sensor
Functional principle detail	Without reflector minimum distance (autocollimation/coaxial optics)
Sensing range	
Sensing range min.	0 m
Sensing range max.	10 m
Maximum distance range from reflector to sensor (operating reserve 1)	0 m 10 m
Recommended distance range from reflector to sensor (operating reserve 3,75)	0 m 7 m
Reference reflector	Reflector PL80A
Recommended sensing range for the best performance	0 m 7 m
Polarisation filters	Yes
Emitted beam	
Light source	PinPoint LED
Type of light	Visible red light
Shape of light spot	Point-shaped
Light spot size (distance)	Ø 80 mm (5 m)
Maximum dispersion of the emitted beam around the standardized transmission axis (squint angle)	< +/- 1.0° (at Ta = +23 °C)
Key LED figures	

Normative reference	EN 62471:2008-09 IEC 62471:2006, modified
LED risk group marking	Free group
Wave length	635 nm
Average service life	100,000 h at T_a = +25 °C
Adjustment	
Wire/pin	For activating the test input
Display	
LED blue	BluePilot: Alignment aid
LED green	Operating indicator Static on: power on
LED yellow	Status of received light beam Static on: object not present Static off: object present Flashing: Below the 1.5 function reserve
Special applications	Detecting objects wrapped in film

Safety-related parameters

MTTF _D	690 years
DC _{avg}	0 %
T _M (mission time)	20 years

Electronics

pply voltage U _B	10 V DC 30 V DC ¹⁾
pple	≤ 5 V _{pp}
age category	DC-12 (According to EN 60947-5-2) DC-13 (According to EN 60947-5-2)
rrent consumption	\leq 30 mA, without load. At U _B = 24 V 2
otection class	III
gital output	
Numbe	r 2 (Complementary)
Туро	Push-pull: PNP/NPN
Switching mode	e Light/dark switching
Signal voltage PNP HIGH/LOV	V Approx. U _B -2.5 V / 0 V
Signal voltage NPN HIGH/LOV	V Approx. $U_B / < 2.5 V$
Output current I _{max}	. ≤ 100 mA
Circuit protection output	Reverse polarity protected
	Overcurrent and short-circuit protected
Response time	e ≤ 500 μs ³⁾
Repeatability (response time) 150 μs
Switching frequency	1,000 Hz ⁴⁾
Switching frequency	⁴ 1,000 Hz ⁴⁾

¹⁾ Limit values.

²⁾ 10 V DC ... 16 V DC, without load.
³⁾ Signal transit time with resistive load in switching mode.

⁴⁾ With light/dark ratio 1:1.

⁵⁾ This switching output must not be connected to another output.

Pin/Wire assignment	
Function of pin 4/black (BK)	Digital output, dark switching, object present \rightarrow output \bar{Q} HIGH $^{5)}$
Function of pin 2/white (WH)	Digital output, light switching, object present \rightarrow output Q LOW $^{5)}$
Pin 5 function/gray (GY)	Digital input, sender off, LOW active

¹⁾ Limit values.

Mechanics

Housing	Rectangular
Dimensions (W x H x D)	20 mm x 55.7 mm x 42 mm
Connection	Cable, 5-wire, 2 m
Connection detail	
Deep-freeze property	Do not bend below 0 °C
Conductor size	0.14 mm ²
Cable diameter	Ø 4.8 mm
Length of cable (L)	2 m
Bending radius	For flexible use > 12 x cable diameter
Bending cycles	1,000,000
Material	
Housing	Plastic, VISTAL®
Front screen	Plastic, PMMA
Cable	Plastic, PVC
Weight	Approx. 100 g
Maximum tightening torque of the fixing screws	1.3 Nm

Ambient data

Enclosure rating	IP66 (EN 60529) IP67 (EN 60529) IP69 (EN 60529) ¹⁾
Ambient operating temperature	-40 °C +60 °C
Ambient temperature, storage	-40 °C +75 °C
Shock resistance	50 g, 11 ms (25 positive and 25 negative shocks per axis, for X, Y, Z axes, 150 shocks in total (EN60068-2-27)) 50 g, 6 ms (5,000 positive and 5,000 negative shocks per axis, for X, Y, Z axes, $30,\!000$ shocks in total (EN60068-2-27))
Vibration resistance	10 Hz 2,000 Hz (Amplitude 0.5 mm / 10 g, 20 sweeps per axis, for X, Y, Z axes, 1 octave/min, (EN60068-2-6))
Air humidity	35 % 95 %, relative humidity (no condensation)
Electromagnetic compatibility (EMC)	EN 60947-5-2
Resistance to cleaning agent	ECOLAB
UL File No.	NRKH.E181493 & NRKH7.E181493

¹⁾ Replaces IP69K with ISO 20653: 2013-03.

 $^{^{2)}}$ 10 V DC ... 16 V DC, without load.

 $^{^{\}rm 3)}$ Signal transit time with resistive load in switching mode.

⁴⁾ With light/dark ratio 1:1.

⁵⁾ This switching output must not be connected to another output.


Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
ECOLAB certificate	✓
cULus certificate	✓
Photobiological safety (DIN EN 62471) certificate	✓

Classifications

ECLASS 5.0	27270902
ECLASS 5.1.4	27270902
ECLASS 6.0	27270902
ECLASS 6.2	27270902
ECLASS 7.0	27270902
ECLASS 8.0	27270902
ECLASS 8.1	27270902
ECLASS 9.0	27270902
ECLASS 10.0	27270902
ECLASS 11.0	27270902
ECLASS 12.0	27270902
ETIM 5.0	EC002717
ETIM 6.0	EC002717
ETIM 7.0	EC002717
ETIM 8.0	EC002717
UNSPSC 16.0901	39121528

Dimensional drawing, sensor




WLA16P-11722100ZZZ | W16

PHOTOELECTRIC SENSORS

- ① Center of optical axis
- ② Mounting hole, Ø 4.1 mm
- ③ Connection
- (4) display and adjustment elements

display and adjustment elements




- ① LED indicator green
- ② LED indicator yellow
- ③ LED blue

Connection type Cable, 5-wire



Connection diagram Cd-141



Truth table Push-pull: PNP/NPN – dark switching \bar{Q}


	Dark switching $\overline{\mathbb{Q}}$ (normally open (upper switch), normally closed (lower switch))	
	Object not present → Output LOW	Object present → Output HIGH
Light receive		
Light receive indicator	:	
Load resistance to L+	A	
Load resistance to M		<u>A</u>
	+ (L+) Q - (M)	+ (L+) \(\overline{Q}\) - (M)

Truth table Push-pull: PNP/NPN - light switching Q

	Light switching Q (normally closed (upper switch), normally open (lower switch))	
	Object not present → Output HIGH	Object present → Output LOW
Light receive		
Light receive indicator	: :	
Load resistance to L+		A
Load resistance to M	A	
	+ (L+) Q Q - (M)	+ (L+) Q - (M)

Characteristic curve Chemical-resistant reflectors






Recommended sensing range for the best performance

- ① PL10F CHEM reflector
- ② Reflector PL20 CHEM
- 3 Reflector P250 CHEM
- 4 Reflector P250H
- **⑤** Reflector PL40A Antifog

Characteristic curve Standard reflectors

Operating reserve




- Recommended sensing range for the best performance
- ① Reflector PL22
- ② Reflector P250, PL30A
- 3 Reflector PL20A

- 4 Reflector PL40A
- ⑤ Reflector PL80A, C110A

Characteristic curve Fine triple reflectors


Operating reserve



- Recommended sensing range for the best performance
- ① PL10FH-1 reflector
- ② PL10F reflector
- 3 Reflector PL20F
- 4 Reflector P250F


Characteristic curve Reflective tape








- Recommended sensing range for the best performance
- ① Reflective tape REF-DG (50 x 50 mm)
- ② Reflective tape REF-IRF-56 (50 x 50 mm)
- 3 Reflective tape REF-AC1000 (50 x 50 mm)

Light spot size WLA16P-xxxxx1xx










Sensing range diagram Standard reflectors




Recommended sensing range for the best performance

WLA16P-xxxxx1xx

1	Reflector PL22	
2	Reflector P250, PL30A	
3	Reflector PL20A	
4	Reflector PL40A	
5	Reflector PL80A, C110A	
A	Sensing range min. in m	
В	Sensing range max. in m	
С	Maximum distance range from reflector to sensor (operating reserve 1)	
D	Recommended distance range from re- flector to sensor (operating reserve 3,75)	

Sensing range diagram Chemical-resistant reflectors



Recommended sensing range for the best performance

WLA16P-xxxxx1xx


1	PL10F CHEM reflector
2	Reflector PL20 CHEM

WLA16P-11722100ZZZ | W16

PHOTOELECTRIC SENSORS

3	Reflector P250 CHEM	
4	Reflector P250H	
5	Reflector PL40A Antifog	
A	Sensing range min. in m	
В	Sensing range max. in m	
С	Maximum distance range from reflector to sensor (operating reserve 1)	
D	Recommended distance range from re- flector to sensor (operating reserve 3,75)	

Sensing range diagram Fine triple reflectors




Recommended sensing range for the best performance

WLA16P-xxxxx1xx

1	PL10FH-1 reflector	
2	PL10F reflector	
3	Reflector PL20F	
4	Reflector P250F	
Α	Sensing range min. in m	
В	Sensing range max. in m	
С	Maximum distance range from reflector to sensor (operating reserve 1)	
D	Recommended distance range from re- flector to sensor (operating reserve 3,75)	

Sensing range diagram Reflective tape




Recommended sensing range for the best performance

WLA16P-xxxxx1xx

1	Reflective tape REF-DG (50 x 50 mm)	
2	Reflective tape REF-IRF-56 (50 x 50 mm)	
3	Reflective tape REF-AC1000 (50 x 50 mm)	
А	Sensing range min. in m	
В	Sensing range max. in m	
С	Maximum distance range from reflector to sensor (operating reserve 1)	
D	Recommended distance range from re- flector to sensor (operating reserve 3,75)	

Functions Operation note



At a sensing range of "x" the photoelectric retro-reflective and through-beam photoelectric sensors have different operating reserves (see blue arrow). The higher the operating reserve factor, the better the sensor can compensate the contamination in the air or in the light beam and on the optical surfaces (front screen, reflector), i.e. the sensor has the maximum availablity, otherwise the sensor switches due to pollution although there is no object in the path of the light beam.

Functions Operation note

BluePilot: Blue indicator LEDs with double benefits

Easy and quick sensor alignment with the help of the LED indicator

All blue LEDs illuminate
- optimum alignment
- highest possible operating reserve

Service note
A reduction in sensor availability is displayed by a decrease of the blue LEDs.

Possible causes:
a) insufficient alignment
b) contamination of the optical surfaces
c) particles in the light beam

WLA photoelectric retro-reflection sensor alignment

WLA photoelectric retro-reflection sensor alignment

Output

Description

Recommended accessories

Other models and accessories → www.sick.com/W16

	Brief description	Туре	part no.		
Mounting systems					
	 Description: Mounting bracket with articulated arm Material: Steel Details: Steel, zinc coated Items supplied: Mounting hardware included Suitable for: W16, W26, W11, W12, W23, W27, Dx50, W280, G10 	BEF-WN-MULTI2	2093945		
	 Description: Plate NO2 for universal clamp bracket Material: Steel, zinc diecast Details: Zinc plated steel (sheet), Zinc die cast (clamping bracket) Items supplied: Universal clamp (5322626), mounting hardware Usable for: W4S-3 Glass, W10, W4SLG-3, W4S-3 Inox, W4S-3 Inox Glass, W9, W11-2, W12-3, W12-2 Laser, W12G, W12 Teflon, W16, W250, W250-2, PowerProx, W11G-2, TranspaTect, WTT12, UC12, P250, G6 Inox, W4S, W4SL-3V, W4SLG-3V, W4SL-3H 	BEF-KHS-N02	2051608		
	 Description: Mounting bracket, large Material: Stainless steel Details: Stainless steel Items supplied: Mounting hardware included Suitable for: W11-2, W12-3, W16 	BEF-WG-W12	2013942		
W T	 Description: Adapter for mounting W16 sensors in existing W14-2/W18-3 installations or L25 sensors in existing L28 installations Material: Plastic Details: Plastic Items supplied: Fastening screws included 	BEF-AP-W16	2095677		
a a a a	 Description: Universal mounting bracket for reflectors Dimensions (W x H x L): 85 mm x 90 mm x 35 mm Material: Steel Details: Steel, zinc coated Suitable for: C110A, P250, PL20, PL30A, PL40A, PL80A 	BEF-WN-REFX	2064574		
reflectors and	reflectors and optics				
area Carre	 Description: Rectangular, screw connection Dimensions: 84 mm 84 mm Ambient operating temperature: -30 °C +65 °C 	PL80A	1003865		
connectors and cables					
	Connection type head A: Male connector, M12, 5-pin, straight, A-coded Description: Unshielded Connection systems: Screw-type terminals Permitted cross-section: ≤ 0.75 mm² Note: For field bus technology	STE-1205-G	6022083		

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

