

V2D631R-MXSXB0

Lector63x

IMAGE-BASED CODE READERS

SICKSensor Intelligence.



Ordering information

Туре	part no.
V2D631R-MXSXB0	1078472

Other models and accessories → www.sick.com/Lector63x



Detailed technical data

Features

Variant	Main unit	
Optical focus	Adjustable focus (manual)	
Sensor	CMOS monochrome	
Sensor resolution	1,280 px x 1,024 px (1.3 MP)	
Illumination	To be ordered separately as accessories	
Alignment aid	Laser, Red, 630 nm 680 nm	
Laser class	1, Complies with 21 CFR 1040.10 and 1040.11 except for conformance with IEC 60825-1 Ed.3., as described in "Laser Notice No. 56" dated May 8, 2019 (IEC 60825-1:2014, EN 60825-1:2014+A11:2021)	
Lens	S-mount	
Optical format	1/1.8"	
Note	To be ordered separately as accessories	
Scanning frequency ≤ 50 Hz, With resolution of 1.3 megapixels		
Code resolution $\geq 0.1 \text{ mm}^{-1}$		
Working range	50 mm 2,200 mm ^{2) 3)}	

 $^{^{1)}}$ Depends on lens used, for details see field of view diagram.

Mechanics/electronics

Connection type	1 x M12, 17-pin plug (serial, CAN, I/Os, power supply)
	1 x M12, 8-pin socket (Ethernet, 1 GBit/s) 1 x M8, 4-pin socket (USB)
	1 x M12, 4-pin socket (external illumination control)

 $^{^{1)}\,\}mathrm{Housing}$ only, without lens and optics protection hood.

²⁾ Depends on lens used.

³⁾ For details see field of view diagram.

Supply voltage	12 V DC 24 V DC, ± 20 %
Power consumption	Typ. 10 W, ± 20 %
Output current	≤ 100 mA
Housing material	Aluminum die cast
Window material	Plastic (To be ordered separately as accessories) Glass (To be ordered separately as accessories)
Enclosure rating	IP67 (EN 60529 (1991-10), EN 60529/A2 (2002-02))
Electrical safety	EN 60950-1 (2011-01)
Weight	+ 430 g, without lens and connection cables
Dimensions (L x W x H)	108 mm x 63.1 mm x 45.8 mm ¹⁾

 $^{^{1)}\,\}mathrm{Housing}$ only, without lens and optics protection hood.

Performance

Readable code structures	1D codes, Stacked, 2D codes
Bar code types	GS1-128 / EAN 128, UPC / GTIN / EAN, Interleaved 2 of 5, Pharmacode, GS1 DataBar, Code 39, Code 128, Codabar, Code 32, Code 93, USPS (Postnet, Planet, USPS4SCB), Australian Post, Dutch KIX Post, Royal Mail, Swedish Post
2D code types	Data Matrix ECC200, GS1 Data-Matrix, MaxiCode, QR code
Stacked code types	PDF417
Code qualification	On the basis of ISO/IEC 16022, ISO/IEC 15415, ISO/IEC 18004

Interfaces

Ethernet	✓, TCP/IP		
Functio	Data interface (read result output), Service interface, FTP (image transmission)		
Data transmission rat	e 10/100/1,000 Mbit/s		
PROFINET	√		
Functio	PROFINET Single Port (integrated), PROFINET Dual Port (optional via external connection module CDF600-2)		
Data transmission rat	e 10/100 MBit/s		
EtherNet/IP™	✓		
Data transmission rat	e 10/100/1,000 Mbit/s		
Serial	✓ , RS-232, RS-422		
Functio	Data interface (read result output), Service interface		
Data transmission rat	e 0.3 kBaud 115.2 kBaud, AUX: 57.6 kBaud (RS-232)		
CAN	✓		
Functio	SICK CAN sensor network CSN (CAN controller/CAN device, multiplexer/server)		
Data transmission rat	250 kbit/s 500 kbit/s		
PROFIBUS DP	√		
Type of fieldbus integration	Optional over external fieldbus module CDF600-2		
Digital inputs	4 ("Sensor 1", "Sensor 2", 2 inputs via optional CMC600 parameter memory in CDB650/CDM420)		
Configurable inputs	Encoder input, external trigger		
Digital outputs	6 (CDB650: "Result 1", "Result 2", "Result 3", "Result 4", 2 external outputs via CMC600 or CDM420: "Result 1", "Result 2", 2 external outputs via CMC600 or cable with open end: "Result 1", "Result 2", "Result 4")		
Configurable outputs	Good read, External illumination control, free configurable output condition, "device ready"		

Reading pulse	Digital inputs, non-powered, serial interface, Ethernet, CAN, auto pulse, presentation mode	
Optical indicators	11 LEDs (5 status displays, 16 LEDs, 5 LED bar graphs, 1 green/red feedback spot)	
Acoustic indicators	Beeper (configurable)	
Control elements	2 buttons (choose and start/stop functions)	
Operator interfaces	Web server	
Configuration software	SOPAS ET	
Memory card	Micro SD memory card (flash card) max. 32 GB, optional	
Data storage and retrieval	Image and data storage via microSD memory card and external FTP	
EncoderFrequency	Max. 1 kHz	
External illumination control	Via digital output (max. 24 V trigger) or external illumination connection	

Ambient data

Electromagnetic compatibility (EMC)	EN 61000-6-2:2005-08 / EN 61000-6-4 (2007-01) + A1 (2011)
Vibration resistance	EN 60068-2-6:2008-02
Shock resistance	EN 60068-2-27:2009-05
Ambient operating temperature	0 °C +50 °C
Storage temperature	-20 °C +70 °C
Permissible relative humidity	90 %, Non-condensing

Certificates


EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
China RoHS	✓
cULus certificate	√
KC Mark certificate	✓
BIS registration	✓
Information according to Art. 3 of Data Act (Regulation EU 2023/2854)	✓
4Dpro	✓

Classifications

ECLASS 5.0	27280103
ECLASS 5.1.4	27280103
ECLASS 6.0	27280103
ECLASS 6.2	27280103
ECLASS 7.0	27280103
ECLASS 8.0	27280103
ECLASS 8.1	27280103
ECLASS 9.0	27280103
ECLASS 10.0	27280103
ECLASS 11.0	27280103
ECLASS 12.0	27280103
ETIM 5.0	EC002550

ETIM 6.0	EC002550
ETIM 7.0	EC002999
ETIM 8.0	EC002999
UNSPSC 16.0901	43211701


Dimensional drawing




Dimensions in mm (inch)

- ① "External light" connection (external illumination unit, female connector, M12, 4-pin, A-coded)
- ② "Ethernet" connection (Gigabit Ethernet, female connector, M12, 8-pin, X-coded)
- 3 "USB" connection (female connector, type M8, 4-pin), for temporary use as a service interface only
- ④ "Power/Serial Data/CAN/I/O" connection (male connector, M12, 17-pin, A-coded)
- ⑤ Optics protection hood (length: 22.7 mm, 37.7 mm or 60 mm)
- (a) 4 protective caps for sealing off the electrical connections as required for enclosure rating IP67 (delivery condition)
- 7 4 tapped blind holes, M5, 5.5 mm deep for mounting the product
- ② 2 M5 sliding nuts; 5.5 mm deep; pivoting; as an alternative method of mounting the product
- Onnection for an integrable illumination unit (VI55I ring illumination unit)
- 1 2 laser alignment aids
- 1 S-mount or C-mount optics module
- @ 4 blind tapped holes, 2.5 mm for mounting the spacers for the integrable illumination (VI55I ring illumination unit)
- ⁽³⁾ Optical axis and center of the image sensor
- Basic device: Manual focus screw for an S-mount lens, accessible via the round opening in the housing cover. To secure the focus setting, cover the round opening with a self-adhesive label. Complete device: The opening is already covered by a label.
- 15 2 function keys
- 6 5 bar graph LEDs
- Thinged cover on the top side of the device, access to the microSD memory card and the manual focus screw (S-mount)
- ® 5 status LEDs (2 levels)

Field of view







For S-mount and standard C-mount lenses, spacer rings are needed for working distances shorter than approximately 10 times the focal length. For compact C-mount lenses, spacer rings are not needed, but the built-in illumination cannot be used for distances shorter than 300 mm.

- ① perceived field of view area: horizontal x vertical (mm)
- ② complete area
- 3 Minimum resolution in mm
- 4 1D code
- ⑤ 2D code
- **(6)** Working distance in mm
- 7 Focal length of lens, here example for f = 12.5 mm
- ® Close range
- Optional spacer ring required

Selection Guide Lector63x S-mount



Exploded view



- ① Camera housing
- ② Spacer for built-in illumination
- 3 Spacer ring (optional)
- 4 Plug connector for illumination
- ⑤ S-mount lens
- Built-in illumination
- ⑦ Optical filter (optional)
- 8 Filter holder
- optics protection hood

Recommended accessories

Other models and accessories → www.sick.com/Lector63x

	Brief description	Туре	part no.
reflectors and optics			
	Description: Distance bracket and light extension connector (medium) for mounting integratable lighting, length 15 mm, used with compact C-mount lenses with focal length of 12 mm or 25 mm and S-mount lens with focal length 25mm	Distance bracket	2079501
O	Description: Optics protection hood, medium, enclosure rating IP 67, length: 37.7 mm, PMMA, for use with compact C-mount lens with focal length 12 mm or 25 mm and S-mount lens with focal length 25 mm	Optics protection hood (PMMA)	2079127

	Brief description	Туре	part no.
connectors and cables			
W. W.	 Connection type head A: Female connector, M12, 17-pin, straight, A-coded Connection type head B: Male connector, M12, 17-pin, straight, A-coded Signal type: Power, serial, CAN, digital I/Os Cable: 2 m, suitable for refrigeration Description: Power, suitable for 2 A, shielded, Serial, CAN, Digital I/Os 	YM2A8D-020XXXF2A8D	6053230
8 8	 Connection type head A: Male connector, M12, 8-pin, straight, X-coded Connection type head B: Male connector, RJ45, 8-pin, straight Signal type: Ethernet, Gigabit Ethernet Cable: 2 m, 8-wire, PUR, halogen-free Description: Ethernet, shielded, Gigabit Ethernet Application: Zones with oils and lubricants 	YM2X18-020EG1M- RJA8	2106258
8 8	 Connection type head A: Male connector, M12, 8-pin, straight, X-coded Connection type head B: Male connector, RJ45, 8-pin, straight Signal type: Ethernet, Gigabit Ethernet Cable: 3 m, 8-wire, PUR, halogen-free Description: Ethernet, shielded, Gigabit Ethernet Application: Zones with oils and lubricants 	YM2X18-030EG1M- RJA8	2145693
Junction boxe	es		
		CDB650-204	1064114
Mounting systems			
	 Description: Mounting bracket with screws, L-shaped for mounting with sliding nuts, includes angle indicator for adjusting the tilt angle Suitable for: Lector83x, Inspector83x, Lector63x, InspectorP63x, Lector83x, Inspector83x, Lector83x, InspectorP63x, Lector83x, Inspector83x, Lector83x, Inspector83x, Lector83x 	Mounting bracket	2078970

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

