

GTB10-R3821 G10

**PHOTOELECTRIC SENSORS** 



#### PHOTOELECTRIC SENSORS

#### Ordering information

Туре	part no.
GTB10-R3821	1065863

Other models and accessories → www.sick.com/G10

Illustration may differ



#### Detailed technical data

#### **Features**

Functional principle	Photoelectric proximity sensor
Functional principle detail	Background suppression
Dimensions (W x H x D)	20 mm x 50 mm x 51.5 mm
Housing design (light emission)	Rectangular
Sensing range max.	20 mm 1,200 mm <sup>1)</sup>
Type of light	Infrared light
Light source	LED <sup>2)</sup>
Light spot size (distance)	Ø 22 mm (700 mm)
Wave length	850 nm
Adjustment	Potentiometer, 5 turns

 $<sup>^{1)}</sup>$  Object with 90% remission (based on standard white, DIN 5033).

### Mechanics/electronics

Supply voltage U <sub>e</sub>	24.44.20 24.24.20 25.1)
Supply voltage o <sub>e</sub>	24 V AC/DC 240 V AC/DC <sup>1)</sup>

<sup>&</sup>lt;sup>1)</sup> +- 10 %.

 $<sup>^{2)}</sup>$  Average service life: 100,000 h at  $T_{U}$  = +25  $^{\circ}\text{C}.$ 

 $<sup>^{2)}\ \</sup>mbox{Provide}$  suitable spark suppression for inductive or capacitive loads.

 $<sup>^{3)}</sup>$  With light/dark ratio 1:1.

 $<sup>^{4)}</sup>$  Do not bend below 0  $^{\circ}\text{C}.$ 

 $<sup>^{5)}</sup>$  C = interference suppression.

<sup>&</sup>lt;sup>6)</sup> Reference voltage: 250 V AC.

 $<sup>^{7)}</sup>$  In the case of a DC supply (ref. to EN 61000-6-3) the length of cable between the supply source and the sensor must be < 30 m.

<sup>&</sup>lt;sup>8)</sup> UL: 0 °C ... +50 °C.

 $<sup>^{9)}</sup>$  Complies with the UL325 standard when used with sturdy protection hood (e.g. BEF-G10WSG, 2071960).

Ripple	< 10 %
Power consumption	≤ 2.5 VA
Switching output	Relay, SPDT, electrically isolated <sup>2)</sup>
Switching mode	Light/dark switching <sup>2)</sup>
Switching load max. (current/voltage)	0.11 A (250 V DC) 3 A (30 V DC) 3 A (250 V AC)
Response time	≤ 10 ms
Switching frequency	20 Hz <sup>3)</sup>
Connection type	Cable, 5-wire, 2 m <sup>4)</sup>
Cable material	Plastic, PVC
Conductor cross section	0.25 mm <sup>2</sup>
Circuit protection	C <sup>5)</sup>
Protection class	II <sup>6)</sup>
Weight	115 g
Interference emission	EN 61000-6-3 (2011-09) <sup>7)</sup>
Housing material	Plastic, ABS/PMMA
Enclosure rating	IP67
Relay switching cycles min.	100.000 cycles (3 A)
Usage category	DC-13 (according to EN 60947-1) AC-15 (according to EN 60947-1)
Electromagnetic compatibility (EMC)	EN 60947-5-2 EN 61000-6-3 (2011-09)
Ambient operating temperature	-30 °C +60 °C <sup>8)</sup>
Ambient temperature, storage	-40 °C +70 °C
UL File No.	NRKH.E348498 & NRKH7.E348498
More standards	UL325 <sup>9)</sup>

<sup>&</sup>lt;sup>1)</sup> +- 10 %.

#### Safety-related parameters

MTTF <sub>D</sub>	1,279 years
DC <sub>avg</sub>	0 %
B <sub>10D</sub>	59,123 Switching cycles <sup>1)</sup>

 $<sup>^{1)}</sup>$  Only for devices containing electro-mechanical components. In this case, the MTTF<sub>D</sub> value of the entire device must be calculated from the given B<sub>10D</sub> value, the number of switching cycles and the given MTTF<sub>D</sub> value.

#### Certificates

EU declaration of conformity	✓
------------------------------	---

 $<sup>^{2)}\,\</sup>mbox{Provide}$  suitable spark suppression for inductive or capacitive loads.

 $<sup>^{3)}</sup>$  With light/dark ratio 1:1.

<sup>&</sup>lt;sup>4)</sup> Do not bend below 0 °C.

 $<sup>^{5)}</sup>$  C = interference suppression.

<sup>&</sup>lt;sup>6)</sup> Reference voltage: 250 V AC.

 $<sup>^{7)}</sup>$  In the case of a DC supply (ref. to EN 61000-6-3) the length of cable between the supply source and the sensor must be < 30 m.

 $<sup>^{8)}</sup>$  UL: 0 °C ... +50 °C.

 $<sup>^{9)}</sup>$  Complies with the UL325 standard when used with sturdy protection hood (e.g. BEF-G10WSG, 2071960).

# GTB10-R3821 | G10


# PHOTOELECTRIC SENSORS

UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
CCC certificate	✓
cULus certificate	✓
Photobiological safety (DIN EN 62471) certificate	<b>✓</b>

#### Classifications


ECLASS 5.0	27270904
ECLASS 5.1.4	27270904
ECLASS 6.0	27270904
ECLASS 6.2	27270904
ECLASS 7.0	27270904
ECLASS 8.0	27270904
ECLASS 8.1	27270904
ECLASS 9.0	27270904
ECLASS 10.0	27270904
ECLASS 11.0	27270904
ECLASS 12.0	27270903
ETIM 5.0	EC002719
ETIM 6.0	EC002719
ETIM 7.0	EC002719
ETIM 8.0	EC002719
UNSPSC 16.0901	39121528

# Adjustments




6 Adjustment of sensing range

#### Connection diagram Cd-163



#### scanning range


% of sensing range




- ① Sensing range on white, 90% remission factor
- ② Sensing range on gray, 18% remission factor
- 3 Sensing range on black, 6% remission factor

#### Light spot size

Diameter in mm (inch)



#### scanning range




0 200 400 600 800 1,000 1,200 1,400 (7.87) (15.75) (23.62) (31.5) (39.37) (47.24) (55.12) Distance in mm (inch)

Sensing range

Sensing range max.

- ① Sensing range on white, 90% remission factor
- ② Sensing range on gray, 18% remission factor
- 3 Sensing range on black, 6% remission factor

#### Dimensional drawing GTB10, AC/DC, cable



Dimensions in mm (inch)

- ① Center of optical axis, sender
- 2 Center of optical axis, receiver
- 3 Mounting hole, Ø 4.2 mm
- 4 LED indicator yellow: Status of received light beam
- ⑤ LED indicator green: power on

#### Recommended accessories

Other models and accessories → www.sick.com/G10

	Brief description	Туре	part no.
Mounting systems			
	<ul> <li>Description: Q-Lock, bar clamp system for G10 and reflector P250</li> <li>Material: Zinc diecast, steel</li> <li>Details: Die-cast zinc, steel, zinc coated</li> <li>Suitable for: G10 and reflector P250</li> </ul>	BEF-KHSQ12R01	2071260
	<ul> <li>Description: Mounting bracket with articulated arm</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Mounting hardware included</li> <li>Suitable for: W16, W26, W11, W12, W23, W27, Dx50, W280, G10</li> </ul>	BEF-WN-MULTI2	2093945
connectors and cables			
	Connection type head A: Male connector, M12, 5-pin, straight, A-coded Description: Unshielded Connection systems: Screw-type terminals Permitted cross-section: ≤ 0.75 mm² Note: For field bus technology	STE-1205-G	6022083

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

