



# EXS-09D6403B020

deTec

**SAFETY LIGHT CURTAINS**

**SICK**  
Sensor Intelligence.



Illustration may differ



## Ordering information

| Type            | part no. |
|-----------------|----------|
| EXS-09D6403B020 | 1068410  |

Other models and accessories → [www.sick.com/deTec](http://www.sick.com/deTec)

## Detailed technical data

### Features

|                                |                                                                                                                                                                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product version</b>         | deTec4 Core Ex                                                                                                                                                                                                                         |
| <b>Application</b>             | Explosive areas                                                                                                                                                                                                                        |
| <b>Ex-approvals</b>            | ATEX for gas: II 2 G Ex db IIB T6 Gb<br>ATEX for dust: II 2 D Ex tb IIIC T56 °C Db IP6X<br>NFPA 70/NEC 500 Class I, Div. 1, Groups C and D<br>NFPA 70/NEC 500 Class II, Div. 1, Groups E, F and G<br>NFPA 70/NEC 500 Class III, Div. 1 |
| <b>System part</b>             | Sender                                                                                                                                                                                                                                 |
| <b>Compatible receiver</b>     | 1068409                                                                                                                                                                                                                                |
| <b>Resolution</b>              | 30 mm                                                                                                                                                                                                                                  |
| <b>Scanning range</b>          | 10 m                                                                                                                                                                                                                                   |
| <b>Protective field height</b> | 900 mm                                                                                                                                                                                                                                 |
| <b>Synchronization</b>         | Optical synchronization                                                                                                                                                                                                                |
| <b>Items supplied</b>          | Sender in explosion-proof enclosure with connecting cable, 30 m<br>2 handles including screws                                                                                                                                          |

### Safety-related parameters

|                                                                           |                                        |
|---------------------------------------------------------------------------|----------------------------------------|
| <b>Type</b>                                                               | Type 4 (IEC 61496-1)                   |
| <b>Safety integrity level</b>                                             | SIL 3 (IEC 61508)                      |
| <b>Category</b>                                                           | Category 4 (ISO 13849-1)               |
| <b>Performance level</b>                                                  | PL e (ISO 13849-1)                     |
| <b>PFH<sub>D</sub> (mean probability of a dangerous failure per hour)</b> | $3.7 \times 10^{-9}$                   |
| <b>T<sub>M</sub> (mission time)</b>                                       | 20 years (ISO 13849-1)                 |
| <b>Safe state in the event of a fault</b>                                 | At least one OSSD is in the OFF state. |

## Functions

|                                                            |   |
|------------------------------------------------------------|---|
| <b>Protective operation</b>                                | ✓ |
| <b>Automatic calibration of the protective field width</b> | ✓ |

## Interfaces

|                          |                                              |
|--------------------------|----------------------------------------------|
| <b>System connection</b> | Connecting cable, 30 m, flying leads, 5-wire |
| Length of cable          | 30 m                                         |
| Cable diameter           | 7.4 mm                                       |
| Conductor cross section  | 0.75 mm <sup>2</sup>                         |
| <b>Display elements</b>  | LEDs                                         |

## Electronics

|                                     |                             |
|-------------------------------------|-----------------------------|
| <b>Protection class</b>             | III (IEC 61140)             |
| <b>Supply voltage V<sub>s</sub></b> | 24 V DC (19.2 V ... 28.8 V) |
| <b>Ripple</b>                       | ≤ 10 %                      |
| <b>Power consumption typical</b>    | 1.01 W (DC)                 |

## Mechanics

|                              |                          |
|------------------------------|--------------------------|
| <b>Dimensions</b>            | See dimensional drawing  |
| <b>Housing cross-section</b> | 161.8 mm x 142.1 mm      |
| <b>Housing material</b>      | Aluminum cast/AISi7Mg0.6 |

## Ambient data

|                                      |                                           |
|--------------------------------------|-------------------------------------------|
| <b>Enclosure rating</b>              | IP65 (IEC 60529)<br>IP66 (IEC 60529)      |
| <b>Ambient operating temperature</b> | -20 °C ... +55 °C                         |
| <b>Storage temperature</b>           | -30 °C ... +70 °C                         |
| <b>Air humidity</b>                  | 15 % ... 95 %, Non-condensing             |
| <b>Vibration resistance</b>          | 5 ... 150 Hz, 3,5 mm / 1 g (EN 60068-2-6) |
| <b>Shock resistance</b>              | 15 g / 6 ms (EN 60068-2-27)               |
| <b>Class</b>                         | 3M4 (IEC TR 60721-4-3)                    |

## Other information

|                      |                                |
|----------------------|--------------------------------|
| <b>Wave length</b>   | 850 nm                         |
| <b>Type of light</b> | Near-infrared (NIR), invisible |

## Certificates


|                                              |   |
|----------------------------------------------|---|
| <b>EU declaration of conformity</b>          | ✓ |
| <b>China-RoHS</b>                            | ✓ |
| <b>ATEX certificate</b>                      | ✓ |
| <b>IECEX certificate</b>                     | ✓ |
| <b>cULus certificate</b>                     | ✓ |
| <b>Japan EX Type-Examination Certificate</b> | ✓ |

## Classifications

|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27272704 |
| <b>ECLASS 5.1.4</b> | 27272704 |

|                |          |
|----------------|----------|
| ECLASS 6.0     | 27272704 |
| ECLASS 6.2     | 27272704 |
| ECLASS 7.0     | 27272704 |
| ECLASS 8.0     | 27272704 |
| ECLASS 8.1     | 27272704 |
| ECLASS 9.0     | 27272704 |
| ECLASS 10.0    | 27272704 |
| ECLASS 11.0    | 27272704 |
| ECLASS 12.0    | 27272704 |
| ETIM 5.0       | EC002549 |
| ETIM 6.0       | EC002549 |
| ETIM 7.0       | EC002549 |
| ETIM 8.0       | EC002549 |
| UNSPSC 16.0901 | 46171620 |

## Dimensional drawing deTec4 Core Ex, 900 mm



Dimensions in mm (inch)

## Recommended accessories

Other models and accessories → [www.sick.com/deTec](http://www.sick.com/deTec)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Type           | part no. |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|
| Safety relays                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                |          |
|    | <ul style="list-style-type: none"> <li>• <b>Applications:</b> Evaluation unit</li> <li>• <b>Compatible sensor types:</b> Safety sensors with OSSDs</li> <li>• <b>Connection type:</b> Front connector with spring terminals</li> <li>• <b>Restart interlock:</b> yes</li> <li>• <b>External device monitoring (EDM):</b> Integrated</li> <li>• <b>Outputs:</b> 3 enabling current paths (safe), 2 application diagnostic outputs (not safe), 1 test pulse output (not safe)</li> <li>• <b>Housing width:</b> 18 mm</li> </ul> | RLY3-OSSD300   | 1099969  |
|    | <ul style="list-style-type: none"> <li>• <b>Applications:</b> Evaluation unit</li> <li>• <b>Compatible sensor types:</b> Safety sensors with OSSDs</li> <li>• <b>Connection type:</b> Front connector with spring terminals</li> <li>• <b>Restart interlock:</b> yes</li> <li>• <b>External device monitoring (EDM):</b> Integrated</li> <li>• <b>Outputs:</b> 2 enabling current paths (safe), 2 application diagnostic outputs (not safe), 1 test pulse output (not safe)</li> <li>• <b>Housing width:</b> 18 mm</li> </ul> | RLY3-OSSD200   | 1085344  |
| Commissioning aids and test equipment                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                |          |
|   | <ul style="list-style-type: none"> <li>• <b>Product:</b> Test equipment</li> <li>• <b>Description:</b> 30 mm diameter, 250 mm length</li> </ul>                                                                                                                                                                                                                                                                                                                                                                               | Test rod 30 mm | 2022602  |
| Mounting systems                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                |          |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Alignment bracket for explosion-proof enclosure</li> <li>• <b>Packing unit:</b> 2 pieces</li> </ul>                                                                                                                                                                                                                                                                                                                                                              | BEF-1SHABRST2  | 2072525  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)