



# WTB4ST-22161120A00


## W4

PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



Ordering information

| Type               | part no. |
|--------------------|----------|
| WTB4ST-22161120A00 | 1131620  |

Other models and accessories → [www.sick.com/W4](http://www.sick.com/W4)

Detailed technical data

Features

|                                                                                                 |                                                                                       |
|-------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Functional principle                                                                            | Photoelectric proximity sensor                                                        |
| Functional principle detail                                                                     | Background suppression, DoubleLine                                                    |
| Sensing range                                                                                   |                                                                                       |
| Sensing range min.                                                                              | 0 mm                                                                                  |
| Sensing range max.                                                                              | 150 mm                                                                                |
| Adjustable switching threshold for background suppression                                       | 10 mm ... 150 mm                                                                      |
| Reference object                                                                                | Object with 90% remission factor (complies with standard white according to DIN 5033) |
| Minimum distance between set sensing range and background (black 6% / white 90%)                | 0.8 mm, At 70 mm distance                                                             |
| Recommended sensing range for the best performance                                              | 50 mm ... 90 mm                                                                       |
| Emitted beam                                                                                    |                                                                                       |
| Light source                                                                                    | PinPoint LED                                                                          |
| Type of light                                                                                   | Visible red light                                                                     |
| Shape of light spot                                                                             | Line-shaped, two parallel line-shaped light spots                                     |
| Light spot size (distance)                                                                      | 2.5 mm x 16 mm (50 mm)                                                                |
| Maximum dispersion of the emitted beam around the standardized transmission axis (squint angle) | < +/- 1.5° (at Ta = +23 °C)                                                           |
| Key LED figures                                                                                 |                                                                                       |
| Normative reference                                                                             | EN 62471:2008-09   IEC 62471:2006, modified                                           |
| LED risk group marking                                                                          | Free group                                                                            |
| Wave length                                                                                     | 635 nm                                                                                |
| Average service life                                                                            | 100,000 h at Ta = +25 °C                                                              |
| Smallest detectable object (MDO) typ.                                                           |                                                                                       |

|                             |                       |                                                                                                                          |
|-----------------------------|-----------------------|--------------------------------------------------------------------------------------------------------------------------|
| <b>Adjustment</b>           |                       | 1 mm (At 70 mm distance)                                                                                                 |
|                             |                       | Object with 90% remission factor (complies with standard white according to DIN 5033)                                    |
|                             | Teach-Turn adjustment | BluePilot: For setting the sensing range                                                                                 |
| <b>Display</b>              | IO-Link               | For configuring the sensor parameters and Smart Task functions                                                           |
|                             | LED blue              | BluePilot: sensing range indicator                                                                                       |
|                             | LED green             | Operating indicator<br>Static on: power on<br>Flashing: IO-Link mode                                                     |
|                             | LED yellow            | Status of received light beam<br>Static on: object present<br>Static off: object not present                             |
| <b>Special applications</b> |                       | Detecting flat objects, Detecting objects wrapped in film, Detecting perforated objects, Detecting uneven, shiny objects |

### Safety-related parameters

|                         |             |
|-------------------------|-------------|
| <b>MTTF<sub>D</sub></b> | 1,399 years |
| <b>DC<sub>avg</sub></b> | 0%          |

### Communication interface

|                |                             |                                              |
|----------------|-----------------------------|----------------------------------------------|
| <b>IO-Link</b> |                             | ✓, IO-Link V1.1                              |
|                | Data transmission rate      | COM2 (38,4 kBaud)                            |
|                | Cycle time                  | 2.3 ms                                       |
|                | Process data length         | 16 Bit                                       |
|                | Process data structure      | Bit 0 = switching signal Q <sub>L1</sub>     |
|                |                             | Bit 1 = switching signal Q <sub>L2</sub>     |
|                |                             | Bit 2 ... 15 = Current receiver level (live) |
|                | VendorID                    | 26                                           |
|                | DeviceID HEX                | 0x80031E                                     |
|                | DeviceID DEC                | 8389406                                      |
|                | Compatible master port type | A                                            |
|                | SIO mode support            | Yes                                          |

### Electronics

|                                     |        |                                                                        |
|-------------------------------------|--------|------------------------------------------------------------------------|
| <b>Supply voltage U<sub>B</sub></b> |        | 10 V DC ... 30 V DC <sup>1)</sup>                                      |
| <b>Ripple</b>                       |        | ≤ 5 V <sub>pp</sub>                                                    |
| <b>Usage category</b>               |        | DC-12 (According to EN 60947-5-2)<br>DC-13 (According to EN 60947-5-2) |
| <b>Current consumption</b>          |        | ≤ 20 mA, without load. At U <sub>B</sub> = 24 V                        |
| <b>Protection class</b>             |        | III                                                                    |
| <b>Digital output</b>               | Number | 2                                                                      |
|                                     | Type   | Push-pull: PNP/NPN                                                     |

<sup>1)</sup> Limit values.

<sup>2)</sup> This switching output must not be connected to another output.

|                                       |                                                                                          |
|---------------------------------------|------------------------------------------------------------------------------------------|
| Switching mode                        | Light/dark switching                                                                     |
| Signal voltage PNP HIGH/LOW           | Approx. $U_B$ -2.5 V / 0 V                                                               |
| Signal voltage NPN HIGH/LOW           | Approx. $U_B$ / < 2.5 V                                                                  |
| Output current $I_{max.}$             | $\leq 100$ mA                                                                            |
| Circuit protection outputs            | Reverse polarity protected                                                               |
|                                       | Overcurrent protected                                                                    |
|                                       | Short-circuit protected                                                                  |
| Response time                         | $\leq 1,000$ $\mu$ s                                                                     |
| Repeatability (response time)         | 240 $\mu$ s                                                                              |
| Switching frequency                   | 500 Hz                                                                                   |
| <b>Pin/Wire assignment</b>            |                                                                                          |
| Function of pin 4/black (BK)          | Digital output, light switching, object present → output $Q_{L1}$ HIGH <sup>2)</sup>     |
|                                       | IO-Link communication C                                                                  |
| Function of pin 4/black (BK) – detail | The pin 4 function of the sensor can be configured                                       |
|                                       | Additional possible settings via IO-Link                                                 |
| Function of pin 2/white (WH)          | Digital output, dark switching, object present → output $\bar{Q}_{L1}$ LOW <sup>2)</sup> |
| Function of pin 2/white (WH) – detail | The pin 2 function of the sensor can be configured                                       |
|                                       | Additional possible settings via IO-Link                                                 |

<sup>1)</sup> Limit values.

<sup>2)</sup> This switching output must not be connected to another output.

## Mechanics

|                                                       |                                 |
|-------------------------------------------------------|---------------------------------|
| <b>Housing</b>                                        | Rectangular                     |
| <b>Design detail</b>                                  | Slim                            |
| <b>Dimensions (W x H x D)</b>                         | 12.1 mm x 41.9 mm x 18.6 mm     |
| <b>Connection</b>                                     | Male connector M8, 4-pin        |
| <b>Material</b>                                       |                                 |
|                                                       | Housing Plastic, VISTAL®        |
|                                                       | Front screen Plastic, PMMA      |
|                                                       | Male connector Plastic, VISTAL® |
| <b>Maximum tightening torque of the fixing screws</b> | 0.4 Nm                          |

## Ambient data

|                                            |                                                                                                   |
|--------------------------------------------|---------------------------------------------------------------------------------------------------|
| <b>Enclosure rating</b>                    | IP66 (EN 60529)<br>IP67 (EN 60529)                                                                |
| <b>Ambient operating temperature</b>       | -40 °C ... +60 °C                                                                                 |
| <b>Ambient temperature, storage</b>        | -40 °C ... +75 °C                                                                                 |
| <b>Typ. Ambient light immunity</b>         | Artificial light: $\leq 50,000$ lx<br>Sunlight: $\leq 50,000$ lx                                  |
| <b>Shock resistance</b>                    | 30 g, 11 ms (3 positive and 3 negative shocks along X, Y, Z axes, 18 total shocks (EN60068-2-27)) |
| <b>Vibration resistance</b>                | 10 Hz ... 1,000 Hz (Amplitude 1 mm, 3 x 30 min (EN60068-2-6))                                     |
| <b>Air humidity</b>                        | 35 % ... 95 %, relative humidity (no condensation)                                                |
| <b>Electromagnetic compatibility (EMC)</b> | EN 60947-5-2                                                                                      |

|                                     |                              |
|-------------------------------------|------------------------------|
| <b>Resistance to cleaning agent</b> | ECOLAB                       |
| <b>UL File No.</b>                  | NRKH.E181493 & NRKH7.E181493 |

## Smart Task

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| <b>Smart Task name</b>           | Base logics                                                                           |
| <b>Logic function</b>            | Direct<br>AND<br>OR                                                                   |
| <b>Timer function</b>            | Deactivated<br>Switch-on delay<br>Off delay<br>ON and OFF delay<br>Impulse (one shot) |
| <b>Inverter</b>                  | Yes                                                                                   |
| <b>Switching frequency</b>       | SIO Logic: 450 Hz <sup>1)</sup>                                                       |
| <b>Response time</b>             | SIO Logic: 1100 µs <sup>1)</sup>                                                      |
| <b>Repeatability</b>             | SIO Logic: 500 µs <sup>1)</sup>                                                       |
| <b>Switching signal</b>          |                                                                                       |
| Switching signal Q <sub>L1</sub> | Switching output                                                                      |
| Switching signal $\bar{Q}_{L1}$  | Switching output                                                                      |

<sup>1)</sup> Use of Smart Task functions without IO-Link communication (SIO mode).

## Diagnosis

|                                                    |                                      |
|----------------------------------------------------|--------------------------------------|
| <b>Device temperature</b>                          |                                      |
| Measuring range                                    | Very cold, cold, moderate, warm, hot |
| <b>Device status</b>                               | Yes                                  |
| <b>Detailed device status</b>                      | Yes                                  |
| <b>Operating hour counter</b>                      | Yes                                  |
| <b>Operating hours counter with reset function</b> | Yes                                  |
| <b>Quality of teach</b>                            | Yes                                  |

## Certificates


|                                                                              |   |
|------------------------------------------------------------------------------|---|
| <b>EU declaration of conformity</b>                                          | ✓ |
| <b>UK declaration of conformity</b>                                          | ✓ |
| <b>ACMA declaration of conformity</b>                                        | ✓ |
| <b>Moroccan declaration of conformity</b>                                    | ✓ |
| <b>China-RoHS</b>                                                            | ✓ |
| <b>cULus certificate</b>                                                     | ✓ |
| <b>Information according to Art. 3 of Data Act (Regulation EU 2023/2854)</b> | ✓ |

## Classifications

|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27270904 |
| <b>ECLASS 5.1.4</b> | 27270904 |
| <b>ECLASS 6.0</b>   | 27270904 |
| <b>ECLASS 6.2</b>   | 27270904 |


|                       |          |
|-----------------------|----------|
| <b>ECLASS 7.0</b>     | 27270904 |
| <b>ECLASS 8.0</b>     | 27270904 |
| <b>ECLASS 8.1</b>     | 27270904 |
| <b>ECLASS 9.0</b>     | 27270904 |
| <b>ECLASS 10.0</b>    | 27270904 |
| <b>ECLASS 11.0</b>    | 27270904 |
| <b>ECLASS 12.0</b>    | 27270903 |
| <b>ETIM 5.0</b>       | EC002719 |
| <b>ETIM 6.0</b>       | EC002719 |
| <b>ETIM 7.0</b>       | EC002719 |
| <b>ETIM 8.0</b>       | EC002719 |
| <b>UNSPSC 16.0901</b> | 39121528 |

### display and adjustment elements




- ① LED green
- ② LED yellow
- ③ Teach-Turn adjustment
- ④ LED blue

### Connection type Male connector M8, 4-pin





Connection diagram Cd-490



Truth table Push-pull: PNP/NPN – dark switching  $\bar{Q}$


|                         | Dark switching $\bar{Q}$ (normally closed (upper switch), normally open (lower switch)) |                             |
|-------------------------|-----------------------------------------------------------------------------------------|-----------------------------|
|                         | Object not present → Output HIGH                                                        | Object present → Output LOW |
| Light receive           | ✗                                                                                       | ✓                           |
| Light receive indicator | ✗                                                                                       | ☀                           |
| Load resistance to L+   | ✗                                                                                       | ⚡                           |
| Load resistance to M    | ⚡                                                                                       | ✗                           |
|                         |                                                                                         |                             |

Truth table Push-pull: PNP/NPN - light switching Q

|                         | Light switching Q (normally open (upper switch), normally closed (lower switch))   |                                                                                     |
|-------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                         | Object not present → Output LOW                                                    | Object present → Output HIGH                                                        |
| Light receive           | ✗                                                                                  | ✓                                                                                   |
| Light receive indicator | ✗                                                                                  | ☀                                                                                   |
| Load resistance to L+   | ⚡                                                                                  | ✗                                                                                   |
| Load resistance to M    | ✗                                                                                  | ⚡                                                                                   |
|                         |  |  |

Characteristic curve


Minimum distance in mm (y) between the set sensing range and white background (90 % remission factor)



Recommended sensing range for the best performance

- ① Black object, 6% remission factor
- ② Gray object, 18% remission factor
- ③ White object, 90% remission factor

Example:  
Safe suppression of the background




Black object (6 % remission factor)  
Set sensing range x = 80 mm  
Needed minimum distance to white background y = 1.2 mm



## Light spot size


Dimensions in mm (inch)



Recommended sensing range for the best performance


## Light spot size

Dimensions in mm (inch)



Recommended sensing range for the best performance


Sensing range diagram



Recommended sensing range for the best performance

| 1 | Black object, 6% remission factor                         |
|---|-----------------------------------------------------------|
| 2 | Gray object, 18% remission factor                         |
| 3 | White object, 90% remission factor                        |
| A | Sensing range min. in mm                                  |
| B | Sensing range max. in mm                                  |
| C | Field of view                                             |
| D | Adjustable switching threshold for background suppression |
| E | Sensing range indicator                                   |
| F | Teach-Turn adjustment                                     |

Dimensional drawing, sensor




Dimensions in mm (inch)

- ① Center of optical axis, receiver
- ② Center of optical axis, sender
- ③ Connection
- ④ M3 mounting hole
- ⑤ display and adjustment elements

## Recommended accessories

Other models and accessories → [www.sick.com/W4](http://www.sick.com/W4)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Type               | part no. |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
| Mounting systems                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                    |          |
|    | <ul style="list-style-type: none"> <li><b>Description:</b> Plate N08 for universal clamp bracket</li> <li><b>Material:</b> Steel, zinc diecast</li> <li><b>Details:</b> Zinc plated steel (sheet), Zinc die cast (clamping bracket)</li> <li><b>Items supplied:</b> Universal clamp (5322626), mounting hardware</li> <li><b>Usable for:</b> W100, W150, W4S, W4F, W8, W9-3, W8G, W8 Laser, W8 Inox, G6, W100 Laser, W100-2, W10, G6 Inox, RAY10, W4SLG-3, W9, GR18, MultiPulse, Reflex Array, MultiLine, LUT3, KT5, KT8, KT10, CS8</li> </ul> | BEF-KHS-N08        | 2051607  |
|    | <ul style="list-style-type: none"> <li><b>Material:</b> Stainless steel</li> <li><b>Details:</b> Stainless steel (1.4301)</li> <li><b>Suitable for:</b> W4S, W4S</li> </ul>                                                                                                                                                                                                                                                                                                                                                                    | BEF-WN-G6          | 2062909  |
| connectors and cables                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                    |          |
|    | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Male connector, M8, 4-pin, straight, A-coded</li> <li><b>Description:</b> Unshielded</li> <li><b>Connection systems:</b> Screw-type terminals</li> <li><b>Permitted cross-section:</b> 0.14 mm² ... 0.5 mm²</li> </ul>                                                                                                                                                                                                                                                   | STE-0804-G         | 6037323  |
|   | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 4-pin, straight, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 5 m, 4-wire, PUR, halogen-free</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li> </ul>                                                                    | YF8U14-050UA3XLEAX | 2094792  |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Female connector, M8, 4-pin, straight, A-coded</li> <li><b>Connection type head B:</b> Flying leads</li> <li><b>Signal type:</b> Sensor/actuator cable</li> <li><b>Cable:</b> 5 m, 4-wire, PVC</li> <li><b>Description:</b> Sensor/actuator cable, unshielded</li> <li><b>Application:</b> Zones with chemicals, Uncontaminated zones</li> </ul>                                                                                                                         | YF8U14-050VA3XLEAX | 2095889  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)