

LL3-TV05

Fiber-optic cables

FIBER-OPTIC SENSORS





Ordering information

Туре	part no.
LL3-TV05	5322546

Other models and accessories -> www.sick.com/Fiber-optic_cables

Detailed technical data

Features

Device type	Fiber-optic cables
Functional principle	Through-beam system, consisting of a sender and a receiver
Fiber-optic head design	Threaded sleeve, 90° deflection
Application	Standard
Compatible fiber-optic amplifiers	GLL70, WLL80, WLL180, GLL170(T), WLL24 Ex
Sensing range max.	3,600 mm (Sensing range of WLL80 at 8 ms)
Minimal object diameter	0.4 mm ¹⁾
Optical fiber head	
Angle of dispersion	16°
Integrated lens	Yes
Compatibility tip adapters	No
Optical fiber	
Compatibility with infrared light	No
Optical fiber cable can be shortened	1
Adapter end sleeves required	No
Included with delivery	Mounting, 2 x M4 hexagon nut, FC fiber cutter (5304141)

 $^{^{1)}}$ Minimum detectable object was determined at optimum measuring distance and optimum setting.

Mechanics


Optical fiber head	
Light emission	Radial
Thread diameter (housing)	M4
Optical fiber	
Fiber length	2,000 mm
Bending radius	25 mm
Dynamic flexibility (robotics)	No
Outside diameter, optical fiber cable connection	2.2 mm
Core structure	Ø 1 mm
Material	
Optical fiber head	Polyamid (PA)
Sheath	Polyethylen (PE)
Fibers	Polymethylmethacrylat (PMMA)

Weight	29 g
Ambient data	
	40.00 +70.00
Ambient operating temperature	-40 °C +70 °C
Classifications	
ECLASS 5.0	27270905
ECLASS 5.1.4	27270905
ECLASS 6.0	27270905
ECLASS 6.2	27270905
ECLASS 7.0	27270905
ECLASS 8.0	27270905
ECLASS 8.1	27270905
ECLASS 9.0	27270905
ECLASS 10.0	27270905
ECLASS 11.0	27270905
ECLASS 12.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
ETIM 8.0	EC002651
UNSPSC 16.0901	39121528
Sensing ranges with GLL70	
Operating mode 50 µs	930 mm
Operating mode 250 μs	2,230 mm
Operating mode 1 ms	3,020 mm
Operating mode 4 ms	3,600 mm
Sensing ranges with WLL80	
Operating mode 16 µs	475 mm
Operating mode 70 µs	1,455 mm
Operating mode 250 μs	2,230 mm
Operating mode 500 μs	2,685 mm
Operating mode 1 ms	3,020 mm
Operating mode 2 ms	3,600 mm
Operating mode 8 ms	3,600 mm
Note	Sensing ranges related to fiber-optic sensors with type of light: visible red light
Sensing ranges with WLL180T	
Operating mode 16 μs	350 mm
Operating mode 70 μs	750 mm
Operating mode 250 μs	1,800 mm
Operating mode 2 ms	4,000 mm

LL3-TV05 | Fiber-optic cables FIBER-OPTIC SENSORS

Note	Sensing ranges related to fiber-optic sensors with type of light: visible red light
Sensing ranges with GLL170	
Operating mode 250 µs	640 mm
Sensing ranges with GLL170T	
Operating mode 50 µs	620 mm
Operating mode 250 µs	1,410 mm

Dimensional drawing LL3-TV05, LL3-TV06, LL3-TV07



Dimensions in mm (inch)

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

