

# IM12-04NPS-ZWXS01

**IM Standard** 

**INDUCTIVE PROXIMITY SENSORS** 





#### Ordering information

| Туре              | part no. |
|-------------------|----------|
| IM12-04NPS-ZWXS01 | 6032979  |

Other models and accessories → www.sick.com/IM\_Standard

Illustration may differ



#### Detailed technical data

#### **Features**

| Housing                      | Metric                          |
|------------------------------|---------------------------------|
| Housing                      | Standard design                 |
| Thread size                  | M12 x 1                         |
| Diameter                     | Ø 12 mm                         |
| Sensing range S <sub>n</sub> | 4 mm                            |
| Installation type            | Non-flush                       |
| Switching frequency          | 2,000 Hz                        |
| Connection type              | Cable with JST-connector, 0.1 m |
| Switching output             | PNP                             |
| Switching output detail      | PNP                             |
| Output function              | NO                              |
| Electrical wiring            | DC 3-wire                       |
| Enclosure rating             | IP67 <sup>1)</sup>              |
| Special characteristic       | JST connector, 3-pin            |

 $<sup>^{1)}</sup>$  According to EN 60529.

#### Mechanics/electronics

| Supply voltage                 | 10 V DC 30 V DC        |
|--------------------------------|------------------------|
| Ripple                         | ≤ 10 % <sup>1)</sup>   |
| Voltage drop                   | $\leq$ 1.2 V $^{2)}$   |
| Time delay before availability | ≤ 100 ms               |
| Hysteresis                     | 2 % 10 %               |
| Reproducibility                | ≤ 2 % <sup>3)</sup> 4) |

 $<sup>^{1)}</sup>$  Of  $V_S$ .

<sup>2)</sup> With I max.

 $<sup>^{\</sup>rm 3)}$  Supply voltage  $U_B$  and constant ambient temperature Ta.

<sup>&</sup>lt;sup>4)</sup> Of Sr.

| Temperature drift (of S <sub>r</sub> ) | ± 10 %                       |
|--|------------------------------|
| EMC                                    | According to EN 60947-5-2    |
| Continuous current I <sub>a</sub>      | ≤ 200 mA                     |
| Cable material                         | PVC                          |
| Conductor size                         | 0.22 mm <sup>2</sup>         |
| Short-circuit protection               | ✓                            |
| Power-up pulse protection              | ✓                            |
| Shock and vibration resistance         | 30 g, 11 ms / 10 55 Hz, 1 mm |
| Ambient operating temperature          | -25 °C +70 °C                |
| Housing material                       | Brass, Nickel-plated brass   |
| Sensing face material                  | Plastic                      |
| Housing length                         | 50 mm                        |
| Thread length                          | 35 mm                        |
| Tightening torque, max.                | 10 Nm                        |

 $<sup>^{1)}</sup>$  Of  $V_{S}$ .

## Safety-related parameters

| MTTF <sub>D</sub> | 192 years |
|-------------------|-----------|
| DC <sub>avg</sub> | 0 %       |

#### Installation note

| Remark | Associated graphic see "Installation" |
|--------|---------------------------------------|
| A      | 12 mm                                 |
| В      | 24 mm                                 |
| c      | 12 mm                                 |
| D      | 12 mm                                 |
| E      | 6 mm                                  |
| F      | 32 mm                                 |

#### Certificates

| EU declaration of conformity       | 1 |
|------------------------------------|---|
| UK declaration of conformity       | 1 |
| Moroccan declaration of conformity | 1 |
| China RoHS                         | ✓ |

#### Classifications

| ECLASS 5.0   | 27270101 |
|--------------|----------|
| ECLASS 5.1.4 | 27270101 |
| ECLASS 6.0   | 27270101 |
| ECLASS 6.2   | 27270101 |
| ECLASS 7.0   | 27270101 |
| ECLASS 8.0   | 27270101 |

<sup>&</sup>lt;sup>2)</sup> With I max.

 $<sup>^{\</sup>rm 3)}$  Supply voltage  $\rm U_B$  and constant ambient temperature Ta.


<sup>&</sup>lt;sup>4)</sup> Of Sr.


# IM12-04NPS-ZWXS01 | IM Standard

INDUCTIVE PROXIMITY SENSORS

| ECLASS 8.1     | 27270101 |
|----------------|----------|
| ECLASS 9.0     | 27270101 |
| ECLASS 10.0    | 27270101 |
| ECLASS 11.0    | 27270101 |
| ECLASS 12.0    | 27274001 |
| ETIM 5.0       | EC002714 |
| ETIM 6.0       | EC002714 |
| ETIM 7.0       | EC002714 |
| ETIM 8.0       | EC002714 |
| UNSPSC 16.0901 | 39122230 |

#### Installation note Non-flush installation





#### Recommended accessories

Other models and accessories → www.sick.com/IM\_Standard

|               | Brief description   | Туре        | part no. |  |
|---------------|---|-------------|----------|--|
| Mounting syst | Mounting systems  |             |          |  |
|               | Description: Clamping block for round sensors M12, with fixed stop     Material: Plastic     Details: Plastic (PA12), glass-fiber reinforced     Items supplied: Mounting hardware included                                       | BEF-KHF-M12 | 2051480  |  |
|               | <ul> <li>Description: Clamping block for round sensors M12, without fixed stop</li> <li>Material: Plastic</li> <li>Details: Plastic (PA12), glass-fiber reinforced</li> <li>Items supplied: Mounting hardware included</li> </ul> | BEF-KH-M12  | 2051479  |  |
|               | <ul> <li>Description: Mounting plate for M12 sensors</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Without mounting hardware</li> </ul>  | BEF-WG-M12  | 5321869  |  |
| 40            | Description: Mounting bracket for M12 sensors     Material: Steel     Details: Steel, zinc coated     Items supplied: Without mounting hardware   | BEF-WN-M12  | 5308447  |  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

