

CM30-25NAP-KW1

CAPACITIVE PROXIMITY SENSORS



Section of the sectio

Ordering information

Туре	part no.
CM30-25NAP-KW1	6028413

Other models and accessories → www.sick.com/CM

Illustration may differ



Detailed technical data

Features

Housing	Metric
Thread size	M30 x 1.5
Diameter	Ø 30 mm
Sensing range S _n	4 mm 25 mm
Safe sensing range S _a	18 mm
Installation type	Non-flush
Switching frequency	10 Hz
Connection type	Cable, 2-wire, 2 m ¹⁾
Output function	NC or NO
Electrical wiring	AC 2-wire
Adjustment	
Potentiometer	Sensitivity (11 turns)
Enclosure rating	IP67 (According to EN 60529)
Items supplied	Mounting nut, PA12 plastic (2x) Screwdriver for potentiometer adjustment (1 x)

 $^{^{1)}}$ Do not bend below 0 $^{\circ}\text{C}.$

Mechanics/electronics

Supply voltage	20 V AC 250 V AC
Ripple	≤ 10 % ¹⁾
Voltage drop	\leq 10 V DC $^{2)}$

 $^{^{1)}}$ Of Ub.

²⁾ At I_a max.

³⁾ Without load.

 $^{^{4)}}$ Of Sr.

 $^{^{5)}\,\}mbox{Supply}$ voltage $\mbox{U}_{\mbox{\footnotesize B}}$ and constant ambient temperature Ta.

⁶⁾ In EMC critical applications, conducted interference levels may lie within the frequency range of the oscillator. This can cause changes to the output signal. (See operating instructions.).

Current consumption	10 mA ³⁾
Time delay before availability	≤ 100 ms
Hysteresis	4 % 20 %
Reproducibility	≤ 5 % ⁴⁾ 5)
Temperature drift (of S _r)	± 10 %
EMC	According to EN 60947-5-2 ⁶⁾
Continuous current I _a	≤ 500 mA
Cable material	PVC
Conductor size	0.5 mm ²
Power-up pulse protection	✓
Shock and vibration resistance	30 g, 11 ms / 10 55 Hz, 1 mm
Ambient operating temperature	-25 °C +80 °C
Housing material	Plastic, PBT
Housing length	75.6 mm
Thread length	50 mm
Tightening torque, max.	≤ 7.5 Nm

¹⁾ Of Ub.

Safety-related parameters

MTTFD	815 years
DC _{avg}	0 %
T _M (mission time)	20 years

Reduction factors

Note	The values are reference values which may vary
Metal	1
Water	1
PVC	Approx. 0.4
Oil	Approx. 0.25
Glass	0.6
Ceramics	0.5
Alcohol	0.7
Wood	0.2 0.7

Installation note

Remark	Associated graphic see "Installation"
A	30 mm
В	60 mm

²⁾ At I_a max.

³⁾ Without load.

⁴⁾ Of Sr.

 $^{^{5)}}$ Supply voltage $\mbox{U}_{\mbox{\footnotesize B}}$ and constant ambient temperature Ta.

⁶⁾ In EMC critical applications, conducted interference levels may lie within the frequency range of the oscillator. This can cause changes to the output signal. (See operating instructions.).

CM30-25NAP-KW1 | CM

CAPACITIVE PROXIMITY SENSORS

c	30 mm
D	75 mm
E	14.5 mm In critical distances, the sensor should be tested in the application


Certificates


EU declaration of conformity	1
UK declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
cULus certificate	1

Classifications

ECLASS 5.0	27270102
ECLASS 5.1.4	27270102
ECLASS 6.0	27270102
ECLASS 6.2	27270102
ECLASS 7.0	27270102
ECLASS 8.0	27270102
ECLASS 8.1	27270102
ECLASS 9.0	27270102
ECLASS 10.0	27270102
ECLASS 11.0	27270102
ECLASS 12.0	27274201
ETIM 5.0	EC002715
ETIM 6.0	EC002715
ETIM 7.0	EC002715
ETIM 8.0	EC002715
UNSPSC 16.0901	39122230

Installation note Non-flush installation







Connection diagram Cd-013



Response diagram CM30, Non-flush installation



Dimensional drawing CM30, non-flush, cable



Dimensions in mm (inch)

- ① Connection
- ② Display LED
- 3 Potentiometer for sensitivity adjustment
- ④ fastening nuts (2 x); 36 mm hex, plastic

Recommended accessories

Other models and accessories → www.sick.com/CM

	Brief description	Туре	part no.	
Mounting syst	Mounting systems			
40	 Description: Mounting bracket for M30 sensors Material: Steel Details: Steel, zinc coated Items supplied: Without mounting hardware 	BEF-WN-M30	5308445	
0	 Description: Mounting plate for M30 sensors Material: Steel Details: Steel, zinc coated Items supplied: Without mounting hardware 	BEF-WG-M30	5321871	

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

