



# WL100-2P4400S38

W100-2

**PHOTOELECTRIC SENSORS** 





## Ordering information

Туре	part no.
WL100-2P4400S38	6052406

Other models and accessories → www.sick.com/W100-2

Illustration may differ



#### Detailed technical data

#### **Features**

Functional principle	Photoelectric retro-reflective sensor		
Functional principle detail	With minimum distance to reflector (dual lens system)		
Dimensions (W x H x D)	11 mm x 31 mm x 20 mm		
Housing design (light emission)	Rectangular		
Sensing range max.	0.01 m 7.2 m <sup>1)</sup>		
Sensing range	0.01 m 5.5 m <sup>1)</sup>		
Type of light	Visible red light		
Light source	LED <sup>2)</sup>		
Light spot size (distance)	Ø 280 mm (4 m)		
Wave length	632 nm		
Adjustment	None		

<sup>1)</sup> Reflector PL80A.

## Mechanics/electronics

Supply voltage U <sub>B</sub>	10 V DC 30 V DC <sup>1)</sup>

<sup>1)</sup> Limit values.

 $<sup>^{2)}</sup>$  Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

 $<sup>^{2)}</sup>$  May not fall below or exceed  $\mathrm{U}_{\mathrm{V}}$  tolerances.

<sup>3)</sup> Without load.

<sup>&</sup>lt;sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

 $<sup>^{6)}</sup>$  A = V<sub>S</sub> connections reverse-polarity protected.

<sup>&</sup>lt;sup>7)</sup> B = output reverse-polarity protected.

 $<sup>^{\</sup>rm 8)}$  D = outputs overcurrent and short-circuit protected.

	2)		
Ripple	± 10 % <sup>2)</sup>		
Current consumption	30 mA <sup>3)</sup>		
Switching output	PNP		
Switching mode	Light switching		
Signal voltage PNP HIGH/LOW	U <sub>V</sub> - 1,8 V / ca. 0 V		
Output current I <sub>max.</sub>	≤ 100 mA		
Response time	$\leq$ 0.5 ms $^{4)}$		
Switching frequency	1,000 Hz <sup>5)</sup>		
Connection type	Male connector M8, 4-pin		
Circuit protection	A <sup>6)</sup> B <sup>7)</sup> D <sup>8)</sup>		
Protection class	III		
Polarisation filter	✓		
Housing material	Plastic, ABS/PC/POM		
Optics material	Plastic, PMMA		
Enclosure rating	IP67		
Ambient operating temperature	-25 °C +55 °C		
Ambient temperature, storage	-40 °C +70 °C		

<sup>1)</sup> Limit values.

#### Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
cRUus certificate	✓
Photobiological safety (DIN EN 62471) certificate	✓

## Classifications

ECLASS 5.0	27270902
ECLASS 5.1.4	27270902
ECLASS 6.0	27270902
ECLASS 6.2	27270902
ECLASS 7.0	27270902
ECLASS 8.0	27270902

<sup>&</sup>lt;sup>2)</sup> May not fall below or exceed U<sub>V</sub> tolerances.

<sup>3)</sup> Without load.

<sup>&</sup>lt;sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

 $<sup>^{6)}</sup>$  A = V<sub>S</sub> connections reverse-polarity protected.

<sup>&</sup>lt;sup>7)</sup> B = output reverse-polarity protected.


 $<sup>^{8)}</sup>$  D = outputs overcurrent and short-circuit protected.

# WL100-2P4400S38 | W100-2

PHOTOELECTRIC SENSORS

ECLASS 8.1	27270902
ECLA33 6.1	21210902
ECLASS 9.0	27270902
ECLASS 10.0	27270902
ECLASS 11.0	27270902
ECLASS 12.0	27270902
ETIM 5.0	EC002717
<b>ETIM 6.0</b>	EC002717
ETIM 7.0	EC002717
ETIM 8.0	EC002717
UNSPSC 16.0901	39121528


## Adjustments



- ⑤ Orange LED indicator : switching output active
- **(6)** LED indicator green: stability indicator
- 7 sensitivity control


## Connection diagram Cd-067

#### Characteristic curve WL100-2



- ① Reflector PL80A
- ② Reflector P250
- 3 Diamond Grade reflective tape, 100 mm x 100 mm

## Light spot size



## Sensing range diagram WL100-2

						1
1	0.01*			5.5	7.2	
2	0.01*		4.0	5.7		
3	0.01*		4.0	5.5		
4	0.01*	3.0		5.2		
(5)	0.01* 1.	6 2.2				
6	0.1* 1.2	1.7				
7	0.01* 1.2	1.7				
(				.76) (19	.0 7. .67) (24. .ce in m (fe	.61)

Sensing range

Sensing range max.

\*Close-up range at maximum sensitivity

① Reflector PL80A

② Reflector P250

3 Reflector PL50A, PL40A


4 Reflector PL30A, PL31A


⑤ Reflector PL20A

**6** Reflective tape Diamond Grade

⑦ P45

## Dimensional drawing WT100, WL100





Dimensions in mm (inch)

- ① Threaded mounting hole M3
- 2 Center of optical axis, receiver
- 3 Center of optical axis, sender
- 4 Connection
- ⑤ LED indicator orange: switching output active
- 6 LED indicator green: power on

## Recommended accessories

Other models and accessories → www.sick.com/W100-2

	Brief description	Туре	part no.		
Mounting systems					
0,	<ul> <li>Description: Mounting bracket for wall mounting</li> <li>Material: Stainless steel</li> <li>Details: Stainless steel</li> <li>Items supplied: Mounting hardware included</li> <li>Suitable for: W8, W8G, W8 Laser, W8 Inox, G6, G6 Inox, W100 Laser, W100-2, KTM Core, KTM Prime, CSM, LUTM, W4S</li> </ul>	BEF-W100-A	5311520		
	<ul> <li>Description: Mounting bracket for floor mounting</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Items supplied: Mounting hardware included</li> <li>Suitable for: W8, W8G, W8 Laser, W8 Inox, G6, G6 Inox, W100 Laser, W100-2, KTM Core, KTM Prime, CSM, LUTM</li> </ul>	BEF-W100-B	5311521		
2 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	<ul> <li>Description: Universal mounting bracket for reflectors</li> <li>Dimensions (W x H x L): 85 mm x 90 mm x 35 mm</li> <li>Material: Steel</li> <li>Details: Steel, zinc coated</li> <li>Suitable for: C110A, P250, PL20, PL30A, PL40A, PL80A</li> </ul>	BEF-WN-REFX	2064574		
6	<ul> <li>Description: Plate N11N for universal clamp bracket</li> <li>Material: Stainless steel</li> <li>Details: Stainless steel 1.4571 (sheet), Stainless steel 1.4408 (clamp)</li> <li>Items supplied: Universal clamp (5322627), mounting hardware</li> <li>Usable for: DeltaPac, Glare, WTD20E</li> </ul>	BEF-KHS-N11N	2071081		
reflectors and	optics				
	<ul> <li>Description: Rectangular, screw connection</li> <li>Dimensions: 51 mm 61 mm</li> <li>Ambient operating temperature: -30 °C +65 °C</li> </ul>	P250	5304812		
connectors an	nd cables				
	<ul> <li>Connection type head A: Female connector, M8, 4-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Sensor/actuator cable</li> <li>Cable: 5 m, 4-wire, PVC</li> <li>Description: Sensor/actuator cable, unshielded</li> <li>Application: Zones with chemicals, Uncontaminated zones</li> </ul>	YF8U14-050VA3XLEAX	2095889		
No.	<ul> <li>Connection type head A: Female connector, M8, 4-pin, straight, A-coded</li> <li>Connection type head B: Flying leads</li> <li>Signal type: Sensor/actuator cable</li> <li>Cable: 5 m, 4-wire, PUR, halogen-free</li> <li>Description: Sensor/actuator cable, unshielded</li> <li>Application: Uncontaminated zones, Zones with oils and lubricants, Robot, Drag chain operation</li> </ul>	YF8U14-050UA3XLEAX	2094792		
	<ul> <li>Connection type head A: Male connector, M8, 4-pin, straight, A-coded</li> <li>Description: Unshielded</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: 0.14 mm² 0.5 mm²</li> </ul>	STE-0804-G	6037323		

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

