



# GL10-R9811P16

G10

PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



Ordering information

| Type          | part no. |
|---------------|----------|
| GL10-R9811P16 | 1125850  |

Included in delivery: BEF-AP-H18 (1)

Other models and accessories → [www.sick.com/G10](http://www.sick.com/G10)

Detailed technical data

Features

|                                 |                                                                |
|---------------------------------|----------------------------------------------------------------|
| Functional principle            | Photoelectric retro-reflective sensor                          |
| Functional principle detail     | With minimum distance to reflector (dual lens system)          |
| Dimensions (W x H x D)          | 20 mm x 50 mm x 51.5 mm                                        |
| Housing design (light emission) | Rectangular                                                    |
| Sensing range max.              | 0.08 m ... 15 m <sup>1)</sup><br>0.08 m ... 12 m <sup>2)</sup> |
| Sensing range                   | 0.15 m ... 12 m <sup>1)</sup><br>0.15 m ... 10 m <sup>2)</sup> |
| Type of light                   | Visible red light                                              |
| Light source                    | PinPoint LED <sup>3)</sup>                                     |
| Light spot size (distance)      | Ø 58 mm (5 m)                                                  |
| Wave length                     | 625 nm                                                         |
| Adjustment                      | Potentiometer, 270°                                            |

<sup>1)</sup> Reflector PL80A.

<sup>2)</sup> Reflector P250.

<sup>3)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

## Mechanics/electronics

|                                              |                                                                    |
|----------------------------------------------|--------------------------------------------------------------------|
| <b>Supply voltage U<sub>e</sub></b>          | 24 V AC/DC ... 240 V AC/DC <sup>1)</sup>                           |
| <b>Ripple</b>                                | < 10 %                                                             |
| <b>Power consumption</b>                     | ≤ 2.5 VA                                                           |
| <b>Switching output</b>                      | Relay, SPDT, electrically isolated <sup>2)</sup>                   |
| <b>Switching mode</b>                        | Light/dark switching <sup>2)</sup>                                 |
| <b>Switching load max. (current/voltage)</b> | 0.11 A (250 V DC)<br>3 A (30 V DC)<br>3 A (250 V AC)               |
| <b>Response time</b>                         | ≤ 10 ms                                                            |
| <b>Switching frequency</b>                   | 20 Hz <sup>3)</sup>                                                |
| <b>Connection type</b>                       | Cable, 5-wire, 5 m <sup>4)</sup>                                   |
| <b>Cable material</b>                        | Plastic, PVC                                                       |
| <b>Conductor cross section</b>               | 0.25 mm <sup>2</sup>                                               |
| <b>Circuit protection</b>                    | C <sup>5)</sup>                                                    |
| <b>Protection class</b>                      | II <sup>6)</sup>                                                   |
| <b>Weight</b>                                | 351 g                                                              |
| <b>Polarizing filter</b>                     | ✓                                                                  |
| <b>Interference emission</b>                 | EN 61000-6-3 (2011-09) <sup>7)</sup>                               |
| <b>Housing material</b>                      | Plastic, ABS/PMMA                                                  |
| <b>Enclosure rating</b>                      | IP67                                                               |
| <b>Relay switching cycles min.</b>           | 100.000 cycles (3 A)                                               |
| <b>Items supplied</b>                        | Mounting system BEF-KHS-ISG6 (premounted)                          |
| <b>Usage category</b>                        | DC-13 (according to EN 60947-1)<br>AC-15 (according to EN 60947-1) |
| <b>Electromagnetic compatibility (EMC)</b>   | EN 60947-5-2<br>EN 61000-6-3 (2011-09)                             |
| <b>Ambient operating temperature</b>         | -30 °C ... +60 °C <sup>8)</sup>                                    |
| <b>Ambient temperature, storage</b>          | -40 °C ... +70 °C                                                  |
| <b>UL File No.</b>                           | NRKH.E348498 & NRKH7.E348498                                       |
| <b>More standards</b>                        | UL325 <sup>9)</sup>                                                |

<sup>1)</sup> +/- 10 %.

<sup>2)</sup> Provide suitable spark suppression for inductive or capacitive loads.

<sup>3)</sup> With light/dark ratio 1:1.

<sup>4)</sup> Do not bend below 0 °C.

<sup>5)</sup> C = interference suppression.

<sup>6)</sup> Reference voltage: 250 V AC.

<sup>7)</sup> In the case of a DC supply (ref. to EN 61000-6-3) the length of cable between the supply source and the sensor must be < 30 m.

<sup>8)</sup> UL: 0 °C ... +50 °C.

<sup>9)</sup> Complies with the UL325 standard when used with sturdy protection hood (e.g. BEF-G10WSG, 2071960).

## Certificates


|                                       |   |
|---------------------------------------|---|
| <b>EU declaration of conformity</b>   | ✓ |
| <b>UK declaration of conformity</b>   | ✓ |
| <b>ACMA declaration of conformity</b> | ✓ |

|                                                   |   |
|---------------------------------------------------|---|
| Moroccan declaration of conformity                | ✓ |
| China RoHS                                        | ✓ |
| cULus certificate                                 | ✓ |
| Photobiological safety (DIN EN 62471) certificate | ✓ |


Classifications

|                |          |
|----------------|----------|
| ECLASS 5.0     | 27270902 |
| ECLASS 5.1.4   | 27270902 |
| ECLASS 6.0     | 27270902 |
| ECLASS 6.2     | 27270902 |
| ECLASS 7.0     | 27270902 |
| ECLASS 8.0     | 27270902 |
| ECLASS 8.1     | 27270902 |
| ECLASS 9.0     | 27270902 |
| ECLASS 10.0    | 27270902 |
| ECLASS 11.0    | 27270902 |
| ECLASS 12.0    | 27270902 |
| ETIM 5.0       | EC002717 |
| ETIM 6.0       | EC002717 |
| ETIM 7.0       | EC002717 |
| ETIM 8.0       | EC002717 |
| UNSPSC 16.0901 | 39121528 |

Adjustments



Connection diagram Cd-163




Characteristic curve GL10



Light spot size




Sensing range diagram GL10



- ③ Reflector PL30A
- ④ Reflector P250
- ⑤ Reflector PL40A
- ⑥ Reflector PL80A

### Dimensional drawing



Dimensions in mm (inch)

- ① Center of optical axis, sender
- ② Center of optical axis, receiver
- ③ pre-mounted fixing screws (M4 x 30 mm)
- ④ LED indicator yellow: Status of received light beam
- ⑤ LED indicator green: power on

## Recommended accessories

Other models and accessories → [www.sick.com/G10](http://www.sick.com/G10)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                             | Type          | part no. |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------|
| Mounting systems                                                                    |                                                                                                                                                                                                                                                                                                                                               |               |          |
|    | <ul style="list-style-type: none"> <li><b>Description:</b> Q-Lock, bar clamp system for G10 and reflector P250</li> <li><b>Material:</b> Zinc diecast, steel</li> <li><b>Details:</b> Die-cast zinc, steel, zinc coated</li> <li><b>Suitable for:</b> G10 and reflector P250</li> </ul>                                                       | BEF-KHSQ12R01 | 2071260  |
|    | <ul style="list-style-type: none"> <li><b>Description:</b> Mounting bracket with articulated arm</li> <li><b>Material:</b> Steel</li> <li><b>Details:</b> Steel, zinc coated</li> <li><b>Items supplied:</b> Mounting hardware included</li> <li><b>Suitable for:</b> W16, W26, W11, W12, W23, W27, Dx50, W280, G10</li> </ul>                | BEF-WN-MULTI2 | 2093945  |
|    | <ul style="list-style-type: none"> <li><b>Description:</b> Universal mounting bracket for reflectors</li> <li><b>Dimensions (W x H x L):</b> 85 mm x 90 mm x 35 mm</li> <li><b>Material:</b> Steel</li> <li><b>Details:</b> Steel, zinc coated</li> <li><b>Suitable for:</b> C110A, P250, PL20, PL30A, PL40A, PL80A</li> </ul>                | BEF-WN-REFX   | 2064574  |
| reflectors and optics                                                               |                                                                                                                                                                                                                                                                                                                                               |               |          |
|   | <ul style="list-style-type: none"> <li><b>Description:</b> Rectangular, screw connection</li> <li><b>Dimensions:</b> 51 mm 61 mm</li> <li><b>Ambient operating temperature:</b> -30 °C ... +65 °C</li> </ul>                                                                                                                                  | P250          | 5304812  |
| connectors and cables                                                               |                                                                                                                                                                                                                                                                                                                                               |               |          |
|  | <ul style="list-style-type: none"> <li><b>Connection type head A:</b> Male connector, M12, 5-pin, straight, A-coded</li> <li><b>Description:</b> Unshielded</li> <li><b>Connection systems:</b> Screw-type terminals</li> <li><b>Permitted cross-section:</b> ≤ 0.75 mm<sup>2</sup></li> <li><b>Note:</b> For field bus technology</li> </ul> | STE-1205-G    | 6022083  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)