




# ARS60-H4A04096

ARS60

**ABSOLUTE ENCODERS**

**SICK**  
Sensor Intelligence.



## Ordering information

| Type           | part no. |
|----------------|----------|
| ARS60-H4A04096 | 1031697  |

Other models and accessories → [www.sick.com/ARS60](http://www.sick.com/ARS60)

Illustration may differ



## Detailed technical data

### Safety-related parameters

|                                                          |                                          |
|----------------------------------------------------------|------------------------------------------|
| <b>MTTF<sub>D</sub> (mean time to dangerous failure)</b> | 300 years (EN ISO 13849-1) <sup>1)</sup> |
|----------------------------------------------------------|------------------------------------------|

<sup>1)</sup> This product is a standard product and does not constitute a safety component as defined in the Machinery Directive. Calculation based on nominal load of components, average ambient temperature 40 °C, frequency of use 8760 h/a. All electronic failures are considered hazardous. For more information, see document no. 8015532.

### Performance

|                                                               |                                               |
|---------------------------------------------------------------|-----------------------------------------------|
| <b>Number of steps per revolution (max. resolution)</b>       | 4,096 (12 bit)                                |
| <b>Measuring step</b>                                         | 360° / number of steps                        |
| <b>Measuring step deviation</b>                               | 0.005° binary number of steps                 |
| <b>Error limits G</b>                                         | 0.035° (binary number of steps) <sup>1)</sup> |
| <b>Repeatability standard deviation <math>\sigma_r</math></b> | 0.005° <sup>2)</sup>                          |

<sup>1)</sup> In accordance with DIN ISO 1319-1, position of the upper and lower error limit depends on the installation situation, specified value refers to a symmetrical position, i.e. deviation in upper and lower direction is the same.

<sup>2)</sup> In accordance with DIN ISO 55350-13; 68.3% of the measured values are inside the specified area.

### Interfaces

|                                           |                                                                     |
|-------------------------------------------|---------------------------------------------------------------------|
| <b>Communication interface</b>            | Parallel data world                                                 |
| <b>Initialization time</b>                | 80 ms <sup>1)</sup>                                                 |
| <b>Code type</b>                          | Binary                                                              |
| <b>Code sequence parameter adjustable</b> | CW (clockwise) increasing when viewing the clockwise rotating shaft |
| <b>Measured value backlash</b>            | 0.005°                                                              |
| <b>Response threshold</b>                 | 0.003°                                                              |

<sup>1)</sup> Valid positional data can be read once this time has elapsed.

### Electronics

|                          |                                     |
|--------------------------|-------------------------------------|
| <b>Connection type</b>   | Male connector, M23, 21-pin, radial |
| <b>Supply voltage</b>    | 10 ... 32 V                         |
| <b>Operating current</b> | Typ. 90 mA                          |

<sup>1)</sup> Only with shaft stationary (note initialisation time).

|                                          |                                                                         |
|------------------------------------------|-------------------------------------------------------------------------|
| <b>Switching level of control inputs</b> | Logic H = 0.7 x U <sub>S</sub> , Logic L = 0 V ... 0.3 x U <sub>S</sub> |
| <b>Actuation of set button</b>           | ≥ 100 ms <sup>1)</sup>                                                  |

<sup>1)</sup> Only with shaft stationary (note initialisation time).

## Mechanics

|                                       |                                                                                                          |
|---------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Mechanical design</b>              | Solid shaft, face mount flange                                                                           |
| <b>Shaft diameter</b>                 | 10 mm                                                                                                    |
| <b>Shaft length</b>                   | 19 mm                                                                                                    |
| <b>Characteristics of the shaft</b>   | With flat                                                                                                |
| <b>Weight</b>                         | Approx. 0.3 kg <sup>1)</sup>                                                                             |
| <b>Housing material</b>               | Aluminum die cast                                                                                        |
| <b>Start up torque</b>                | Typ. 0.4 Ncm                                                                                             |
| <b>Operating torque</b>               | Typ. 0.3 Ncm                                                                                             |
| <b>Permissible shaft loading</b>      | 20 N (radial)<br>10 N (axial)                                                                            |
| <b>Operating speed</b>                | ≤ 6,000 min <sup>-1</sup> with shaft seal<br>≤ 10,000 min <sup>-1</sup> without shaft seal <sup>2)</sup> |
| <b>Moment of inertia of the rotor</b> | 54 gcm <sup>2</sup>                                                                                      |
| <b>Bearing lifetime</b>               | 3.6 x 10 <sup>9</sup> revolutions                                                                        |
| <b>Angular acceleration</b>           | ≤ 500,000 rad/s <sup>2</sup>                                                                             |

<sup>1)</sup> Based on devices with male connector.

<sup>2)</sup> If the shaft seal has been removed by the customer.

## Ambient data

|                                      |                                                          |
|--------------------------------------|----------------------------------------------------------|
| <b>EMC</b>                           | According to EN 61000-6-2 and EN 61000-6-3 <sup>1)</sup> |
| <b>Enclosure rating</b>              | IP65, male connector (IEC 60529) <sup>2)</sup>           |
| <b>Permissible relative humidity</b> | 90 % (Condensation not permitted)                        |
| <b>Operating temperature range</b>   | -20 °C ... +85 °C                                        |
| <b>Storage temperature range</b>     | -40 °C ... +100 °C, without package                      |
| <b>Resistance to shocks</b>          | 50 g, 11 ms (EN 60068-2-27)                              |
| <b>Resistance to vibration</b>       | 20 g, 10 Hz ... 2,000 Hz (EN 60068-2-6)                  |

<sup>1)</sup> EMC according to the standards quoted is achieved if shielded cables are used.

<sup>2)</sup> With mating connector fitted.


## Certificates

|                                                                              |   |
|------------------------------------------------------------------------------|---|
| <b>EU declaration of conformity</b>                                          | ✓ |
| <b>UK declaration of conformity</b>                                          | ✓ |
| <b>ACMA declaration of conformity</b>                                        | ✓ |
| <b>China RoHS</b>                                                            | ✓ |
| <b>cULus certificate</b>                                                     | ✓ |
| <b>Information according to Art. 3 of Data Act (Regulation EU 2023/2854)</b> | ✓ |

## Classifications

|                   |          |
|-------------------|----------|
| <b>ECLASS 5.0</b> | 27270502 |
|-------------------|----------|

## Dimensional drawing



## PIN assignment



| PIN | Wire colors (cable connection) | SignalBinary | SignalGray   | SignalBCD              |   |
|-----|--------------------------------|--------------|--------------|------------------------|---|
| 1   | Violet                         | $2^0$        | $G^0$        | $2^0 \text{ v. } 10^0$ | - |
| 2   | White/brown                    | $2^1$        | $G^1$        | $2^1 \text{ v. } 10^0$ | - |
| 3   | White/green                    | $2^2$        | $G^2$        | $2^2 \text{ v. } 10^0$ | - |
| 4   | White/yellow                   | $2^3$        | $G^3$        | $2^3 \text{ v. } 10^0$ | - |
| 5   | White/grey                     | $2^4$        | $G^4$        | $2^0 \text{ v. } 10^1$ | - |
| 6   | White/pink                     | $2^5$        | $G^5$        | $2^1 \text{ v. } 10^1$ | - |
| 7   | White/blue                     | $2^6$        | $G^6$        | $2^2 \text{ v. } 10^1$ | - |
| 8   | White/red                      | $2^7$        | $G^7$        | $2^3 \text{ v. } 10^1$ | - |
| 9   | White/black                    | $2^8$        | $G^8$        | $2^0 \text{ v. } 10^2$ | - |
| 10  | Brown/green                    | $2^9$        | $G^9$        | $2^1 \text{ v. } 10^2$ | - |
| 11  | Brown/yellow                   | $2^{10}$     | $G^{10}$     | $2^2 \text{ v. } 10^2$ | - |
| 12  | Brown/gray                     | $2^{11}$     | $G^{11}$     | $2^3 \text{ v. } 10^2$ | - |
| 13  | Brown/pink                     | $2^{12}$     | $G^{12}$     | $2^0 \text{ v. } 10^3$ | - |
| 14  | Brown/blue                     | $2^{13}$     | $G^{13}$     | $2^1 \text{ v. } 10^3$ | - |
| 15  | Brown/red                      | $2^{14}$     | $G^{14}$     | $2^2 \text{ v. } 10^3$ | - |
| 16  | Green                          | Parity       |              | Parity                 |   |
| 17  | Pink                           |              | Store        |                        | - |
| 18  | Yellow                         |              | Enable       |                        | - |
| 19  | Brown                          |              | CW/CCW (V/R) |                        | - |
| *   | Gray                           |              | SET          |                        | - |
| 20  | Blue                           |              | GND          |                        | - |
| 21  | Red                            |              | $U_S$        |                        | - |

Diagrams



Recommended accessories

Other models and accessories → [www.sick.com/ARS60](http://www.sick.com/ARS60)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                            | Type             | part no. |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|----------|
| connectors and cables                                                               |                                                                                                                                                                                                                                                                                                                                              |                  |          |
|    | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Flying leads</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Parallel</li><li>• <b>Items supplied:</b> By the meter</li><li>• <b>Cable:</b> 22-wire, PUR, halogen-free</li><li>• <b>Description:</b> Parallel, shielded</li></ul> | LTG-2622-MW      | 6027532  |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M23, 21-pin, straight, A-coded</li><li>• <b>Signal type:</b> SSI</li><li>• <b>Description:</b> SSI, shielded</li><li>• <b>Connection systems:</b> Crimp contacts</li></ul>                                                                          | DOS-2321-G       | 6027539  |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M23, 21-pin, straight</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Parallel</li><li>• <b>Cable:</b> 1.5 m, 22-wire, PUR, halogen-free</li><li>• <b>Description:</b> Parallel, shielded</li></ul>             | DOL-2321-G1M5PA4 | 2029218  |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M23, 21-pin, straight</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Parallel</li><li>• <b>Cable:</b> 3 m, 22-wire, PUR, halogen-free</li><li>• <b>Description:</b> Parallel, shielded</li></ul>               | DOL-2321-G03MPA4 | 2029219  |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M23, 21-pin, straight</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Parallel</li><li>• <b>Cable:</b> 5 m, 22-wire, PUR, halogen-free</li><li>• <b>Description:</b> Parallel, shielded</li></ul>               | DOL-2321-G05MPA4 | 2029220  |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M23, 21-pin, straight</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Parallel</li><li>• <b>Cable:</b> 10 m, 22-wire, PUR, halogen-free</li><li>• <b>Description:</b> Parallel, shielded</li></ul>              | DOL-2321-G10MPA4 | 2029221  |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M23, 21-pin, straight</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Parallel</li><li>• <b>Cable:</b> 20 m, 22-wire, PUR, halogen-free</li><li>• <b>Description:</b> Parallel, shielded</li></ul>              | DOL-2321-G20MPA4 | 2029222  |

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                                                                       | Type              | part no. |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|----------|
| Mounting systems                                                                    |                                                                                                                                                                                                                                                                                                                                                                         |                   |          |
|    | <ul style="list-style-type: none"> <li><b>Description:</b> Flange adapter, adaptation of face mount flange with 36 mm centering hub to 50 mm servo flange, aluminum, including 3 flat head screws M4 x 10</li> <li><b>Material:</b> Aluminum</li> <li><b>Details:</b> Aluminum</li> <li><b>Items supplied:</b> Including 3 countersunk screws M3 x 10</li> </ul>        | BEF-FA-036-050    | 2029160  |
|    | <ul style="list-style-type: none"> <li><b>Description:</b> Flange adapter, adaptation of face mount flange with 36 mm centering hub to 60 mm square mounting plate, aluminum, including 3 flat head screws M4 x 8</li> <li><b>Material:</b> Aluminum</li> <li><b>Details:</b> Aluminum</li> <li><b>Items supplied:</b> Including 3 countersunk screws M4 x 8</li> </ul> | BEF-FA-036-060REC | 2029162  |
|    | <ul style="list-style-type: none"> <li><b>Description:</b> Flange adapter, adaptation of face mount flange with 36 mm centering hub to 58 mm square mounting plate with shock absorbers, aluminum</li> <li><b>Material:</b> Aluminum</li> <li><b>Details:</b> Aluminum</li> </ul>                                                                                       | BEF-FA-036-060RSA | 2029163  |
|   | <ul style="list-style-type: none"> <li><b>Description:</b> Flange adapter, adaptation of face mount flange with 36 mm centering hub to 100 mm servo flange with 60 mm centering hub, aluminum</li> <li><b>Material:</b> Aluminum</li> <li><b>Details:</b> Aluminum</li> </ul>                                                                                           | BEF-FA-036-100    | 2029161  |
|  | <ul style="list-style-type: none"> <li><b>Description:</b> Mounting bracket for encoder with spigot 36 mm for face mount flange</li> <li><b>Items supplied:</b> Mounting kit included</li> </ul>                                                                                                                                                                        | BEF-WF-36         | 2029164  |

|                                                                                   | Brief description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Type       | part no. |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------|
| shaft adaptation                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |            |          |
|  | <ul style="list-style-type: none"> <li><b>Product segment:</b> Shaft adaptation</li> <li><b>Product:</b> Shaft couplings</li> <li><b>Description:</b> Bellows coupling, shaft diameter 6 mm / 10 mm, maximum shaft offset: radial <math>\pm 0.25</math> mm, axial <math>\pm 0.4</math> mm, angular <math>\pm 4^\circ</math>; max. speed 10,000 rpm, <math>-30^\circ\text{C}</math> to <math>+120^\circ\text{C}</math>, max. torque 120 Ncm; material: stainless steel bellows, aluminum hub</li> </ul>                                                   | KUP-0610-B | 5312982  |
|  | <ul style="list-style-type: none"> <li><b>Product segment:</b> Shaft adaptation</li> <li><b>Product:</b> Shaft couplings</li> <li><b>Description:</b> Spring washer coupling, shaft diameter 6 mm / 10 mm, Maximum shaft offset: radial <math>\pm 0.3</math> mm, axial <math>\pm 0.4</math> mm, angular <math>\pm 2.5^\circ</math>; max. speed 12,000 rpm, <math>-10^\circ</math> to <math>+80^\circ\text{C}</math>, max. torque 60 Ncm; material: aluminum flange, glass fiber-reinforced polyamide membrane and hardened steel coupling pin</li> </ul> | KUP-0610-F | 5312985  |
|  | <ul style="list-style-type: none"> <li><b>Product segment:</b> Shaft adaptation</li> <li><b>Product:</b> Shaft couplings</li> <li><b>Description:</b> Bellows coupling, shaft diameter 10 mm/10 mm; maximum shaft offset: radial <math>\pm 0.25</math> mm, axial <math>\pm 0.4</math> mm, angular <math>\pm 4^\circ</math>; max. revolutions 10,000 rpm, <math>-30^\circ</math> to <math>+120^\circ\text{C}</math>, max. torque 120 Ncm; material: stainless steel bellows, aluminum clamping hubs</li> </ul>                                            | KUP-1010-B | 5312983  |
|  | <ul style="list-style-type: none"> <li><b>Product segment:</b> Shaft adaptation</li> <li><b>Product:</b> Shaft couplings</li> <li><b>Description:</b> Spring washer coupling, shaft diameter 10 mm / 10 mm, maximum shaft offset, radial <math>\pm 0.3</math> mm, axial <math>\pm 0.4</math> mm, angle <math>\pm 2.5^\circ</math>, torsion spring stiffness 30 Nm/rad; material: aluminum flange, glass-fiber reinforced polyamide membrane and hardened steel coupling pin</li> </ul>                                                                   | KUP-1010-F | 5312986  |
|  | <ul style="list-style-type: none"> <li><b>Product segment:</b> Shaft adaptation</li> <li><b>Product:</b> Shaft couplings</li> <li><b>Description:</b> 10 mm / 12 mm; maximum shaft offset: radial <math>\pm 0.25</math> mm, axial <math>\pm 0.4</math> mm, angular <math>\pm 4^\circ</math>; max. revolutions 10,000 rpm, <math>-30^\circ</math> to <math>+120^\circ\text{C}</math>, max. torque 120 Ncm; material: stainless steel bellows, aluminum clamping hubs</li> </ul>                                                                           | KUP-1012-B | 5312984  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)