

IQ10-03BPSKWDSS18

INDUCTIVE PROXIMITY SENSORS

SICKSensor Intelligence.

SICK

Ordering information

Туре	part no.
IQ10-03BPSKWDSS18	1071068

Other models and accessories → www.sick.com/IQB

Illustration may differ



Detailed technical data

Features

Housing	Rectangular
Dimensions (W x H x D)	10 mm x 28 mm x 16 mm
Sensing range S _n	3 mm
Safe sensing range S _a	2.43 mm
Installation type	Flush
Switching frequency	2,000 Hz
Connection type	Cable with connector Micro, 3-pin, 0.25 m
Switching output	PNP
Switching output detail	PNP
Output function	NO
Electrical wiring	DC 3-wire
Enclosure rating	IP68 ¹⁾

¹⁾ According to EN 60529.

Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	≤ 10 % ¹⁾
Voltage drop	\leq 2 V $^{2)}$
Time delay before availability	≤ 100 ms
Hysteresis	5 % 15 %

 $^{^{1)}}$ Of V_S .

²⁾ At L may

 $^{^{\}rm 3)}$ Supply voltage U_B and constant ambient temperature Ta.

⁴⁾ Of Sr.

Reproducibility	≤ 2 % ³⁾ 4)
Temperature drift (of S _r)	± 10 %
EMC	According to EN 60947-5-2
Continuous current I _a	≤ 200 mA
No load current	10 mA
Cable material	PVC
Conductor size	0.25 mm ²
Cable diameter	Ø 3.7 mm
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	30 g, 11 ms / 10 55 Hz, 1 mm
Ambient operating temperature	-30 °C +75 °C
Housing material	Plastic, VISTAL®
Sensing face material	Plastic, VISTAL®
Tightening torque, max.	≤ 1 Nm

 $^{^{1)}}$ Of V_S .

Safety-related parameters

MTTF _D	1,775 years
DC _{avg}	0 %

Reduction factors

Note	The values are reference values which may vary
Stainless steel (V2A, 304)	0.7
Aluminum (AI)	0.4
Copper (Cu)	0.3
Brass (Br)	0.5

Installation note

Remark	Associated graphic see "Installation"
Α	0 mm
В	10 mm
c	10.3 mm
D	9 mm
E	0 mm
F	24 mm
G	0 mm

Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓

²⁾ At I_a max.

 $^{^{\}rm 3)}$ Supply voltage U_{B} and constant ambient temperature Ta.

⁴⁾ Of Sr


IQ10-03BPSKWDSS18 | IQB INDUCTIVE PROXIMITY SENSORS

ACMA declaration of conformity	1
Moroccan declaration of conformity	√
China RoHS	1
cULus certificate	√

Classifications

ECLASS 5.0	27270101
ECLASS 5.1.4	27270101
ECLASS 6.0	27270101
ECLASS 6.2	27270101
ECLASS 7.0	27270101
ECLASS 8.0	27270101
ECLASS 8.1	27270101
ECLASS 9.0	27270101
ECLASS 10.0	27270101
ECLASS 11.0	27270101
ECLASS 12.0	27274001
ETIM 5.0	EC002714
ETIM 6.0	EC002714
ETIM 7.0	EC002714
ETIM 8.0	EC002714
UNSPSC 16.0901	39122230


Installation note



Connection diagram Cd-002




Response diagram



Distance of target edge to center of active face in mm (inch)

All dimensions in mm (inch)

Dimensional drawing IQ10, cable



Dimensions in mm (inch)

① Connection

IQ10-03BPSKWDSS18 | IQB

INDUCTIVE PROXIMITY SENSORS

② LED indicator 270°

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

