

# GRSE18-N1121V

GR18

**PHOTOELECTRIC SENSORS** 





# Ordering information

Туре	part no.
GRSE18-N1121V	1085939

Illustration may differ

Other models and accessories → www.sick.com/GR18



#### Detailed technical data

#### **Features**

Functional principle	Through-beam photoelectric sensor
Dimensions (W x H x D)	18 mm x 18 mm x 73.5 mm
Housing design (light emission)	Cylindrical
Housing length	73.5 mm
Thread length	49.3 mm
Thread diameter (housing)	M18 x 1
Optical axis	Axial
Sensing range max.	0 m 15 m
Sensing range	0 m 10 m
Type of light	Infrared light
Light source	LED <sup>1)</sup>
Light spot size (distance)	Ø 420 mm (10 m)
Wave length	850 nm
Adjustment	None
Display	
LED green	Operating indicator Static on: power on
LED yellow	Status of received light beam Static on: object not present Static off: object present
Special applications	Hygienic and washdown zones

 $<sup>^{1)}</sup>$  Average service life: 100,000 h at  $\rm T_U$  = +25  $^{\circ}\rm C.$ 

# Mechanics/electronics

Supply voltage U <sub>B</sub>	10 V DC 30 V DC <sup>1)</sup>
Ripple	< 5 V <sub>pp</sub> <sup>2)</sup>
Current consumption	30 mA
Switching output	NPN
Output function	Complementary
Switching mode	Light/dark switching <sup>3)</sup>
Signal voltage NPN HIGH/LOW	Approx. $V_S / \leq 3 V$
Output current I <sub>max</sub> .	$\leq$ 100 mA $^{4)}$
Response time	< 500 μs <sup>5)</sup>
Switching frequency	1,000 Hz <sup>6)</sup>
Connection type	Cable, 4-wire, 2 m <sup>7)</sup>
Cable material	Plastic, PVC
Conductor cross section	0.14 mm <sup>2</sup>
Cable diameter	Ø 4.8 mm
Circuit protection	A <sup>8)</sup> B <sup>9)</sup> D <sup>10)</sup>
Protection class	III
Weight	190 g
Housing material	Metal, Stainless steel V4A (1.4404, 316L)
Optics material	Plastic, PMMA
Tightening torque, max.	90 Nm
Enclosure rating	IP67 IP68 <sup>11)</sup> IP69K <sup>12)</sup>
Items supplied	Fastening nuts (4 x)
Electromagnetic compatibility (EMC)	EN 60947-5-2
Test input	Sender OFF at "Test" 0 V
Ambient operating temperature	-25 °C +55 °C <sup>13)</sup>
Ambient temperature, storage	-30 °C +75 °C

 $<sup>^{1)}</sup>$  Limit values. Operated in short-circuit protected network: max. 8 A.

 $<sup>^{2)}\,\</sup>mbox{May}$  not fall below or exceed  $\mbox{U}_{\mbox{\scriptsize V}}$  tolerances.

 $<sup>^{3)}</sup>$  Q = light switching;  $\bar{Q}$  = dark switching.

 $<sup>^{4)}</sup>$  At Uv > 24 V or ambient temperature > 49 °C, IA max. = 50 mA.

<sup>5)</sup> Signal transit time with resistive load.

<sup>6)</sup> With light/dark ratio 1:1.

<sup>7)</sup> Do not bend below 0 °C.

 $<sup>^{8)}</sup>$  A = V<sub>S</sub> connections reverse-polarity protected.

 $<sup>^{9)}</sup>$  B = inputs and output reverse-polarity protected.

 $<sup>^{10)}</sup>$  D = outputs overcurrent and short-circuit protected.

 $<sup>^{11)}</sup>$  According to EN 60529 (10 m water depth / 24 h).

 $<sup>^{12)}</sup>$  According to ISO 20653:2013-03.

 $<sup>^{13)}</sup>$  At  $\rm U_{V}$  <=24V and  $\rm I_{A}\!\!<\!50mA.$ 

UL File No.	E348498
Part number of individual components	2091363 GRS18-D1121V 2091615 GRE18-N1111V

<sup>1)</sup> Limit values. Operated in short-circuit protected network: max. 8 A.

#### Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China RoHS	✓
ECOLAB certificate	✓
cULus certificate	✓
Photobiological safety (DIN EN 62471) certificate	✓

#### Classifications

ECLASS 5.0	27270901
ECLASS 5.1.4	27270901
ECLASS 6.0	27270901
ECLASS 6.2	27270901
ECLASS 7.0	27270901
ECLASS 8.0	27270901
ECLASS 8.1	27270901
ECLASS 9.0	27270901
ECLASS 10.0	27270901
ECLASS 11.0	27270901
ECLASS 12.0	27270901
ETIM 5.0	EC002716
ETIM 6.0	EC002716
ETIM 7.0	EC002716
ETIM 8.0	EC002716
UNSPSC 16.0901	39121528

 $<sup>^{2)}</sup>$  May not fall below or exceed  $\mathrm{U}_{\mathrm{V}}$  tolerances.

 $<sup>^{3)}</sup>$  Q = light switching;  $\bar{Q}$  = dark switching.

 $<sup>^{4)}</sup>$  At Uv > 24 V or ambient temperature > 49 °C, IA max. = 50 mA.

 $<sup>^{5)}</sup>$  Signal transit time with resistive load.

<sup>6)</sup> With light/dark ratio 1:1.

<sup>7)</sup> Do not bend below 0 °C.

 $<sup>^{8)}</sup>$  A = V<sub>S</sub> connections reverse-polarity protected.

<sup>&</sup>lt;sup>9)</sup> B = inputs and output reverse-polarity protected.


<sup>10)</sup> D = outputs overcurrent and short-circuit protected.

 $<sup>^{11)}\,\</sup>mbox{According to EN 60529}$  (10 m water depth / 24 h).


 $<sup>^{12)}\</sup>operatorname{According}$  to ISO 20653:2013-03.

 $<sup>^{13)}</sup>$  At  $\rm U_{V}$  <=24V and  $\rm I_{A}{<}50mA.$ 


# Connection diagram Cd-088




#### Characteristic curve GRSE18S



# Light spot size GRSE18, infrared light




# Sensing range diagram GRSE18S




#### Response range GRSE18S

Parallel operating range y in mm (inch)



# Dimensional drawing GR18 Inox, cable, straight



Dimensions in mm (inch)

- ① Connection
- ② Threaded mounting hole M18 x 1
- 3 fastening nuts (2 x); width across 24, stainless steel
- ⑤ LED indicator (4 x)
- ⑥ optical axis, receiver
- ⑦ optical axis, sender

#### Recommended accessories

Other models and accessories → www.sick.com/GR18

	Brief description	Туре	part no.
Mounting systems			
40	Description: Mounting bracket for M18 sensors     Material: Stainless steel     Details: Stainless steel     Items supplied: Without mounting hardware	BEF-WN-M18N	5320947
connectors and cables			
1	<ul> <li>Connection type head A: Male connector, M12, 4-pin, straight, A-coded</li> <li>Description: Unshielded</li> <li>Connection systems: Screw-type terminals</li> <li>Permitted cross-section: ≤ 0.75 mm²</li> </ul>	STE-1204-G	6009932

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

