

CM30-16BNP-EWDS03

CAPACITIVE PROXIMITY SENSORS



SICKO STATE OF THE PARTY OF THE

Ordering information

Туре	part no.
CM30-16BNP-EWDS03	6080314

Other models and accessories → www.sick.com/CM

Illustration may differ



Detailed technical data

Features

Housing	Metric
Thread size	M30 x 1.5
Diameter	Ø 30 mm
Sensing range S _n	3 mm 16 mm
Safe sensing range S _a	12.24 mm ¹⁾
Installation type	Flush
Switching frequency	50 Hz
Connection type	Cable with AMP male connector, 3-pin, 0.3 m $^{2)}$
Switching output	NPN
Switching output detail	NPN
Output function	Complementary
Output characteristic	Wire configurable
Electrical wiring	DC 4-wire
Adjustment	
Potentiometer	Sensitivity (11 turns)
Enclosure rating	IP68 ³⁾ IP69K
Items supplied	Mounting nut, PA12 plastic (2x) Screwdriver for potentiometer adjustment (1 x)

 $^{^{1)}}$ For flush mounting in electrically conductive materials Sa = 0.8 x Sr at temperatures <0 °C and >60 °C.

 $^{^{2)}}$ Do not bend below 0 °C.

 $^{^{3)}\, 1}$ m water depth / 60 min.

Mechanics/electronics

Supply voltage	10 V DC 36 V DC
Ripple	≤ 10 % ¹⁾
Voltage drop	\leq 2 V DC $^{2)}$
Current consumption	12 mA ³⁾
Time delay before availability	≤ 200 ms
Hysteresis	3 % 20 %
Reproducibility	≤ 5 % ⁴⁾ 5)
Temperature drift (of S _r)	± 10 %
EMC	According to EN 60947-5-2
Continuous current I _a	≤ 200 mA
Cable material	PVC
Conductor size	0.34 mm ²
Cable diameter	Ø 5.2 mm
Short-circuit protection	✓
Power-up pulse protection	✓
Shock and vibration resistance	According to EN 60068
Ambient operating temperature	-30 °C +85 °C ⁶⁾
Ambient temperature, storage	-40 °C +85 °C
Housing material	Plastic, PBT
Housing length	81 mm
Thread length	59.5 mm
Tightening torque, max.	≤ 7.5 Nm
UL File No.	NRKH.E191603

¹⁾ Of Ub.

Safety-related parameters

$MTTF_D$	919 years
DC _{avg}	0 %
T _M (mission time)	20 years

Reduction factors

Note	The values are reference values which may vary
Metal	1
Water	1
PVC	Approx. 0.4
Oil	Approx. 0.25

²⁾ At I_a max.

³⁾ Without load.

⁴⁾ Of Sr.

 $^{^{5)}}$ Supply voltage U_{B} and constant ambient temperature Ta.

 $^{^{6)}}$ +120 $^{\circ}$ C short time, at the front of the sensor.

CM30-16BNP-EWDS03 | CM

CAPACITIVE PROXIMITY SENSORS

Glass	0.6
Ceramics	0.5
Alcohol	0.7
Wood	0.2 0.7

Installation note

Remark	Associated graphic see "Installation"
В	30 mm
C	30 mm
D	48 mm
F	64 mm


Certificates


EU declaration of conformity	1
UK declaration of conformity	1
Moroccan declaration of conformity	1
China RoHS	1
cULus certificate	1

Classifications

ECLASS 5.0	27270102
ECLASS 5.1.4	27270102
ECLASS 6.0	27270102
ECLASS 6.2	27270102
ECLASS 7.0	27270102
ECLASS 8.0	27270102
ECLASS 8.1	27270102
ECLASS 9.0	27270102
ECLASS 10.0	27270102
ECLASS 11.0	27270102
ECLASS 12.0	27274201
ETIM 5.0	EC002715
ETIM 6.0	EC002715
ETIM 7.0	EC002715
ETIM 8.0	EC002715
UNSPSC 16.0901	39122230

Installation note Flush installation






Shock and vibration resistance

Shock (IEC 60068-2-27):	30 G / 11ms, 3 pos, 3 neg per axis	
Rough handling shocks (IEC 60068-2-31):	2 times from 1m, 100 times from 0,5m	
Vibration (IEC 60068-2-6):	10 to 150 Hz, 1 mm / 15 G	


Electromagnetic compatibility (EMC)

Electrostatic discharge (EN61000-4-2):	Contact discharge > 40 kV Air discharge > 40 kV
Electrical fast transients/burst (EN 61000-4-4):	+/- 4 kV
Surge (EN 61000-4-5):	Power supply > 2 kV (with 500 0hm) Sensor output > 2 kV (with 500 0hm)
Wire conducted disturbances (EN 61000-4-6):	> 20 Vrms
Power-frequency magnetic fields (EN 61000-4-8):	Continous > 60 A/m, 75.9 μ tesla Short-time > 600 A/m, 759 μ tesla
Radiated RF electromagnetic fields (EN 61000-4-3):	> 20 V/m


Connection diagram Cd-007



Response diagram CM30, Flush installation



Dimensional drawing CM30, flush, cable with male connector



Dimensions in mm (inch)

- 1) fastening nuts (2 x); 36 mm hex, plastic
- ② Cable 4 x 0.34 mm² PVC; Ø 5.2 mm
- ③ Heat-shrink tubing, 25 mm
- 4 Male connector: 1 x housing: AMP no.: 282105-1; 3 x tab contact AMP no.: 282404-1, tin plated pins AWG 20-22; 3 x green
- seal AMP no.: 0-0281934-4
- ⑤ Potentiometer for sensitivity adjustment
- **©** LED yellow: output active
- 7 LED green: operating indicator

Recommended accessories

Other models and accessories → www.sick.com/CM

	Brief description	Туре	part no.	
Mounting syst	Mounting systems			
40	 Description: Mounting bracket for M30 sensors Material: Steel Details: Steel, zinc coated Items supplied: Without mounting hardware 	BEF-WN-M30	5308445	
0	 Description: Mounting plate for M30 sensors Material: Steel Details: Steel, zinc coated Items supplied: Without mounting hardware 	BEF-WG-M30	5321871	

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

