

# FLN-EMSS1100108

Flexi Loop

**SAFE SERIES CONNECTION** 





## Ordering information

Туре	part no.
FLN-EMSS1100108	1061712

Other models and accessories → www.sick.com/Flexi\_Loop



#### Detailed technical data

## Safety-related parameters

Safety integrity level	SIL 3 (IEC 61508)
Category	Category 4 (EN ISO 13849)
Performance level	PL e (EN ISO 13849)
$\ensuremath{PFH_D}$ (mean probability of a dangerous failure per hour)	0.76 x 10 <sup>-9</sup> (EN ISO 13849)
T <sub>M</sub> (mission time)	20 years (EN ISO 13849)

#### **Functions**

Diagnostic and monitoring functions	
Cross-circuit	Monitoring via Flexi Loop node
Short-circuit	Monitoring via Flexi Loop node
Discrepancy errors	Monitoring via Flexi Loop node
Sequence errors	Monitoring via Flexi Loop node

#### Interfaces

Connection usage	
Safety device connection	For dual-channel equivalent electro-mechanical safety switch (EMSS), With standard input, with standard output
Flexi Loop input	To connect to a Flexi Loop predecessor node or to connect the Flexi Loop line to the Flexi Soft safety controller.
Flexi Loop output	To connect to a Flexi Loop successor node or to terminate the Flexi Loop line with the Flexi Loop terminator.
Connection type	
Safety device connection	Female connector M12, 8-pin
Flexi Loop input	Male connector M12, 5-pin
Flexi Loop output	Female connector M12, 5-pin
Number of non-safe inputs	1
Number of non-safe outputs	1
Power supply output for external devices	<b>√</b>

## Electrical data - Operating data

Protection class	III (EN 61140)
Type of supply voltage	PELV or SELV
Supply voltage $V_s$	24 V DC (16.8 V DC 30 V DC)
Power consumption	55 mA

#### Electrical data - EMSS interface

Test pulse interval	40 ms
Test pulse width	12 ms
Test pulse current via the switch contacts	3 mA 6.2 mA

## Electrical data - Non-safe inputs

Switching voltage	
HIGH	13 V DC 30 V DC
LOW	0 V DC 5 V DC
Input current	≤ 6.2 mA

## Electrical data - Non-safe outputs

Type of output	Highside driver, short-circuit protected
Output current	≤ 500 mA

## Electrical data - Power supply output for external devices

Supply voltage	24 V DC (16.8 V DC 30 V DC)
Output current	≤ 2 A

#### Mechanical data

Dimensions (W x H x D)	68.15 mm x 48 mm x 18 mm
Weight	28 g (± 5 %)

#### Ambient data

Enclosure rating	IP65 (EN 60529) IP67 (EN 60529)
Ambient operating temperature	-25 °C +55 °C
Storage temperature	-25 °C +70 °C


#### Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
China RoHS	✓
UK-Type-Examination approval	<b>✓</b>
cULus certificate	<b>√</b>
cTUVus certificate	<b>✓</b>
EC-Type-Examination approval	<b>√</b>
Information according to Art. 3 of Data Act (Regulation EU 2023/2854)	<b>√</b>


#### Classifications

ECLASS 5.0	27371990
ECLASS 5.1.4	27371990
ECLASS 6.0	27371819
ECLASS 6.2	27371819
ECLASS 7.0	27371819
ECLASS 8.0	27371819
ECLASS 8.1	27371819
ECLASS 9.0	27371819
ECLASS 10.0	27371819
ECLASS 11.0	27371819
ECLASS 12.0	27371819
ETIM 5.0	EC001449
ETIM 6.0	EC001449
ETIM 7.0	EC001449
ETIM 8.0	EC001449
UNSPSC 16.0901	41113704

## Dimensional drawing OSSD, EMSS



## PIN assignment



The FL\_IN pin assignment is only relevant for the first loop node in a safe series connection when connected to Flexi Soft. Additional Flexi Loop nodes are connected to FL\_OUT using standardized cables with M12 plug connectors.

Connection	Pin	Signal	Description	Color-coded con- necting cable
FL_IN	1	VDC	24 V supply voltage	Brown
	2	DATA_OUT	Output to Flexi Soft input In +1	White
	3	GND	GND supply voltage	Blue
	4	SAFE_OUT	Safe cut-off signal, out- put to Flexi Soft input In	Black
	5	DATA_IN	Input from Flexi Soft output Xn	Gray
EMSS	1	VDC	24 V supply voltage	White
	2	AUX_IN	Non-safe input	Brown
	3	EMSS1_A	Switching contact 1, connection A	Green
	4	EMSS1_B	Switching contact 1, connection B	Yellow
	5	AUX_OUT	Non-safe output	Gray
	6	GND	GND supply voltage	Pink
	7	EMSS2_A	Switching contact 2, connection A	Blue
	8	EMSS2_B	Switching contact 2, connection B	Red
	The colors listed apply	y when using pre-assembled o	ables (no guarantee).	

## Recommended accessories

Other models and accessories → www.sick.com/Flexi\_Loop

	Brief description	Туре	part no.
Mounting syst	tems		
8	<ul> <li>Description: Flexi Loop fixing clip</li> <li>Dimensions (W x H x L): 15 mm x 32 mm x 21 mm</li> <li>Packing unit: 1 piece</li> <li>Suitable for: Flexi Loop</li> </ul>	C-Fix bracket	2068830

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

## **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

