



## LED system light and workplace lighting



|                                   |                                         |
|-----------------------------------|-----------------------------------------|
| <b>Product-Nr.</b>                | 110914-21                               |
| <b>EAN:</b>                       | 4260556623382                           |
| <b>Model:</b>                     | UNILED SL DC                            |
| Order number:                     | 110914-21                               |
| <b>Model:</b>                     | UNILED SL DC                            |
| <b>Type:</b>                      | LED system light and workplace lighting |
| <b>Illuminant:</b>                | SMD LED                                 |
| <b>Power consumption:</b>         | ~12 W                                   |
| <b>Lamp luminous flux:</b>        | 1899 lm                                 |
| <b>Lamp luminous efficiency:</b>  | ~155 lm/W                               |
| <b>Light distribution:</b>        | Direct                                  |
| <b>Light colour:</b>              | 5700K 3-step MacAdam                    |
| <b>Colour rendering (Ra):</b>     | >85                                     |
| <b>Connected load:</b>            | 24V DC $\pm$ 10%                        |
| <b>Connection (connector):</b>    | M12 A-coded                             |
| <b>Degree of protection:</b>      | IP50                                    |
| <b>Class of protection:</b>       | III                                     |
| <b>Glare control:</b>             | Microprisms                             |
| <b>Beam angle (optics):</b>       | 100°                                    |
| <b>Operating temperature:</b>     | -10 °C - +60 °C (14 °F - 140 °F)        |
| <b>Lamps lifetime:</b>            | > 100,000 h (L80/B10)                   |
| <b>Housing material:</b>          | aluminium                               |
| <b>Cover material:</b>            | micro prisms cover                      |
| <b>Height [B] x Width [C]:</b>    | 35 mm x 85 mm (~1,38" x ~3,35")         |
| <b>Length [A]:</b>                | 295 mm (~11,61")                        |
| <b>Weight (net):</b>              | 550 g (~19 oz)                          |
| <b>Gross weight:</b>              | 850 g (~30 oz)                          |
| <b>Risk group (DIN EN 62471):</b> | Free group                              |
| <b>Markings:</b>                  | CE, UKCA, ETL Listed (5003529)          |
| <b>Dimmable:</b>                  | Optional via accessories                |
| <b>Mounting accessories:</b>      | Optional                                |
| <b>Made in:</b>                   | Germany                                 |
| <b>Feature:</b>                   | high light diffusion                    |