



profiled light with adjustable pull pendants

Product-Nr.	150714-05
EAN:	4260556625775
Model:	PROFILED Suspension Pendant

Order number: 150714-05

Model: PROFILED Suspension Pendant

Type: profiled light with adjustable pull pendants

Illuminant: SMD LED

Total output incl. driver: ~27 W

Power consumption: ~23 W

Lamp luminous flux: 3674 lm

Lamp luminous efficiency: ~155 lm/W

Light distribution: Direct

Light colour: 5700K 3-step MacAdam

Colour rendering (Ra): >85

Connected load: 120-277V AC $\pm$ 10%, 50-60 Hz

Power supply: Integrated

Connection (connector): 1 pair of tension pendants, ceiling transfer point, 3 m (~9,84 ft.) cable with open cable ends

Degree of protection: IP40

Class of protection: I

Glare control: Microprisms

Beam angle (optics): 100°

Operating temperature: -10 °C - +45 °C (14 °F - 113 °F)

Lamps lifetime: > 100.000 h (L80/B10)

Housing material: aluminium

Cover material: plastics

Height [B] x Width [C]: 65 mm x 45 mm (~2,56" x ~1,77")

Length [A]: 1000 mm (~39,37")

Weight (net): 3040 g (~107 oz)

Gross weight: 3740 g (~132 oz)

Risk group (DIN EN 62471): Free group

Markings: CE, UKCA

Mounting accessories: Optional

Made in: Germany

