



profiled light with adjustable pull pendants

Product-Nr.	150814-05
EAN:	4260556625799
Model:	PROFILED Suspension Pendant
Order number:	150814-05
Model:	PROFILED Suspension Pendant
Type:	profiled light with adjustable pull pendants
Illuminant:	SMD LED
Total output incl. driver:	~34 W
Power consumption:	~30 W
Lamp luminous flux:	4676 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Connected load:	120-277V AC $\pm$ 10%, 50-60 Hz
Power supply:	Integrated
Connection (connector):	1 pair of tension pendants, 1x 90-305V ceiling transfer point, 3 m (~9,84 ft.) cable with open cable ends
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-10 °C - +45 °C (14 °F - 113 °F)
Lamps lifetime:	> 100.000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (~2,56" x ~1,77")
Length [A]:	1200 mm (~47,24")
Weight (net):	3840 g (~135 oz)
Gross weight:	4640 g (~164 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Dimmable:	No
Mounting accessories:	Optional
Made in:	Germany

