


LED tube luminaire



Product-Nr.	158010-02
EAN:	4260556628370
Model:	INROLED 50 CleanPro ECO
Order number:	158010-02
Model:	INROLED 50 CleanPro ECO
Type:	LED tube luminaire
Illuminant:	SMD LED
Power consumption:	~6,5 W
Lamp luminous flux:	1002 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded
Number of poles:	3
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-30 °C - +70 °C (-22 °F - 158 °F)
Storage temperature:	-30 °C - +80 °C (-22 °F - 176 °F)
Lamps lifetime:	> 100.000 h (L80/B10)
Housing material:	Tube – Polycarbonate, matt, shatterproof with Ecolab coating Cap/M12 connector – V4A stainless steel
Impact resistance:	IK09
Height [B] x Width [C]:	Ø 50 mm (~1,97")
Length [A]:	305 mm (~12,01")
Weight (net):	560 g (~20 oz)
Gross weight:	705 g (~25 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Dimmable:	External PWM <5 kHz
Made in:	Germany
Feature:	Food+Beverage suitable: Ecolab certified, HACCP certificate