





Desktop power supply with M12 socket on cable, additional IEC cable with SCHUKO plug



PIN 3 GND
PIN 4 V DC



Product-Nr.	210100-02
EAN:	4260556624914
Model:	Constant Voltage Power Supply
Order number:	210100-02
Model:	Constant Voltage Power Supply
Type:	Desktop power supply with M12 socket on cable, additional IEC cable with SCHUKO plug
Cable length:	~1,8 m (~5,91 ft.)
Number of poles:	4
Ambient temperature:	-30°C -> +70 °C (-22 °F -> 158 °F)
Nominal output voltage:	24V DC
Max. output power:	60 W
Output current:	2500 mA
Voltage range:	90...264V AC
Input frequency:	47...63 Hz
Max. input current (230 V AC):	1000 mA ± 1%
Max. Input current (115 V AC):	1400 mA ± 1%
Output voltage setting range:	22...27V DC
Overvoltage protection:	25,2 - 32,4V DC
Connection to a light:	M12 socket, A-coded
Efficiency at full load:	90,50%
P no:	<0,075 W
Dimensions (mm):	125 mm x 50 mm x 31,5 mm (~4,92" x ~1,97" x ~1,24")
Overtemperature protection:	75 °C ± 5 °C
Humidity during operation:	20...90% (non-condensing)
Weight (net):	250 g (~9 oz)
Gross weight:	300 g (~11 oz)
Markings:	EISA 2007/DoE, NRCan, Korea K-MEPS, AU/NZ MEPS, EU, CE, UKCA
Dimmable:	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
Protective devices:	short circuit protection, overload protection, overvoltage protection, overtemperature protection
Feature:	Overvoltage and overtemperature protection