



## Switching power supply with M12 socket and connection via a plug



|                                |                                                                  |
|--------------------------------|------------------------------------------------------------------|
| <b>Product-Nr.</b>             | 210100-11                                                        |
| <b>EAN:</b>                    | 4260556624891                                                    |
| <b>Model:</b>                  | Constant Voltage Power Supply                                    |
| Order number:                  | 210100-11                                                        |
| <b>Model:</b>                  | Constant Voltage Power Supply                                    |
| Type:                          | Switching power supply with M12 socket and connection via a plug |
| Cable length:                  | 0,30 m (~0,98 ft.)                                               |
| Number of poles:               | 4                                                                |
| Ambient temperature:           | -30°C -> +70 °C (-22 °F -> 158 °F)                               |
| Nominal output voltage:        | 24V DC                                                           |
| Max. output power:             | ~60 W                                                            |
| Output current:                | 2500 mA                                                          |
| Voltage range:                 | 90...264V AC                                                     |
| Input frequency:               | 47...63 Hz                                                       |
| Max. input current (230 V AC): | 1000 mA ± 1%                                                     |
| Max. Input current (115 V AC): | 1400 mA ± 1%                                                     |
| Output voltage setting range:  | 22...27V DC                                                      |
| Overvoltage protection:        | 25,2... 32,4V DC                                                 |
| Connection to a light:         | M12 socket, A-coded                                              |
| Overtemperature protection:    | 75 °C ± 5 °C                                                     |
| Humidity during operation:     | 20...90% (non-condensing)                                        |
| Weight (net):                  | 600 g (~21 oz)                                                   |
| Gross weight:                  | 700 g (~25 oz)                                                   |
| Markings:                      | CE                                                               |
| Feature:                       | Connection cable can be disconnected via screw coupling          |