



48 x 96mm

Features :

- True RMS Measurement
- For 1 Ø 2 Wire Electrical Network

Certifications :

Display Specifications

Display	7 segment LED Display
Digits	4
Digit Height	0.56" (14.2mm)
Display Range	0 - 4960A

Input Specifications

Electrical Connection	1 Ø-2 wire
Input Current Range	50mA - 5A AC
Continuous Max. Input Current	6.2A AC
Overrange Indication	"Or" for input > 6.2A AC
Frequency Range	50 / 60Hz
Resolution	0.001, 0.01, 0.1, 1A (Depending upon CT primary setting)
Accuracy	±0.5% of F.S
Input Burden	0.5 VA @ 5A AC (CT Input)
Sampling Rate	3 samples / second
Dielectric withstand Voltage	2kV AC between auxiliary supply & measuring input
Rated Impulse withstand Voltage	3.5kV (1.2/50µs)

Auxiliary Supply Specifications

Auxiliary Supply	240V AC ±20%, (50 / 60Hz) 110V AC ±20%, (60Hz)
Power Consumption	5VA max

Settable Parameters

CT Primary Setting	5, 10, 20, 30, 40, 50, 60, 75, 80, 100, 150, 200, 250, 300, 400, 500, 600, 800, 1000, 1200, 1500, 1600, 2000, 2500, 3000, 4000
CT Secondary Setting	5A Fixed


Environmental Specifications

Temperature	Operating: -10 to +55°C Storage: -20 to +75°C
Humidity (non-condensing)	Upto 95% RH

Mechanical Specifications

Mounting	Panel mount
Weight	170 gms

Dimensions



Terminal Connections

AC Models (CT Type[§]) 	
AC Models (Direct Type[§]) 	
Cable Size (AWG): 20 to 14 ; Tightening Torque (Lb-inch): 6.018 to 6.992	
Cable Size (mm²): 0.5 to 2.5 ; Tightening Torque (N-m): 0.68 to 0.79	

*NOTE

- 1) CT Type: There is an internal CT with CT setting. Above 5A(0-5A model) external CT is required.
- 2) Direct Type: Input is directly connected to the input of the unit.

Compliance

Applicable EMI / EMC Standards		
Product Standard : IEC 61326-1		
Category		Standards Compliance
ESD Immunity	IEC 61000-4-2	Level IV (Air discharge : 15kV), (Contact Discharge : -8kV)
Surge Immunity	IEC 61000-4-5	+/- 2kV common mode, (Line to ground) +/- 1kV differential mode, (Line to Line)
Radiated Susceptibility	IEC 61000-4-3	Level III, 80 to 1000MHz (10V/m) Level II, 1.4GHz to 2GHz (3V/m) Level I, 2GHz to 2.7GHz (1V/m)
Conducted Susceptibility	IEC 61000-4-6	Level II (3V/m)
Voltage Dips and Interruptions	IEC 61000-4-11	Dips : 0% residual voltage / 1 cycle (Criteria B), 40% residual voltage / 10 cycles 50Hz / 12 cycles 60Hz (Criteria C) 70% residual voltage / 25 cycles 50Hz / 30 cycles 60Hz (Criteria C) Interruptions : 0% residual voltage / 250 cycles 50Hz / 300 cycles 60Hz (Criteria C)
Conducted Emission	CISPR-11	
Radiated Emission	CISPR-11	
Electrical Fast Transient	IEC 61000-4-4	Level III (2kV)

Ordering Information

Product Code	Supply Voltage	Certification
MA12	240V AC	---
MA12-CE	240V AC	CE
MA12-CU	240V AC	CE 
MA12-20A-AC	240V AC	---
MA12-75mV-DC	240V AC	---
MA12-110V-CU	110V AC	CE 
MA12-100mV-DC-110V-CU	110V AC	CE 

Note:

- CT Type** : There is an internal CT with CT setting (5-4000A).
For current input >5A, external CT is required.
- Direct Type** : Input is directly connected to the unit.