

Technical Information:


Material	: AISi12, as per DIN EN 1706
Components	: Fastening threads M4 / M6 in the enclosure bottom
Ingress protection	: IP66 / IP67 / IP68 as per IEC 60529
Gasket	: Neoprene gasket (-40°C to +110°C)
Lid Screws	: Stainless Steel 1.4301 (A2), captive
Surface	: Painted / Non-Painted
Standard Color	: RAL 7001, 7031, 7032, 7035, 7038 Black RAL 9004



Optionally available:

External Mounting Bracket	: Stainless Steel 1.4301 (A2)
Mounting Plates	: Sheet Steel, galvanized
Gasket	: Silicon gasket (-50°C to +135°C)
Surface	: Special Colours on request
Certified	: CE, UL, RMRS, RETIE & RoHS

ALUMINIUM STANDARD ENCLOSURE



Product Code	Y-->Yes			Standard Accessories							Certification				
	External Dimensions (mm)			Mounting Plate	M6 External Brackets	External Hinges	Internal Hinge	DIN rail for terminals		Silicon Gasket	IP 66	IP 67	IP 68	Impact Test IK	EMC
	Length	Width	Height					TS15	TS35						
RJ01	50	45	30	-	-	-	-	-	-	Y	Y	Y	Y	IK09	Y
RJ02	98	64	34	-	-	-	-	-	-	Y	Y	Y	Y	IK09	Y
RJ03	150	64	34	-	-	-	-	-	-	Y	Y	Y	Y	IK09	Y
RJ04	58	64	34	-	-	-	-	-	-	Y	Y	y	Y	IK09	Y
RJ05	75	80	57	Y	-	-	-	Y	-	Y	Y	Y	Y	IK09	Y
RJ06	125	80	57	Y	-	-	-	Y	-	Y	Y	Y	Y	IK09	Y
RJ07	175	80	57	Y	-	-	-	Y	-	Y	Y	Y	Y	IK09	Y
RJ08	250	80	57	Y	-	-	-	Y	-	Y	Y	Y	Y	IK09	Y
RJ09	100	100	81	Y	Y	Y	-	Y	-	Y	Y	Y	Y	IK09	Y
RJ10	160	100	81	Y	Y	Y	-	Y	-	Y	Y	Y	Y	IK09	Y
RJ11	122	120	81	Y	Y	Y	-	-	Y	Y	Y	Y	Y	IK09	Y
RJ21	220	120	81	Y	Y	Y	-	-	Y	Y	Y	Y	Y	IK09	Y
RJ22	122	120	91	Y	Y	Y	-	-	Y	Y	Y	Y	Y	IK09	Y
RJ12	220	120	90	Y	Y	Y	-	-	Y	Y	Y	Y	Y	IK09	Y
RJ36	140	140	90	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ37	200	140	90	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ15	160	160	91	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ13	260	160	90	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ14	360	160	90	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ28	180	180	100	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ29	280	180	100	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ19	200	230	110	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ17	280	230	110	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ18	330	230	111	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ30	200	230	180	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ20	330	230	180	Y	Y	Y	Y	-	Y	Y	Y	Y	Y	IK09	Y
RJ31	400	310	110	Y	Y	Y	Y	-	Y	Y	Y	Y	-	IK09	Y
RJ32	400	310	180	Y	Y	Y	-	-	Y	Y	Y	Y	-	IK09	Y
RJ33	600	310	110	Y	Y	Y	-	-	Y	Y	Y	Y	-	IK09	Y
RJ34	600	310	180	Y	Y	Y	-	-	Y	Y	Y	Y	-	IK09	Y
RJ35	400	230	110	Y	Y	Y	-	-	Y	Y	Y	Y	-	IK09	Y

Note: Viton gasket available on request

Approvals:



Assembly of Accessories:

Mounting Plates, Mounting Brackets, Internal Hinges, External Hinges.

