



Figure similar

accessories for switch disconnecter with fuses, in-line design, for size NH1, calibrated transformer, 100/5 A, Cl. 0.5, calibrated, 1.5 VA feed-through opening 15.2 mm

Model	
product brand name	SETRON
product designation	Current transformer
design of the product	accessory for switch disconnecter with fuses 3NJ6
product quality calibrated	Yes
operating apparent power rated value	1.5 VA
operating voltage	0.72 kV
insulation voltage rated value	3 kV
designation of overcurrent limiting factor	FS 5
operational current rated value maximum	120 A
current	
• at input rated value	100 A
• at output rated value	5 A
accuracy class of the current transformer	class 0.5
value range of the operating frequency	50/60 Hz
Protection class	
protection class IP	IP20
suitability for use for outside use	No
suitability for use for interior use	Yes
product feature touch protection	Yes
Short circuit	
formula for rated short-time thermal current (I _{th}) for 1 s according to IEC 61869-2	60 x I _{pr}
formula for rated dynamic current (I _{dyn}) according to IEC 61869-2	2.5 x I _{th} or 150 x I _{pr}
Connections	
type of electrical connection at output	screw-type terminals
Mechanical Design	
width of the push-through bus bar	
• at 1 bus bar maximum	17 mm
• in case of 2 bus bars maximum	6 mm
fastening method	mounting
diameter of inlet opening	15.2 mm
outer diameter of the push-through conductor maximum	15 mm
Net Weight	0.19 kg
Environmental conditions	
ambient temperature during operation	
• minimum	-10 °C

• maximum

55 °C

Approvals Certificates

Environment	General Product Approval			Test Certificates	
Environmental Confirmations		Confirmation	 EG-Konf.		Type Test Certificates/Test Report

other

[Confirmation](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NJ6930-3BD23>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NJ6930-3BD23>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ6930-3BD23

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>

last modified:

6/1/2026 

