

Extension Unit 12" KP12 PN for mounting on all fully IP65-enclosed 16:9 HMI/IPC devices. For the flexible installation of operator controls, 3 mounting positions, 3 operator controls equippable; Connection via PROFINET (without equipment)



General information	
Product type designation	Extension Unit 12" KP12 PN
Control elements	
Version of actuating element	1x Key Panel 12
Operating principle of the actuating element	Tactile feedback
Functional lighting	Yes; Freely configurable colors: Red, green, blue, white, yellow
With parameterizable keys	Yes
Connection type	
Connection type of the safety-related contacts (emergency stop)	8-pin connector
Installation type/mounting	
Mounting	For mounting on a 16:9 HMI / IPC PRO device (lower part)
Mounting type	Screwed joint
Rack mounting	No
Front mounting	No
Number of slots for command devices and signaling units	3
RFID reader can be installed	Yes; SIMATIC RF200 Access Control Reader RF1060R
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	150 mA; without load
Power	
Active power input, typ.	3.6 W; Additional 0.1 W per operator control with LED or 0.5 W per RGB illuminated pushbutton or 2.6 W per KP12
Interfaces	
Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
Number of PROFINET interfaces	2; Incl. switch
Protocols	
PROFINET	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
Degree and class of protection	
IP (all-round)	IP65
Standards, approvals, certificates	
CE mark	Yes

UL approval	Yes		
cULus	Yes		
RCM (formerly C-TICK)	Yes		
KC approval	Yes		
EAC (formerly Gost-R)	Yes; EAC		
Suitable for safety functions	Yes; e.g. installation of emergency stop		
Ambient conditions			
Ambient temperature during operation			
• min.	0 °C		
• max.	50 °C		
Ambient temperature during storage/transportation			
• min.	-20 °C		
• max.	60 °C		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	2 000 m		
Relative humidity			
• Operation, max.	90 %; no condensation		
Cables			
Cable length	30 m; Max. for emergency stop		
Mechanics/material			
Material			
• Aluminum	Yes		
Enclosure material (front)			
• Aluminum	Yes; Knockout covered with black film		
Dimensions			
Width	313 mm		
Height	99 mm		
Depth	100.65 mm		
Weights			
Weight (without packaging)	2.2 kg		
Scope of supply			
Delivery quantity in pieces	1		
Components included	Power supply connectors and 8-pole plug-in connectors for safety-related inputs		
Classifications			
		Version	Classification
	eClass	16	27-33-02-92
	eClass	14	27-33-02-92
	eClass	12	27-33-02-92
	eClass	9.1	27-33-02-92
	eClass	9	27-33-02-92
	eClass	8	27-24-92-03
	eClass	7.1	27-24-92-03
	eClass	6	27-24-92-03
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03
Approvals / Certificates			
General Product Approval			EMV

[Manufacturer Declaration](#)



[China RoHS](#)



Industrial Communication

[PROFINET](#)

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

3/12/2024 