



SIMATIC HMI IRD400 Infrared display unit PROFINET interface 3x 7-7-segment display

General information			
Product type designation		IRD400 infrared display unit	
Display			
Design of display		3 x seven-segment display	
Screen diagonal		3.8 in	
Display width		140 mm	
Display height		116 mm	
Number of colors		1; red	
Supply voltage			
Type of supply voltage		DC	
Rated value (DC)		24 V	
permissible range, lower limit (DC)		20.4 V	
permissible range, upper limit (DC)		28.8 V	
Input current			
Current consumption, max.		1.2 A	
Interfaces			
Number of industrial Ethernet interfaces		2	
Classifications			
		Version	Classification
	eClass	16	27-33-02-92
	eClass	14	27-33-02-92
	eClass	12	27-33-02-92
	eClass	9.1	27-33-02-92
	eClass	9	27-33-02-92
	eClass	8	27-24-92-03
	eClass	7.1	27-24-92-03
	eClass	6	27-24-92-03
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03
Approvals / Certificates			
General Product Approval			

[Manufacturer Declaration](#)



[China RoHS](#)



EMV



Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

8/22/2025 