



Figure similar

Article No. : 6SL3121-1TE31-3AA3

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
DC link voltage	DC 510 ... 720 V
Electronics power supply	DC 24 V -15 % / +20 %
Current demand, max.	1.50 A
DC-link current I _d	158.0 A
Output current	
Rated value I _N	132.0 A
Base load current I _H	105.0 A
For S6 duty (40%) I _{S6}	150.0 A
I _{max}	210.0 A
Type rating ²⁾	
Based on I _N	71.0 kW
Based on I _H	57.0 kW
Rated pulse frequency	4.00 kHz
Current carrying capacity	
DC link busbars	200 A
24 V busbars	20 A
DC link capacitance	2,820 µF
Ambient conditions	
Installation altitude (without derating)	1,000 m (3,281 ft)
Cooling ⁸⁾	External air cooling
Cooling air requirement	0.144 m³/s
Ambient temperature	
During operation	0 ... 40 °C (32 ... 104 °F)

Connections	
Motor end	
Version	M8 bolt (X1)
Conductor cross-section	2.5 ... 120 mm² (14 ... -3 AWG)
PE connection	M8 Screw
Max. motor cable length	
Shielded	100 m (328 ft)
Unshielded	150 m (492 ft)
Standards	
Compliance with standards	CE, cULus
Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1
Mechanical data	
Line side	
Width	300.00 mm (11.81 in)
Height	629.00 mm (24.76 in)
Depth	226.00 mm (8.90 in)
Degree of protection	IP20 / UL open type
Type of construction	Booksize
Net weight	27.2 kg (59.97 lb)
General tech. specifications	
Sound pressure level (1m)	73.0 dB
Power loss, max. ⁹⁾	1.00 kW

²⁾Rated output of a typical standard asynchronous motor at 400 V 3 AC

⁸⁾Power units with intensified air cooling thanks to integrated fan

⁹⁾Power loss of the Motor Module with rated power including losses of the 24 V DC electronics power supply